



Certification Record

CUSTOMER	CLASS	FILE
Phoenix Contact Inc. P.O. Box 4100, Harrisburg Pennsylvania 17111-0100 USA	6228-01 WIRE CONNECTING DEVICES-Terminal Assemblies	013631_0_000
Refer to Class Description for program details		

TO THE REQUIREMENTS OF CSA STANDARD C22.2 NO 158-1987 AND E.C.N. 584:

Type	Wire range	Current / gnd	Voltage, Group	Torque(lb-in)	Note
AGK10-UKH 50, 95, 150, 240	24-6	65	600	20	1
AKG16	18-6	65	-	25	19
AKG35	18-2	135	-	50	19
BAK-M12 KER	Term	-	600	-	1
BAK-M12 KRI	Term	-	600	-	1
BAK-M16 KRI	Term	-	600	-	1
BK4	28-12	25	600	6.2	1
BK4-FS(8-2.8 - 0.8)	28-12/ 28-14	20	600	6.2	1,12
BK4-FS/FS(4-8.2 - 0.8)	28-14	20	600	-	1,12
BK10	26-8	55	600	14.2	1
BK16	24-6	80	600	14.2	1
BK35	18-2	140	600	50	1
BK70/E	4-3/0	200	600	100	1,11
BK240/E	2-500MCM	400	600	270	1,11
DFK-2.8	22-12	15/10	150/300	6.2	15
DFK2.8-FRONT2.5	22-12	15	300	5	15
DFK-4.8	22-12	15/10	150/300	6.2	15
DFK 4-PE	26-10	Grounding	-	5	15
DFK 4-SI(5x20)BK	28-10	8	300	5	5,15
DFK 4-SI(6.3x32)	28-10	8	300	5	5,15
DFK5-9.5	22-10	30	300	5	15
DFK/DP-2.8	22-12	15/10	150/300	6.2	15
DFK/DP-2.8-FRONT2.5	22-12	15	300	5	15
DFK/DP-4.8	22-12	15/10	150/300	6.2	15
DFK-MC1.5/X-GF-3.81	-	8	150	-	2, 15
DFK-MSTB2.5	-	10	300	-	15, 20

DFK-PC4/X-G-7.62-LOE	30-12	20	300	-	15
DFK-PC4/X-GF-7.62	28-10	20	300	5	15
DFK-TP(1.6X0.8)	22-12	15/10	150/300	6.2	15
DFK-TP(2.4X0.8)	22-12	15/10	150/300	6.2	15
DFK-WW(1X1)	22-12	10	300	6.2	15
DIK1.5	28-14	15	300	5	1,17
DIKD1.5	28-14	15	300	5	1,17
DIKD1.5-PV	28-14	15	300	5	1,17
DIKD 1.5-TG	28-14	15	300	5	1,17
DLK2.5/PE	28-12	15	300	5	1
DLKB2.5/PE	28-12	15	300	5	1
DMKDS2.5	28-14	10	300	5	2
DMKDS-FS	Q.C.	10	300	-	2,12
DMKDS-FSI	Q.C.	10	300	-	2,12
DOK1.5(-LA)	28-14	15	300	5	1,17
DOK1.5-2D	28-14	15	300	5	1,17
DOK1.5-TG	28-14	15	300	5	1,17
DOKD1.5-TG	28-14	15	300	5	1,17
EMKDS2.5/X-5.08	28-12	10	300	5	2
FAA40	28-12	10	300	5	2
FAA40/20	28-12	10	300	5	2
FKC2,5/...-ST	24-12	12	300		
FKC2,5/...-STF	24-12	12	300		
FKCT2,5/...-ST	24-12	12	300		
FKCT2,5/...-STF	24-12	12	300		
FFKDS/H-2.54	20 Sol	6	150	-	2
FFKDS/H-3.81	26-18	10	150	-	2
FFKDS/H1-5.08	16 Sol	10	300	-	2
FFKDS/V-2.54	20 Sol	6	150	-	2
FFKDS/V-3.81	26-18	10	150	-	2
FFKDS/V1-5.08	16 Sol	10	300	-	2
FFKDS/V2-5.08	16 Sol	10	300	-	2
FFKDSA/H1-7.62	16 Sol	10	300	-	2
FFKDSA1/H-5.08	20 Sol	6	150	-	2
FFKDSA/V1-7.62	16 Sol	10	300	-	2
FFKDSA/V2-7.62	16 Sol	10	300	-	2
FFKDSA1/H-6.35	26-18	10	150	-	2
FFKDSA1/V-5.08	20 Sol	6	150	-	2
FFKDSA1/V-6.35	26-18	10	150	-	2
FK-MCP1.5-ST-3.81	28-16	8	300	-	13
FK-MCP1.5-ST-5.08	28-16	8	300		
FK-MCP1.5-STF-3.81	28-16	8	300	-	13
FK-MCP1.5-STF-5.08	28-16	8	300		
FK-MSTBP 1.5/X-ST-5.08	24-14	10	300	-	13

FK1.5	22-14	15/10	150/300	-	1,6,13
FKMT1.5	22-14	15/10	150/300	-	1,6,13
FKDS-5.08	16 Sol	10	300	-	2
FKDSA-7.62	16 Sol	10	300	-	2
FKDSV-5.08/SA-5.08	16 Sol	10	300	-	2
FKDSV-5.08/SA-10.16	16 Sol	10	300	-	2
FKDSVA-7.62/SA-5.08	16 Sol	10	300	-	2
FKDSVA-7.62/SA-10.16	16 Sol	10	300	-	2
FL2-H, -S, -SH, -V, -VS, (-7.5)	22-14	10	300	-	2, 10, 12
FL3-H, -S, -SH, -V, -VS	22-14	10	300	-	2, 10, 12
FLKM40	28-12	1	125	5	1, 23
FRONT2.5-H/SA5,/SA10	24-12	10	300	5	2
FRONT2.5-V/SA5,/SA10	24-12	10	300	5	2
FRONT4-H-7.62,-6.35	22-10	30	300	6.2	2
FRONT4-V-7.62,-6.35	22-10	30	300	6.2	2
FRONT-GMSTB2.5/ X-ST(F)-7.62	22-12	10	300	5	13
FRONT-MC1.5/ X-ST(F)-3.81	28-16	8	300	2.5	13
FRONT-MC1.5/ X-ST(F)-5.08	28-16	8	300	2.5	13
FRONT-MSTB2.5/ X-ST(F)(-5.08)	22-12	10	300	5	13
FRONT-MSTB2.5/ X-ST(F)(-5.08)	28-16	8	300	2.5	13
G5/X	28-10	30	300	5	6
G10/X	22-6	65	600	20	-
GFKC2,5/...-ST	24-12	12	300		
GFKC2,5/...-STF	24-12	12	300		
GIC2.5/X-G-7.62	-	10	300	-	2, 13
GIC2.5/X-GF-7.62	-	10	300	-	2, 13
GIC2.5/X-ST-7.62	28-12	10	300	5	13
GIC2.5/X-STF-7.62	28-12	10	300	5	13
GIC2.5/X-STGF-7.62	28-12	10	300	5	13
GKDS	22-12	10	300	5	2
GKDS/E	22-12	10	300	5	2
GMKDS1.5/X(-7.62)	28-14	10	300	5	2
GMKDS 3/X (-7.62)	28-12	10	300	5	2
GMKDSN1.5/X-7.62	28-14	10	300	2.5	2
GMSTB-LA/RT	-	-	24	-	2, 13
GMSTB2.5/X-G (-7.62)	-	10	300	-	2, 13
GMSTB2.5/X-G(-7.62)-LA	-	10	300	-	2, 13
GMSTB2.5/X-GF-7.62	-	10	300	-	2, 13
GMSTB2.5/X-G-15.24-1,-2	-	5	600	-	2, 13

GMSTB2.5/X-ST (-7.62)	28-12	10	300	5	13
GMSTB2.5/X-ST-15.24-1,-2	28-12	5	600	5	13
GMSTBA2.5/X-G (-7.62)	-	10	300	-	2, 13
GMSTBA2.5/X-G(-7.62)-LA	-	10	300	-	2, 13
GMSTBA2.5/X-G-15.24-1,-2	-	5	600	-	2, 13
GMSTBHK2.5/10-G(-7.62)	28-12	10	300	5	1, 13
GMSTBP2.5/X-ST-7.62	28-12	10	300	5	13
GMSTBV2.5/X-G (-7.62)	-	10	300	-	2, 13
GMSTBV2.5/X-GF-7.62	-	10	300	-	2, 13
GMSTBV2.5/X-G-15.24-1,-2	-	5	600	-	2, 13
GMSTBVA2.5/X-G (-7.62)	-	10	300	-	2, 13
GMSTBVA2.5/ X-G-15.24-1,-2	-	5	600	-	2, 13
GMVSTBR2.5/X-ST(-7.62)	28-12	10	300	5	13
GMVSTBR2.5/X-STF (-7.62)	28-12	10	300	5	13
GMVSTBW2.5/X-ST (-7.62)	28-12	10	300	5	13
GMVSTBW2.5/X-STF (- 7.62)	28-12	10	300	5	13
GSK-KER,-KRI	24-10	40	600	14.2	1
GSK/S-KER,-KRI	26-12	25	600	6.2	1
GSMKDS1.5/X(-7.62)	28-14	10	300	5	2
GSMKDS 3/X(-7.62)	28-12	10	300	5	2
GSMKDSN1.5/X-7.62	28-14	10	300	2.5	2
HC-BX-EBUS(C)	20-14	16	600	5(-)	-
HC-BX-ESTS(C)	20-14	16	600	5(-)	-
HC-HSB6-EBUS	20-10	35	600	15	-
HC-HSB6-ESTS	20-10	35	600	15	-
HCC4-F	28-10	20	300	5	-
HCC4-M	28-10	20	300	5	-
HC-D	22-16	10	300	N/A	-
HC-KA	22-12	9	300	5	-
HC-KA-D	22-12	5	300	5	-
HDFK4	22-10	30	300	5	15
HDFK10	22-6	65	300	20	15
HDFK10-VP	22-6	65	300	20	15
HDFK25	8-4	100	600	35	15
HDFK25-VP	8-4	100	600	35	15
HDFK25-Green/Yellow	8-4	100	600	35	15
HDFK25-DP	8-4	100	600	35	15,22
HDFK50-VP	6-1/0	125	600	75	29-32
HDFK50	6-1/0	125	600	75	15
HDFK50-DP	6-1/0	125	600	75	29-32
HDFK50-VP-DF	6-1/0	125	600	75	29-32
HDFK50-GNYE	6-1/0	125	600	75	29-32
HDFK50-GNYE-DP	6-1/0	125	600	75	29-32

HDFKV50	6-1/0	125	600	75	29-32
HDFKV50-DP	6-1/0	125	600	75	29-32
HDFKV50-VP	6-1/0	125	600	75	29-32
HDFKV50-VP-DP	6-1/0	125	600	75	29-32
HDFKV50-GNYE	6-1/0	125	600	75	29-32
HDFKV50-GNYE-DP	6-1/0	125	600	75	29-32
HDFKV10	22-6	65	300	20	15
HDFKV10-TWIN	22-6	65	300	20	15
HDFKV10-TWIN-DP	22-6	65	300	20	15
HDFKV95(-F)	2-4/0	200	600	250	15
HDFKV95(-F)	2-4/0	200	600	250	15
HDFKV4	22-10	30	300	5	15
HDFKV25-DP-GNYE	8-4	100	600	35	15
HDFKV25	8-4	100	600	35	15
HDFKV25-DP	8-4	100	600	35	15
HDFKV25-TWIN(-DP)	8-4	100	600	35	15
HK4-FS	28-12/ 28-14	20	600	6.2	1,12
HK4-FS/FS	28-14	20	600	-	1,12
HK4-Loer/FS	28-18/ 28-14	5	150	-	1,12
HSK/S 2000 KRI	26-12	25	600	6.2	1
HUK200-S/KH/KH	3/0	200	600	270	1
HUK400-S/KH/KH	500MCM	400	600	270	1
IC2.5/X-G-5.08	-	10	300	-	2,13
IC2.5/X-GF-5.08	-	10	300	-	2,13
IC2.5/X-ST-5.08	28-12	10	300	5	13
IC2.5/X-STF-5.08	28-12	10	300	5	13
IC2.5/X-STGF-5.08	28-12	10	300	5	13
ICC2.5/X-STZ-5.08	20-14	10	300	-	-
ICC2.5/X-STZF-5.08	20-14	10	300	-	-
ICC2.5/X-STZFD-5.08	20-14	10	300	-	-
ICV2.5/X-G-5.08	-	10	300	-	2,13
ICV2.5/X-GF-5.08	-	10	300	-	2,13
ICVK2.5/X-ST-5.08	28-12	10	300	5	13
IDC 0.3/X-3.81	28-22	5	300	-	2
IDC 0.5-DL	28-20	10	300	-	2
IDC 0.8-DP	28-18	10	300	-	2
K2.5,/E,/M	28-12	25	600	6.2	1,11
K2.5-FS/FS,/E-FS/FS	22-14	20	600	-	1,11,12
K2.5-FSR,/E-FSR	22-12	20	600	6.2	1,11,12
K2.5-Loer,/E-Loer	18	10	150	6.2	1,11,16
K2.5-Loe/Loe, /E-Loe/Loe	22-18	10	150	-	1,11,16
K3, /E, /M	28-12	25	600	6.2	1,11
K4, /E, /M	28-12	25	600	6.2	1,11

K4-FS/FS, /E-FS/FS	22-14	20	150	-	1,11,12
K4-FSR, /E-FSR	28-12	20	150	6.2	1,11,12
K4-Loe/Loe, E-/Loe/Loe	22-16	15	150	-	1,11,16
K4-Loer, /E-Loer	28-12	15	150	-	1,11,16
K4-T, -T-P/P	28-12	15	150	6.2	1,6,13
K4-T-Loe/Loe-P/P	22-16	15	150	-	1,6,13,16
K4-T-Loer-P/P	28-12	15	150	6.2	1,6,13,16
K4-TG	28-12	15	600	6.2	1,13
K5, /E, /M	28-10	40	600	6.2	1,11
K10, /E, /M	26-8	55	600	14.2	1,11
K16, /E	24-6	80	600	14.2	1,11
K25/E	18-4	100	600	23	1,11
K35/E	18-2	140	600	50	1,11
K70/E	4-3/0	200	600	100	1,11
K240/E	2-500MCM	400	600	270	1,11
KDS	24-12	10	50/300	5	2,9,11
KDS2.5	24-12	10	300	5	2
KDS3	24-12	10	300	5	2
KDS3-MT	24-12	10	300	5	2,13
KDS3-Si	24-12	10	300	5	2,5,13
KDS4	28-10	30	300	5	2
KDS10, -PE	18-6	65	300	14.2	2
KDSP1.5/X	28-14	10	300	5	2
KDSP4	28-10	30	300	5	2
KEK/F1635 KER, KRI	18-2	140	600	50	1
KEK/F2570 KER, KRI	12-3/0	260	600	100	1
KEK/F50120 KER, KRI	250MCM	340	600	200	1
MBK	28-12	25	150	5	1
MBK2.5/E	28-12	20	300	5	1
MBK2.5/E-PE	28-12	Grounding	-	5	1
MBK3	28-12	25	150	6.2	1
MBK3/E-Z (BU)	28-12	20	600	5	1
MBK3/E-Z-PE	28-12	Grounding	-	5	1
MBK5	28-10	40/10	150/300	6.2	1,8
MBK5/E	28-10	40/10	150/300	6.2	1,8,11
MBK5/E-T	28-12	15	300	5	1,13
MBK5/E-TG	28-12	15	300	5	1,13
MBK6/E	26-8	50	300	14.2	1
MBK10	26-8	55	300	14.2	1
MBK-FS	28-14	20	150	6.2	1,12
MBK-FS/FS	22-14	20	150	-	1,12
MBK-Loe	28-18	10	150	6.2	1,16
MBK-Loe/Loe	28-18	10	150	-	1,16
MBKKB2.5	28-12	20	300	5	1

MBT2.5 Series	28-12	20	300	5	-
MC1.5/X-G-3.5	-	8	300	-	2,13
MC1.5/X-GO-3.5	-	8	300	-	2,13
MC1.5/X-GF-3.5	-	8	300	-	2,13
MC1.5/X-ST-3.5	28-16	8	300	2.5	13
MC1.5/X-STF-3.5	28-16	8	300	2.5	13
MC1.5/X-ST-3.81	28-16	8	300	2.5	13
MC1.5/X-STF-3.81	28-16	8	300	2.5	13
MC1.5/X-ST-5.08	28-16	8	300	2.5	13
MC1.5/X-STF-5.08	28-16	8	300	2.5	13
MCD1.5/X-G-3.81	-	8	300	-	2,13
MCD1.5/X-GF-3.81	-	8	300	-	2,13
MCD1.5/X-G1-3.81	-	8	300	-	2,13
MCD1.5/X-G1F-3.81	-	8	300	-	2,13
MCDV1.5/X-G-3.81	-	8	300	-	2,13
MCDV1.5/X-GF-3.81	-	8	300	-	2,13
MCDV1.5/X-G1-3.81	-	8	300	-	2,13
MCDV1.5/X-G1F-3.81	-	8	300	-	2,13
MCV1.5/X-G-3.5	-	8	300	-	2,13
MCV1.5/X-GO-3.5	-	8	300	-	2,13
MCV1.5/X-GF-3.5	-	8	300	-	2,13
MCV1.5/X-G-3.81	-	8	300	-	2,13
MCV1.5/X-GF-3.81	-	8	300	-	2,13
MCV1.5/X-G-5.08	-	8	300	-	2,13
MCV1.5/X-GF-5.08	-	8	300	-	2,13
MCVDU1.5/X-G-3.81	-	8	300	-	2,13
MCVK1.5/X-G-3.81	28-16	8	300	2.5	1,13
MCVK1.5/X-GF-3.81	28-16	8	300	2.5	1,13
MCVR1.5/X-ST-3.81	28-16	8	300	2.5	13
MCVR1.5/X-STF-3.81	28-16	8	300	2.5	13
MCVU1.5/X-GFD-3.81	28-16	8	300	2.5	13
MCVW1.5/X-ST-3.81	28-16	8	300	2.5	13
MCVW1.5/X-STF-3.81	28-16	8	300	2.5	13
MDSTB2.5/X-G (-5.08)	-	10	300	-	2,13
MDSTBV2.5/X-G (-5.08)	-	10	300	-	2,13
MDSTBW2.5/X-G (-5.08)	-	10	300	-	2,13
MFKDS-5.08	16 Sol	10	300	-	2
MFKDSA-7.62	16 Sol	10	300	-	2
MFKDSP/X-5.08	22-18	10	300	-	2
MK3DS1/X-3.81	28-16	10	150/300	4	2
MK3DSN1.5/X-5.08	28-14	10	150/300	2.5	2
MK3DS1.5/X-5.08	28-14	10	300	5	2
MK3DS3/X-5.08	28-12	10	300	5	2
MK3DS3/18-36-5.08-AB	28-12	10	300	5	2

MK3DS3/18-52-5.08-AB	28-12	10	300	5	2
MK-FS/TP	22-18	10	300	-	1,6,7,12
MK-FS/WW	22-18	10	300	-	1,6,7, 12,16
MKKDS1/X-3.5	28-16	10	150/300	2.5	2
MK-Loe/TP	22-18	10	300	-	1,6,16
MK-Loe/WW	22-18	10	300	-	1,6,16
MK-TP	22-18	10	300	5/-	1,6,16
MK-TP/TP	22-18	10	300	-	1,6,16
MK-WW	22-18	10	300	5/-	1,6,16
MK-WW/WW	22-18	10	300	-	1,6,16
MKB4	28-10	30	600	5	-
MKB4-PE	28-10	30	600	5	-
MKB4-2PE	28-10	30	600	5	-
MKDS1/X-3.5	28-16	10	150/300	2.5	2
MKDS1/X-3.81 SMD BK	28-16	10	150/300	2.5	2
MKDS1/X-3.81	28-16	10	150/300	2.5	2
MKDS1.5/X(-5.08)	28-14	10	300	5	2
MKDS2.5/X-5.08	28-12	10	300	5	2
MKDS2.5/X-5.08	28-12	10	300	5	2
MKDS3/X(-5.08)	28-12	10	300	5	2
MKDS3/X-B(-5.08)	28-12	10	300	5	2
MKDS3/...	28-12	10	300	5	2
MKDS5/X-6.35	28-10	10	300	5	2
MKDS5/X-9.5	28-10	30	300	5	2
MKDSA3/X(-5.08)	28-12	10	300	5	2
MKDSFW1.5/X(-5.08)	28-14	10	300	5	2
MKDSFW3/X	28-12	10	300	5	2
MKDSF3/X(-5.08)	28-12	10	300	5	2
MKDSN1.5/X(-5.08)	28-14	10	150/300	2.5	2
MKDSNB1.5/X(-5.08)	28-14	10	150/300	2.5	2
MKDSP 10/X-10.16	20-6	57	300	-	2
MKDSO 2.5/X-L	28-12	10	300	5	2
MKDSO 2.5/X-R	28-12	10	300	5	2
MKDSO5/3-L-6.35	28-12	10	300	5	2
MKDSO5/3-L-6.35 BK	28-12	10	300	5	2
MKDSO5/3-R-6.35	28-12	10	300	5	2
MKDSO5/3-R-6.35 BK	28-12	10	300	5	2
MKDSP1.5/X(-5.08)	28-14	10	300	5	2
MKDSP3/X(-5.08)	28-12	10	300	5	2
MKDSW3/X(-5.08)	28-12	10	300	5	2
MKKDS1/X-3.5	28-16	10	150/300	2.5	2
MKKDS1/X-3.81	28-16	10	150/300	2.5	2
MKKDS1.5/X(-5.08)	28-14	10	300	5	2
MKKDS3/X(-5.08)	28-12	10	300	5	2

MKKDSG3/X	28-12	10	300	5	2
MKKDSW3/X-5.08	28-12	10	300	5	2
MKKDS5/X-9.5	28-10	30	300	5	2
MKKDS5/X-6.35	28-10	10	300	5	2
MKKDSN1.5/X(-5.08)	28-14	10	150/300	2.5	2
MPT0.5/X-2.54	28-20	6	125	1	2
MSLKG2.5	28-12	Grounding	-	5	1
MSLKG5	28-10	Grounding	-	5	1
MSLKG6	26-8	Grounding	-	14.2	1
MSTB-LA/RT	-	-	24	-	-
MSTB2.5/X-STF(-5.08)	28-12	10	300	5	13
MSTB2.5/X-STZ(-5.08)	28-12	10	300	5	13
MSTB2.5/X-G (-5.08)	-	10	300	-	2,13
MSTB2.5/X-G (-5.08) -LA	-	10	300	-	2,13
MSTB2.5/X-GF (-5.08)	-	10	300	-	2,13
MSTB2.5/X-ST (-5.08)	28-12	10	300	5	13
MSTBA2.5/X-G (-5.08)	-	10	300	-	2,13
MSTB2.5/X-ST(5.08)-MS	28-12	10	300	5	13
MSTBA2.5/X-G (-5.08) -LA	-	10	300	-	2,13
MSTBAG2.5/X-G (-5.08)	-	10	300	-	2,13
MSTBAGKL2.5/X-G	-	10	300	-	2,13
MSTBC2.5	20-14	10	300	-	13
MSTBH2.5/10-G	-	10	300	-	1,13
MSTBHK2.5/10-G (-5.08)	28-12	10	300	5	1,13
MSTBHKT2.5/10-G (-5.08)	28-12	10	300	5	1,13
MSTBO2.5/X-GL-5.08	-	6.5	300	-	15
MSTBO2.5/X-GR-5.08	-	6.5	300	-	15
MSTBO 2.5/X-G1L	-	10	300	-	15
MSTBO 2.5/X-G1R	-	10	300	-	15
MSTBP2.5/X-ST(-5.08)	28-12	10	300	5	13
MSTBP2.5/X-ST-5.08	28-12	10	300	5	13
AB AU SO					
MSTBP2.5/X-STFG-5.08	28-12	10	300	5	13
AB AU SO					
MSTBT2.5/X-ST(-5.08)	28-12	10	300	5	13
MSTBT2.5/X-STF(-5.08)	28-12	10	300	5	13
MSTBU2.5/X-ST-5.08-FL	28-12	10	300	5	13
MSTBU2.5/X-STD-5.08	28-12	10	300	5	13
MSTBV2.5/X-G(-5.08)	-	10	300	-	2,13
MSTBV2.5/X-GEH-5.08	-	10	300	-	2,13
MSTBVA2.5/X-G(-5.08)	-	10	300	-	2,13
MSTBVAG2.5/X-G(-5.08)	-	10	300	-	2,13
MSTBVK2.5/X-G-5.08	28-12	10	300	5	1,13
MSTBVK2.5/X-GF-5.08	28-12	10	300	5	1,13
MSTBVK2.5/X-ST-5.08	28-12	10	300	5	1,13

MSTBW2.5/X-G(-5.08)	-	10	300	-	2,13
MSTBW2.5/X-GF-5.08 -4.45 AB GY AU	-	10	300	-	2,13
MSTBW2.5/X-GF-5.08 -6.03 AB GY AU	-	10	300	-	2,13
MT1.5	28-14	15	300	2.5	1
MT1.5-PE	28-14	Grounding	-	2.5	1
MT1.5-QUATTRO	28-14	15	300	2.5	1
MT1.5-QUATTRO-PE	28-14	Grounding	-	2.5	1
MT1.5-TWIN	28-14	15	300	2.5	1
MT1.5-TWIN-PE	28-14	Grounding	-	2.5	1
MTK	28-12	15	300	5	1
MTK-P/P	28-12	15	300	5	1,13
MTKD	28-12	20	600	5	1,13
MTKD-P/P	28-12	20	600	5	1,13
MTTB1.5	28-14	15	300	2.5	300
MVSTBN2.5/X-ST(-5.08)	28-12	10	300	5	1
MVSTBR2.5/X-ST (-5.08)	28-12	10	300	5	13
MVSTBR2.5/X-STF(-5.08)	28-12	10	300	5	13
MVSTBU2.5/X-GB-5.08	28-12	10	300	5	13
MVSTBU2.5/X-GFB-5.08	28-12	10	300	5	13
MVSTBU2.5/X-ST	28-12	10	300	5	13
MVSTBU2.5/X-STF	28-12	10	300	5	13
MVSTBW2.5/X-ST (-5.08)	28-12	10	300	5	13
MVSTBW2.5/X-STF(-5.08)	28-12	10	300	5	13
OTTA2.5	22-14	20	600	11	1
OTTA2.5-PE	22-14	Grounding	-	11	1
OTTA2.5-P/P	22-14	20	600	11	1
OTTA6	22-10	30	600	6.2	1
OTTA-6PE	22-10	Grounding	-	20	1
OTTA-6-T	22-10	25	600	20	1,13
OTTA-6-T-P/P	22-10	25	600	20	1,13
OTTA25-M5	18-4	100	600	40	1
OTTA25-M6	18-4	100	600	40	1
PC4/X-G-7.62	-	20	300	5	2,13
PC4/X-G-15.24-1(-2)	-	20	600	5	2,13
PC4/X-ST-7.62	28-10	20	300	5	13
PC4/X-STF-7.62	28-10	20	300	5	13
PC4/X-ST-15.24-1(-2)	28-10	20	600	5	13
PC4HV/X-ST-7.62	28-10	20	600	5	13
PCC4/X-ST-7.62	20-14	10	300	-	13
PCV4/X-G-7.62	28-10	20	300	5	2,13
PCV4/X-G-15.24-1(-2)	28-10	20	600	5	2,13
PCVK4-7.62	28-10	20	300	5-7	1,13
PCVK4-7.62-F	28-10	20	300	5-7	1,13

PSC1.5/X-F	28-16	8	300	2.5	2
PSC1.5/X-M	-	8	300	-	2
PSC1.5/X-M-PE	-	8	300	-	2
RK-ND2 KRI	18-6	65	600	14.2	1
RKN KER, KRI	18-8	50	600	14.2	1
RKN/S KER, KRI	22-12	25	600	6.2	1
RSA 1 KRI	18-6	80	600	14.2	1
RTK KER, KRI	24-8	55	600	14.2	1,13
RTK-BEN, KER, KRI	24-8	50	600	14.2	1,13
RTK/S KER, KRI	26-10	40	600	6.2	1,13
RTK/S-BEN, KER, KRI	26-10	40	600	6.2	1,13
SIG/ST-Si	24-8	10	250	14.2	1,5,13
SIG/ST1-Si	24-8	10	250	14.2	1,5,13
SIG/ST-T	24-8	40	600	14.2	1,5,13
SIM-AMS 1	PCB	5	300	-	18
SIM-AMS 1-R	PCB	5	300	-	18
SK4	28-12	25	600	6.2	1
SK4-FS/FS	28-14	20	600	-	1,12
SK4-FSR	28-12/ 22-14	20	600	6.2	1,12
SK10	26-8	55	600	14.2	1
SK16	24-6	80	600	14.2	1
SLKK5	28-12	25	300	6.2	1,25
SMC1.5/X-G-3.81	-	8	300	-	2, 13
SMC1.5/X-GF-3.81	-	8	300	-	2,13
SMKDS1/X-3.5	28-16	10	150/300	2.5	2
SMKDS1/X-3.81	28-16	10	150/300	2.5	2
SMKDS1.5/X(-5.08)	28-14	10	300	5	2
SMKDS2.5/X-5.08	28-12	10	300	5	2
SMKDSP1.5/X(-5.08)	28-14	10	300	5	2
SMKDS3/X(-5.08)	28-12	10	300	5	2
SMKDS5/X-6.35	28-10	10	300	5	2
SMKDS5/X-9.5	28-10	30	300	5	2
SMKDSN1.5/X(-5.08)	28-14	10	300	2.5	2
SMKDSNF1.5/X-5.08	28-14	10	300	2.5	2
SMKDSNF1.5/X-5.08 BK	28-14	10	300	2.5	2
SMSTB2.5/X-ST (-5.08)	28-12	10	300	5	2,13
SMSTB2.5/X-G(-5.08)	-	10	300	-	2,13
SMSTBA2.5/X-G(-5.08)	-	10	300	-	2,13
SSK 0525 KER-EX	28-12	20	600	6.2	1
SSK 0525-FS/FS KER	28-14	20	150	-	1,12
SSK 0525-L/B1, /C1 KRI	28-12	25	600	6.2	1
SSK 0525-Loe/ Loe KER, KRI	28-14	20	150	-	1,16
SSK 0525-Loer KER, KRI	28-12/ 28-14	20	150	6.2	1,16

	28-14				
SSK 0525-T KRI	28-12	15	600	6.2	1,13
SSK 0525-5-Loe/ Loe-P/P KRI	28-14	15	150	-	1,6,13,16
SSK 0525-T-Loer-P/P KRI	28-12/ 28-14	15	150	6.2	1,6,13,16
SSK 0525-T-P/P KRI	28-12	15/10	150/300	6.2	1,6,13
SSK 0525-TG KRI	28-12	15/10	150/300	6.2	1,6,13
SSK 5 KRI	18-10	40	300	6.2	1
SSK/N 0525-FS/FS KRI	28-14	20	150	-	1,12
SSK/N 0525-FSR KRI	28-12/ 28-14	20	150	6.2	1,12
SSK/N 0525-L/B1, /C1 KRI	28-12	25	600	6.2	1
SSK/N 0525-Loe/Loe KRI	28-14	20	150	-	1,16
SSK/N 0525-Loer KRI	28-12/ 28-14	20	150	6.2	1,16
SSK110 KER-EX, KRI	26-8	55	600	14.2	1
SSK116 KER-EX, KRI	24-6	80	600	14.2	1
SSK125 KER, KRI	3 or less	120	600	23	1
SSK135 KER, KRI	14-2	140	600	50	1
STB3/X-G-5.08 X=3,4	-	10	300	-	2,13
STB3/X-ST-5.08 X=3,4	28-14	10	300	5	13
STB3/X-5.08 X=3,4	28-14	10	300	5	2,13
ST-Si-UK4	Fuseholder	10	300	-	5
ST-SiLED-UK4	Fuseholder	10	300	-	5
ST-SiLA-UK4	Fuseholder	10	300	-	5
ST1.5	26.14	15	300	-	1,34
ST1.5- TWIN	26-14	15	300	-	1,34
ST1.5-Quattro	26-14	15	300	-	1,34
STTB1.5	26-14	15	300	-	1,34
ST35	14-2	115	600	-	1,34
ST1.5-PE	26-14	Grounding	-	-	7
ST4-PE/3L	28-10	Grounding	-	-	7
STTB1.5-PE	26-14	Grounding	-	-	7
ST1.5 -Quattro	26-14	Grounding	-	-	7
STTB1.5-TWIN-PE	26-14	Grounding	-	-	7
ST35-PE	14-2	Grounding	-	-	7
TMSTBP2.5/X-ST-5.08 AB GY AU	28-12	10	300	5	13, 28
TMSTBP2.5/X-STF-5.08 AB GY AU	28-12	10	300	5	13, 28
TRK1.5 with suffixes	22-14	20	300	6.2	4,27
TRK1.5 BlauSO1	22-14	15	300	6.2	4
TRK2.5	18-12	25	600	6.2	4,12
TRK2.5-FS	18-12	25	600	6.2	4,5

TRK2.5-Si	18-12	6.3	250	6.2	4
TRK4	18-10	40	600	6.2	4
TRK4-FS	18-10	40	600	6.2	4,12
TRK4 Blau SO1	18-10	40	600	6.2	4
TRK10	18-6	80	600	14.2	4
TRK10 Blau SO1	18-6	80	600	14.2	4
TRKS4	28-10	30	600	5	4
TRKS4-FS	28-10	30	600	5	4,12
TRKS4-PE	28-10	Grounding	-	5	4
TRKS4-Si	28-10	8	600	5	4,5
TRKS4-Si/K	28-10	8	600	5	4,5
TRKS10	22-6	65	300	20	4
TRKSD4	28-10	30	600	5	4
TRKSD10	22-6	65	600	20.0	4
TRKSD10/3	22-6	65	600	20	4
TT-UK 5/...DC	28-10	34	5-110	0.8Nm	1,33
TT-UK 5/...AC	28-10	34	12-110	0.8Nm	1,33
TT-SLKK 5/...DC	28-12	34	12-110	0.8Nm	1,33
TT-SLKK 5/...AC	28-12	34	12-110	0.8Nm	1,33
TT-SLKK 5-F/...DC	28-12	2	48-110	0.8Nm	1,33
TT-UKK 5-M/...DC	24-12	12	5-110	0.8Nm	1,33
TT-UKK 5-M/...AC	24-12	12	12-110	0.8Nm	1,33
TT-UKK 5-M-F/...AC	24-12	16	300	0.8Nm	1,33
TT-UKK 5-D/...DC	24-12	16	5-110	0.8Nm	1,33
TT-UKK 5-D/...AC	24-12	16	12-110	0.8Nm	1,33
TT-UKK 5-D-F/...AC	24-12	16	300	0.8Nm	1,33
TT-URTK/S-...DC	20-8	44	24-110	1.8Nm	1,33
TT-URTK/S-...AC	20-8	44	24-110	1.8Nm	1,33
UDK3	28-12	20	300	5	1
UDK4	22-10	25/10	300/600	6.2	1
UDK4-DUR	22-10	10	600	5	1
UDK4-DUR 249	22-10	10	600	5	1
UDK4-ILA 500	22-10	0.5	600	5	1
UDK4-ILA 1000	22-10	1	600	5	1
UDK4-MTK-P/P	22-10	15/10	300/600	5	1,13
UDK4-PE	22-10	25	Grounding	5	1
UDK4-ULA/EK	22-12	25/10	300/600	5	1
UDK4-ULA12RT/O-U	22-12	25/10	300/600	5	1
UDK4-ULA24RT/O-U	22-12	25/10	300/600	5	1
UDK4-ULA48RT/O-U	22-12	25/10	300/600	5	1
UDK4-ULA220	22-12	25/10	300/600	5	1
UDMTK 5-P/P	28-12	15	300	5	1,13
UDMTK 5-TWIN-P/P	28-12	8	300	5	1,13
UGMSTBHK2.5/10-G	28-12	10	300	5	1,13

UHK4-FS	28-14	20	600	6.2	1,12
UHK4-FS/FS	22-14	20	600	-	1,12
UHSK/S2000	26-12	25	600	6.2	1
UHV25-AS/AS, -KH/AS, -KH/KH	6-4	100	600	35	1
UHV25-M8/M8, -KH/M8	6-4	100	600	35	1
UHV50-AS/AS, -KH/AS, -KH/KH	6-1/0	125	600	70	1
UHV50-M10/M10, -KH/M10	6-1/0	125	600	70	1
UHV95-AS/AS, -KH/AS, -KH/KH	2-4/0	200	600	250	1
UHV95-M12/M12, -KH/M12	2-4/0	200	600	250	1
UHV150-AS/AS, -KH/AS, -KH/KH	2-300MCM	275	600	250	1
UHV150-M12/M12, -KH/M12	2-300MCM	275	600	250	1
UHV240-AS/AS, -KH/AS, -KH/KH	1/0-500 MCM	400	600	270	1
UHV240-M16-M16, -KH/M16	1/0-500 MCM	400	600	270	1
UICVK2.5/X-ST-5.08	28-12	10	300	5	1,13
UIK16	22-4	85	600	18	1
UIK35	18-2	130	600	30	1
UISLKG16	22-4	Grounding	-	18	1
UK-Si	24-14	10	250	6.2	1,5
UK2.5	28-12	25	600	6.2	1
UK2.5B	28-12	25	600	6.2	1
UK2.5N	28-12	20	300	20	1
UK3	28-12	25	600	6.2	1
UK3N	28-12	20	600	5	1
UK3D-MSTBV-5.08 w/suffixes	28-12	20	300	5	1,13
UK3-MSTB-5.08	28-12	20	300	5	1,13
UK3-RETURN	28-12	25	300	5	1
UK3-RETURN-PE	28-12	Grounding	-	5.0	1
UK3-TWIN	28-12	20	300	5	1
UK-FRONT4-PE	24-10	Grounding		6.5	1
UK-FRONT4	24-10	30	600	6.5	1
UK4	28-12	25	600	6.2	1
UK4-T	28-12	15	600	6.2	1,13
UK4-T-P/P	28-12	15/10	150/300	6.2	1,13
UK4-TG	28-12	15	600	6.2	1,13
UK5	28-10	40	600	6.2	1

UK5N	28-10	40	600	5	1
UK5NCB	28-10	40	600	5	1
UK5-HESi	28-10	6.3	600	6.2	1,3,5
UK5-HESiLA 250, 500	28-10	6.3	600	6.2	1,3,5
UK5-HESiLED 12, 24, 60	28-10	6.3	600	6.2	1,3,5
UK5-MTK-P/P	18-10	15	300	6.2	1, 13
UK5-RETURN	28-10	40	300	5	1
UK5-RETURN-PE	28-10	Grounding	-	5	1
UK5-TWIN	22-10	30	300	6.2	1
UK6-FSI/C w/ suffixes	26-8	30	32	14.2	1,5
UK6N	26-8	50	600	14.2	1
UK6.3HESi	26-8	25	600	14.2	1,5
UK6.3HESiLED w/suffixes	26-8	25	600	14.2	1,5
UK6.3HESiLA w/suffixes	26-8	25	600	14.2	1,5
UK10	26-8	55	600	14.2	1
UK10N	24-6	65	600	20	1
UK10-TWIN	24-6	65	600	20	1
UK10-TWIN-PE	24-6	Grounding	-	20	1
UK10-PLUS	24-6/28-12	65/20	600	20/6.2	1
UK10-PLUS-PE	24-6/28-12	Grounding	-	20/6.2	1
UK10-DREHSI	22-6	20	300	20	1,5
UK10-DREHSI-6.3	22-6	20	300	20	1,5
UK10.3-HESi	18-8	35	600	20	1,5
UK10-PE/N	26-8	55	600	14	1
UK10-RETURN	22-6	65	300	20	1
UK10-RETURN-PE	22-6	Grounding	-	20	1
UK16	24-6	80	600	14.2	1
UK16N	22-4	85	600	18	1
UK16-PE/N	24-6	80	600	14	1
UK25	18-4	100	600	35	1
UK35	18-2	140	600	50	1
UK35-PE/N	18-2	Grounding	-	50	1
UKH25	6-4	100	600	35	1
UKH50	6-1/0	125	600	70	1
UKH95	2-4/0	200	600	250	1
UKH150	2-300MCM	275	600	250	1
UKH240	1/0-500 MCM	400	600	270	1
UKK3	28-12	25/5	300/600	6.2	1
UKK3-MSTB-5.08	28-12	10	300	5	1, 13
UKK3-MSTBVH-5.08	28-12	10	300	5	1, 13
UKK5	28-10	25	300 or 600**	6.2	1

**with D-
UKK
3/5 cover

UKK5-MTK-P/P	22-12	15	300	5	1,13
UKK5-MTKD-P/P	22-12	15	300	5	1,13
UKK5-MTKD-P/ P-LA 24 RD/O-U	22-12	15	300	5	1,13
UKK5-MTKD-P/ P-LA 48 RD/O-U	22-12	15	300	5	1,13
UKK5-MTKD-P/ P-LA 60 RD/O-U	22-12	15	300	5	1,13
UKK5-PE	28-10	Grounding	-	6.2	1
UKK5-T	28-12	15	300	5	1,13
UKK5-TG	28-12	15	300	5	1,13
UKKB3	28-12	25/5	300/600	6.2	1
UKKB5	28-10	25/5	300/600	6.2	1
UKKB5-PE	28-10	Grounding	-	6.2	1
UKKB10	24-6	65	300(B,C spac.) 600(D,E spac.)	20	1
UKKB10-2.5	24-6/28-12	65/20	300(B,C spac.) 600(D,E spac.)	20	1,26
UKKB10-2.5-PV	24-6/28-12	65/20	300(B,C spac.) 600(D,E spac.)	20	1,26
UMK22-RELX/21	28-14	10	250	5	1,24
UMK22-RELX/21-21	28-14	5	250	5	1,24
UMSTBHK2.5/10-G	28-12	10	300	5	1,13
UMSTBVK2.5/X-G-5.08	28-12	10	300	5	1,13
UMSTBVK2.5/X-GF-5.08	28-12	10	300	5	1,13
UMSTBVK2.5/X-ST-5.08	28-12	10	300	5	1,13
URELGX-PMTK	28-12	11	300	5-7	1,13
URELGX-PMTK-RD	28-12	11	300	5-7	1,13
URK-ND2	18-6	65	600	14.2	1
URTK/S	26-10	40	300	6.2	1,13
URTK/SP	26-8	45	300	14.2	1,13
URTK/SS	28-12	25	300	5	1,13
URTK/S-BEN	26-8	55	600	14.2	1,13
URTK/S-BEN10	26-8	55	600	20.0	1,13
USiG/ST-Si	24-8	10	250	14.2	1,5,13
USiG/ST1-Si	24-8	10	250	14.2	1,5,13
USiG/ST-T	24-8	40	600	14.2	1,5,13
USK4	28-12	25	600	6.2	1

USK4-FSR	28-12	20	600	6.2	1,12
USK4-FS/FS	-	20	600	-	1,12
USK10	26-8	50	600	14.2	1
USK16	24-6	65	600	14.2	1
USLKG2.5	28-12	Grounding	-	6.2	1
USLKG3	28-12	Grounding	-	6.2	1
USLKG4	28-12	Grounding	-	6.2	1
USLKG5	28-10	Grounding	-	6.2	1
USLKG10	26-8	Grounding	-	14.2	1
USLKG10N	26-6	Grounding	-	20	1
USLKG16	24-6	Grounding	-	14.2	1
USLKG16N	22-12	Grounding	-	20	1
USLKG35	18-2	Grounding	-	50	1
USLKG95	2-4/0	Grounding	-	250	1
USLKG2.5-1	28-12	Grounding	-	6.2	1
USLKG3-1	28-12	Grounding	-	6.2	1
USLKG4-1	28-12	Grounding	-	6.2	1
USLKG5-1	28-10	Grounding	-	6.2	1
USLKG10-1	26-8	Grounding	-	14.2	1
USLKG10N-1	26-6	Grounding	-	20	1
USLKG16-1	24-6	Grounding	-	14.2	1
USLKG16N-1	22-12	Grounding	-	20	1
USLKG35-1	18-2	Grounding	-	50	1
UT2.5	25-12	Grounding	B,C	5-7	1
UT2.5/1P	26-12	Grounding	B,C	5-7	1
UT4	26-10	Grounding	B,C	5-7	1
UT4-MTD	26-10	Grounding	B,C	5-7	1
UT6	24-8	Grounding	B,C	13-15	1
UT10	20-6	Grounding	B,C	13-15	1
UT16	16-4	Grounding	B,C	35-39	1
UT35	14-0	Grounding	B,C	53-70	1
UT4-MT	26-10	16	600 B,C	5-7	1,13
UT4-TG	26-10	16	600 B,C	5-7	1,13
UT4-MT-P/P	26-10	16	300 B,C	5-7	1,13
UT4-TG-P/P	26-10	16	300 B,C	5-7	1,13
UT4-HEDI	26-10	16	600 B,C	5-7	1
UT4-HEDI-P/P	26-10	16	300 B,C	5-7	1
UT4-HESI(5x20)	26-10	6.3	600 B,C	5-7	1,3
UT4-HESILED 24 (5x20)	26-10	6.3	24	5-7	1,3
UT4-HESILA 250 (5x20)	26-10	6.3	250	5-7	1,3
UT4-HESILED 60 (5x20)	26-10	6.3	60	5-7	1,3
UT4-MTD-DIO/L-R	26-10	1	600 B,C	5-7	1
UT4-MTD-DIO/R/L	26-10	1	600 B,C	5-7	1
UT4-MTD-DIO/L-R-P/P	26-10	1	300 B,C	5-7	1

UT4-MTD-DIO/R-L-P/P	26-10	1	300 B,C	5-7	1
UVK4-FSR	28-14	20	600	6.2	1,12
UVK4-FS/FS	22-14	20	600	-	1,12
VDFK4(-DP), with suffixes	28-10	30	300	5.0	15
VDFK4 GNYE	28-10	30	300	5	15
VDFK4/K(-DP) with suffixes	28-10	30	300	5	15
VDFK4/K GNYE	28-10	30	300	5	15
VDFK4WH	28-10	30	300	5	15
VDFK6(-DP) with suffixes	26-8	50	300	14.2	15
VDFK6 GNYE	26-8	50	300	14.2	15
VDFK6/K-DP	26-8	50	300	14.2	15
VDFK6/K GNYE	26-8	50	300	14.2	15
VIOK1.5-D/TG/D/PE	28-14	15	300	5	1,17
VIOK1.5(-LA)with suffixes	28-14	15	300	5	1
VIOK1.5-2D	28-14	15	300	5	1,17
VIOK1.5-3D/PE	28-14	15	300	5	1,17
VK4-FSR	28-14	20	600	6.2	1,12
VK4-FS/FS	22-14	20	600	-	1,12
VTRK4 OG (GY)	28-10	30	300	5	15
VTRKZ4 OG (GY)	28-10	30	300	5	15
VTRK4-Si/C OG (GY)	28-10	10	32	5	5,15
VTRKZ4-Si/C OG (GY)	28-10	10	32	5	5,15
ZFDK2.5	26-12	20	600	-	1
ZFDK2.5-MT	26-12	15	300	-	1,13
ZFDK2.5-PE	26-12	Grounding	-	-	1
ZFK1.5	26-14	15	300	-	1
ZFK1.5 BU	26-14	15	300	-	1
ZFK2.5	26-12	25	600	-	1
ZFK2.5-MT	26-12	15	300	-	1,13
ZFK2.5-PE	26-12	Grounding	-	-	1
ZFK2.5-TWIN	26-12	20	600	-	1
ZFK2.5-TWIN-PE	26-12	Grounding	-	-	1
ZFK3DS(A)1.5-5.08	28-12	10	300	-	2
ZFKI2.5	26-12	25	600	-	1
ZFKI2.5-PE	26-12	Grounding	-	-	1
ZFK4	24-10	30	600	-	1
ZFK 4-PE	24-12	-	-	-	1
ZFK4-TG	24-10	15	600	-	1,13
ZFKDS1.5-5.08	28-12	10	300	-	2
ZFKDS1.5-W-5.08	28-12	10	300	-	2
ZFKDSA1.5-7.62	28-12	10	300	-	2
ZFKDSA1.5-W-7.62	28-12	10	300	-	2
ZFKI 4	24-10	30	600	-	1

ZFKI 4-PE	24-12	-	-	-	1
ZFKK2.5	26-12	20	600	-	2
ZFKKB2.5	26-12	20	600	-	2
ZFKKDS(A)1.5-5.08	28-12	10	300	-	2

Notes:

1. Recess type terminal blocks for string mounting on a metal groove rail; for solid and stranded insulated copper conductors.
2. Terminal blocks for soldering to a printed wiring board.
3. Terminal block Cat No UK-HESi or UT-HESI series is used with a fuse of max rating 6.3A.
4. Terminal blocks for string mounting on metal bars (i.e. aluminum, steel, etc).
5. Type SiG; USiG, KDS3-Si and TRK 2.5-Si may have fuseholders for miniature size cartridge fuses, rated respectively 250V, 10A max and 6.3A max. Cat No ST-Si-XXX is a plug-in fuseholder for terminal block Cat No UK4-TG.
6. Types MK..., FK 1.5, FKMT 1.5, G5, UK4-T-P/P, K4-T-P/P, SSK 0525-TG and SKK 0525-T-P/P are certified for use only in equipment where the short circuit capacity of the circuit in which they are connected is limited by fuses having ratings not exceeding the rating of the terminal block.
7. Type MK-FS/TP for use with the AMP fast-on receptacles with preinsulated grip.
8. Types MBK 5 above 150V are certified for use only in equipment where the short circuit capacity of the circuit in which they are connected is limited by fuses having ratings not exceeding the rating of the terminal block.
9. Type KDS is acceptable for voltages up to 300V when used in combination with the special barrier Type RZ 2.5.
10. These terminal blocks and Types FL...7.5 above 150V are accepted for use only in equipment where the short circuit capacity of the circuit in which they are connected is limited by fuses having ratings not exceeding the rating of the terminal blocks and where the acceptability of the final assembly has been determined by the Canadian Standards Association.
11. The type designations may be completed with letters E or M indicating the type of mounting feet.
12. Terminal blocks with the letters FL and FS in the type designation have male contacts for quick disconnect connections with fast-on plugs with pre-insulated grip.
13. Types with the letters T, TG or Si in the type designation have a pull type plug. This isolating feature is not for use under load.
Types with letter T may have pull type plug C10 or ST-BE with built in resistor, diode, etc.
Types with MT have a isolating knife switch. Types TK have as slide isolating mean.
14. Insulated terminal strings, cuttable, for stranded and solid insulated copper conductors, with or without special metal groove rail isolated from grounded parts.
15. Panel feed through terminal block.
16. Terminal blocks with Loe in type designation have solder connections. WW= wire wrap, TP = termi-point.
17. Suffixes -LA24RT, -LA48RT, -LA60RT, -LA220, -LA24GN, -LA48GN, -LA60GN additionally followed by suffixes /O-M, /U-0, /O-M0, /MU-0, may be added to the Types DIK 1.5, DOK 1.5, DIKD 1.5, VIOK 1.5 to denote minor variations.
18. Printed circuit board type terminal blocks incorporating relay sockets.
19. Series AKG16, AKG35 may be followed by suffixes "BLACK, BLUE or GREEN-YELLOW".
20. Suffix may be 1.5 or 2.5.
21. Suffixes -LA24RT, -LA48RT, -LA60RT, /EK may be added to Type UK 3D-MSTBV-5.08 to denote minor variations.
22. Series HDFK25-DP may be followed by suffix "GREEN-YELLOW".
23. Terminal block mounted on pcb in conjunction with DIN header.
24. Mounted on pcb in conjunction with relay.

25. Series SLKK5 rated 600V when used with spacer D-UKK3/5 or DG-UKK3/5.
26. Double level DIN rail mountable terminal block.
27. Suffixes -S (GY or OG), -S-FS (GY or OG), -N (GY or OG), -N-S (GY or OG), -N-S-FS OG, -GY-S02, -FS-BU-S01, -S-FS-BU-S01, -N-FS (GY or OG), -BU-S01; may be added to TRK1.5.
28. Prefix T indicates 2 parallel points per circuit, the sum of the currents per position may not exceed a 10A max.
29. Types with letter V following letters HDFK indicates that outside wire entry is vertical.
30. Suffix -VP indicates that the internal connection is for ring tongue equipped cables and the interior of an enclosure is filled with potting compound.
31. Suffix -DP indicates enclosure wall thicknesses of 5 - 10mm.
32. Suffix -GNYE indicates green yellow colour of housing and are not grounding terminal blocks.
33. The type designation ... is completed with numbers indicating the voltage.
34. Suffixes BU, DG, RD, BK or PV may be added.

General Notes:

1. Letter "X" in the above catalogue designations represents numbers denoting the quantity of circuits.
2. Barriers may be necessary in certain applications, to insure proper spacing.
3. These are Certified only for supply to manufacturers for the assembly, as components, of Certified electrical equipment where the suitability of the combination is determined by the CSA International.
4. Suffix letters and numbers may be added to denote minor variations such as colour, packaging, etc.

/jek