

## This document was generated on 02/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0714362164		
Status:	Active		
Overview:	1.00mm Mezzanine (IE		
		386) Plug, Surface Mount, Dual Row, Vertical Stacking, 64	100000000000000000000000000000000000000
		ated Height, with PCB Locator Pegs, without Robotic Placement Id (Au) Selective Plating, Tube	
	Metal Cap, 0.76µm Go	id (Au) Selective Plating, Tube	
Documents:		Draduct Cracification DC 71420 0000 004 (DDE)	
<u>3D Model</u> Drawing (PDF)		Product Specification PS-71436-9999-001 (PDF)	
<u>3D Model (PDF)</u>		Packaging Specification PK-70873-063 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only
			Series Image - Reference Uniy
Agency Certificatio	.n.		
CSA	11	LR19980	EU ELV Not Relevant
		E29179	NOT Relevant
		E23173	EU RoHS China RoHS
General			Compliant
Product Family		PCB Headers	REACH SVHC
Series		71436	Not Contained Per -
Application		Board-to-Board, Signal	D(2020)9139-DC (19
Overview		1.00mm Mezzanine (IEEE 1386)	Jan 2021)
Product Name		1.00mm Mezzanine (IEEE 1386)	Halogen-Free
UPC		800753677814	Status
			Low-Halogen
Physical			For more information, please visit Contact US
Breakaway		No	
Circuits (Loaded)		64	China ROHS Green Image
Circuits (maximum)		64	ELV Not Relevant
Color - Resin		Natural	RoHS Phthalates Not Contained
Flammability		94V-0	
Glow-Wire Capable		No	
Lock to Mating Part		None	Search Parts in this Series
Mated Height		10.00mm, 12.00mm, 13.00mm, 15.00mm	71436 Series
Material - Metal		Phosphor Bronze	
Material - Plating Mating		Gold	
Material - Plating Termination		Tin	Mates With
Material - Resin		High Temperature Thermoplastic	71439 1.00mm Mezz (IEEE 1386)
Net Weight		1.402/g	Receptacle. Be sure to match like stack
Number of Rows		2	heights
Orientation		Vertical	
PCB Locator		Yes	
PCB Retention		None	
PCB Thickness - Re	commended	1.00mm	
Packaging Type	200		
Pitch - Mating Interfa		1.00mm	
Plating min - Mating	ation	0.762µm	
Plating min - Termin		1.905µm No	
Polarized to Mating	rait		
Stackable		Fully	
Temperature Range		No -55° to +85°C	
		Surface Mount	
Termination Interfact			
Electrical			
Current - Maximum	per Contact	1.0A	
		400)/	

100V

Current - Maximum per Contact Voltage - Maximum

**Solder Process Data** 

Duration at Max. Process Temperature (seconds)040Lead-freeProcess CapabilityREFLOWMax. Cycles at Max. Process Temperature003Process Temperature max. C260

## **Material Info**

**Reference - Drawing Numbers** Packaging Specification Product Specification Sales Drawing

PK-70873-063 PS-71436-9999-001 714362000-000

This document was generated on 02/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION