USB333x/334x USB Transceiver Family Hi-Speed USB 2.0 Transceiver Family Featuring RapidCharge Anywhere[™] for Smartphones and Other Portable Devices



SMSC's USB333x/334x family of Hi-Speed USB 2.0 transceivers delivers enhanced USB functionality for the portable market with support for the latest USB-IF Battery Charging 1.1 (BC 1.1) specification. This family of devices dramatically reduces the time required for battery charging and system bill-of-material (BOM) costs by up to 60% over competitive solutions. SMSC has positioned itself as a leader in providing innovative solutions in support of BC 1.1. The new USB333x/334x provides an excellent compliment to USB charging ports by enabling portable devices to negotiate up to three times the charging current compared to a standard USB port, resulting in faster battery charging. The USB333x/334x is designed in a small footprint package and reduces the number of external components through the integration of voltage regulators and other discretes. Additionally, SMSC's complimentary and confidential USBCheck™ online design review service is available for customers who select the USB333x/334x for their application design-in*.

Highlights

Highly-integrated, Hi-Speed USB 2.0 transceivers

- Integrated VBUS over-voltage protection (up to +30V)
- Integrated USB switch enables connector as a single port for data, charging and audio
- Extremely high ESD performance in a Hi-Speed USB transceiver
 - ±8kV HBM with up to ±25kV IEC (contact/air)
- Supports a wide variety of common reference clock frequencies
- USB-IF Battery Charger revision 1.1 support

- Ultra-low standby current
- "Wrapper-less" architecture for optimized timing performance
- Hi-Speed USB On-The-Go (OTG) revision 2.0 compliant
- Link Power Management (LPM)
- Industrial (-40° to 85°C) temperature range options available
- WLCSP, RoHS-compliant package (USB333x)
- QFN, RoHS-compliant package (USB334x)

Target Applications

- Digital Still/Video Cameras
- Smartphones/Cell Phones
- GPS Personal Navigation DevicesMP3/Portable Media Players (PMPs)
- External Hard Disk Drives
- Gaming Consoles

Features	Benefits			
Single supply operation	Eliminates need for external regulators			
Integrated VBUS over-voltage protection (OVP)	Eliminates need for costly external OVP IC			
Integrated USB switch and ESD protection	Enables lower BOM part count and smaller PCB footprint area			
flexPWR® technology providing extremely low power consumption	Longer battery life and variable I/O voltage capability			
Multiple clock input frequencies supported	Allows USB PHY to operate from the system clock, eliminating			
	the need for an external crystal oscillator for the USB PHY			
Extremely small package footprint	Efficient PCB board space utilization			









Downloaded from Arrow.com.



SMSC RapidCharge Anywhere Provides:

- 3X the charging current through a USB port over traditional solutions
- USB-IF Battery Charging 1.1 support to any portable device
- Charging current up to 1.5Amps via compatible USB host or dedicated charger
- Dedicated Charging Port (DCP), Charging (CDP) and Standard (SDP) Downstream Port support
- Complete USB charging ecosystem between device and host

USB333X/334X FAMILY INTEGRATES EIGHT FUNCTIONS INTO ONE SOLUTION!



USB333X FAMILY SELECTOR GUIDE

USB334X FAMILY SELECTOR GUIDE

Part Number	Package	Reference Frequency***	l/O Voltage	Integrated Switch	Part Number	Package	Reference Frequency***	l/O Voltage	Integrated Switch
USB3330	WICSP	Multi	1.8V	No	USB3340	QEN	Multi	1.8 - 3.3V	Yes
USB3331		26MHz	1.8V	Yes	USB3341				
LISB3333		19 2/26MHz	1 8 - 3 3V	No			26MHz	1.8V	Yes
00000000	WEOOI	13.2/2010112	1.0 - 5.5 V	INO	110000040	QIN		10 2 21	NI.
USB3336	-	19.2MHz	1.8V	Yes	USB3343		26MHz Crystal	1.8 - 3.3V	INO
USB3338		38.4MHz	1.8V	No	USB3346		19.2MHz	1.8V	Yes

*USBCheck online design review service requires an SMSC e-Services account and is subject to the terms and conditions listed on SMSC's website

** Integrated USB switch available on select part numbers

*** All parts support ULPI clock 60MHz in mode

Copyright ©2010 SMSC or its subsidiaries. All rights reserved. Although the information in this document has been checked and is believed to be accurate, no responsibility is assumed for inaccuracies. SMSC reserves the right to make changes to product descriptions and specifications at any time without notice. Contact your local SMSC sales office to obtain the latest specifications before placing your product order. The provision of this information does not convey any licenses under any patern rights or other intellectual property rights of SMSC or others. All sales are expressly conditional on your agreement to the terms and conditions of the most recently dated version of SMSC's standard Terms of Sale Agreement dated before the date of your order. Products may contain design defects or errors known as anomalies which may cause a product's functions to deviate from published specifications. Anomaly sheets are available upon request. SMSC products are not designed intended, authorized or warranted for use in any life support or other application where product failure could cause or contribute to personal injury or severe property damage. Any and all such uses without prior written approval of an Officer of SMSC and further testing and/or modification will be fully at the risk of the customer. Copies of this document or other SMSC literature, as well as the Terms of Sale Agreement, may be obtained by visiting SMSC's website at http://www.smsc.com. SMSC hey SMSC logo and flexPWR are registered trademarks and RapidCharge Anywhere, the RapidCharge Anywhere logo and USBCheck are trademarks of Standard Microsystems Corporation ("SMSC"). Other names mentioned may be trademarks of their respective holders. All claims made herein speak as of the date of this material. The company does not undertake to update such statements. (09/10)

For more information visit www.smsc.com or call 1.800.443.SEMI SMSC 80 Arkay Drive, Hauppauge, NY 11788

