

# USB-C Dock - 4K HDMI, USB 3.2 Gen 1, USB-A/C Hub, GbE, Memory Card, 60W PD Charging

## MODEL NUMBER: U442-DOCK11-S







0

USB-C dock with PD Charging adds 4K HDMI, USB-A, USB-C and Ethernet ports to your laptop or tablet's USB-C or Thunderbolt 3 port.

#### Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a WorkstationThis multiport USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, tablet or other device with a USB-C or Thunderbolt 3 port. It's ideal for connecting to a wired Gigabit Ethernet network, transmitting digital audio and video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device and more-all at the same time.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video SignalsBy connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K Video and Digital AudioThe HDMI port supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. A DVI display may also be connected using an HDMI to DVI adapter (sold separately). HDCP 2.2 compliance allows you to stream 4K Amazon and Netflix content with no complications.

Accesses a Wired Gigabit Ethernet Network The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

USB Ports Connect Keyboards, Thumb Drives and Other USB Peripherals Two USB 3.2 Gen 1 ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support fast data transfer rates up to 5 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. Note: Host must support USB OTG (On-the-Go).

PD 2.0 Charging Port Charges Connected Device via AC Wall Charger The USB-C Power Delivery port supports power output up to 20V 3A (60W), which is sufficient for charging and powering the connected source device, such as an Android smartphone or Chromebook. Just connect the device's AC wall charger to the USB-C PD port. This port can also be used for transferring data up to 5 Gbps. Note: USB-C PD port does not support Quick Charge (QC).

### **Highlights**

- Transmits audio/video signals from sources supporting USB **DisplayPort Alt Mode**
- Supports Ultra HD 4K resolutions up to 3840 x 2160 @ 30 Hz for crystal-clear video
- Joins a wired 10/100/1000 Gigabit Ethernet network when no Wi-Fi is available
- Supports 20V 3A (60W) power output for fast-charging compatible mobile devices
- USB-C, USB-A and memory card ports allow connection of flash drives and other peripherals

#### **Applications**

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- · Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Transfer data to and from a USB flash drive or memory card
- Connect a microphone/headset to record a podcast or listen to music

#### System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with HDMI or DVI\* input
- Not for use with Thunderbolt monitors

\*Requires adapter (sold separately)

#### **Package Includes**

- U442-DOCK11-S USB-C Dock, Silver
- Owner's manual



Allows External Memory AccessMemory card slots support Micro SD and SD/MMC cards for transferring data to and from your connected computer, laptop or tablet. Both memory card slots can be used at the same time.

**Built-In USB-C Cable Connects in Either Direction**Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

**Ready to Use Right Out of the Package**The plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. The compact unit fits easily into a pocket, briefcase or laptop bag for connecting on the go. If additional power is required, the 5V DC power jack is compatible with power supplies (not included) equipped with a 3.5 x 1.35 x 9.5 millimeter output plug, a positive tip and a negative sleeve.

# **Specifications**

OVERVIEW	
UPC Code	037332213372
Product Type	Docking Station
Technology	HDMI; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); PD Charging
Host Connector	USB C (MALE)
VIDEO	
Number of Monitors Supported	1
Video Ports	HDMI (FEMALE)
Video Ports Details	HDMI 2.0; HDCP 2.2
Resolutions Supported	HDMI: 4K 30Hz (3840 x 2160)
Max Supported Video Resolution	HDMI: 3840 X 2160 (4K X 2K) @ 30HZ
Extended Mode	No
Mirror Mode	No
Max Supported Color Depth	24-bit True Color
Chroma Sub Sampling	4:4:4
DATA	
Data Ports	(1) USB C (FEMALE); (2) USB A (FEMALE)
Data Ports Details	(1) USB-C - USB 3.2 Gen 1 (5 Gbps); (2) USB-A - USB 3.2 Gen 1 (5 Gbps)
NETWORK	
Network Ports	RJ45 (FEMALE)
STORAGE	



Card Slots Details Both car	MALE); MICRO SD (FEMALE) ard readers can be used at the same time 0; 120; 127; 200; 208; 220; 230; 240	
INPUTVoltage Compatibility (VAC)100; 110Built-In Cable Length (ft.)0.49Built-In Cable Length (m)0.15Built-In Cable Length (in.)5.9Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Voltage Compatibility (VAC)100; 110Built-In Cable Length (ft.)0.49Built-In Cable Length (m)0.15Built-In Cable Length (in.)5.9Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3	0; 120; 127; 200; 208; 220; 230; 240	
Built-In Cable Length (ft.)0.49Built-In Cable Length (m)0.15Built-In Cable Length (in.)5.9Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3	0; 120; 127; 200; 208; 220; 230; 240	
Built-In Cable Length (m)0.15Built-In Cable Length (in.)5.9Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Built-In Cable Length (in.)5.9Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Built-In Cable Length (cm)15Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Bus PoweredYesProduct Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Product Length (in.)12Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Product Length (cm.)30.48Product Length (ft.)1Product Length (m.)0.3		
Product Length (ft.)1Product Length (m.)0.3		
Product Length (m.) 0.3		
BATTERY		
Battery Charging (5V/1.5A Port) No		
POWER		
External Power Supply Output 5V/2A		
External Power Supply DC Barrel OD: 3.5	5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve	
USB Power Delivery (PD) Charging Support Yes		
USB Power Delivery (PD) Charging 2.0		
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators White (P	Power), Green (Link), Yellow (Activity)	
CHARGING		
Total Charging Watts 60		
Charging Ports USB-C:	: 60W (20V 3A) Power Delivery (PD 2.0)	
Charging Ports / Amps (2) 0.9A	A; 3A	
PHYSICAL		
Color Silver		
Cable Jacket Rating VW-1		
Material of Construction Aluminiu		



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Shipping Weight (lbs.)     0.       Unit Dimensions (hwd / in.)     0.       Unit Packaging Type     B       Unit Weight (kg)     0.	0.80 x 5.70 x 3.20 0.30 0.67 x 4.7 x 2.2 30x	
Unit Dimensions (hwd / in.)     0.       Unit Packaging Type     B       Unit Weight (kg)     0.	0.67 x 4.7 x 2.2	
Unit Packaging Type     B       Unit Weight (kg)     0.		
Unit Weight (kg) 0.	Box	
Lipit Woight (lbc.)	0.10	
	.21	
ENVIRONMENTAL		
Operating Temperature Range 32	2 to 131 F (0 to 55 C)	
Storage Temperature Range 14	4 to 158 F (-10 to 70 C)	
Relative Humidity 50	% to 95% RH, Non-Condensing	
BTUs 1	5.7 BTU/Hr	
Power Consumption (Watts) 4.	.60	
Power Provided to Connected 5 Device(s) 5	V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C)	
COMMUNICATIONS		
Network Compatibility G	Gigabit Ethernet (10/100/1000)	
IEEE Standards Supported 8	02.3	
CONNECTIONS		
Ports 8	3	
Dock Connectors 2	2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA	
Side A - Connector 1 U	JSB C (MALE)	
Side B - Connector 1 H	IDMI (FEMALE); RJ45 (FEMALE)	
Side B - Connector 2 (2	2) USB 3.0 A (FEMALE)	
Side B - Connector 3 M	/ICRO SD (FEMALE)	
Side B - Connector 4 S	SD (FEMALE)	
Side B - Connector 5 U	JSB Type-C (FEMALE)	
Connector Plating N	lickel	
FEATURES & SPECIFICATIONS		
HDCP Specification 2.	2	
USB Hub Ports Y	/es	
Number of USB Hub Ports 2	2	
USB Specification U	JSB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required N	10	



[		
Recommended Category Cable	Cat5/5e/6 Cables	
UASP Support	No	
Auto MDIX Support	Yes	
Full Duplex Support	Yes	
Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
SD Card Specification	SD; Micro SD	
STANDARDS & COMPLIANCE		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies