

Overview

Introduction

PL2303 USB To UART (TTL) Communication Module supports Windows XP/7/8/10/11/ etc. and is compatible with 1.8V/2.5V/3.3V/5V logic voltage.

Feature

- Adopt the PL2303GS chip of the new version.
- Support windows XP/7/8/10/11/...
- 3x VCCIO power mode via jumpers setting.

VCCIO - 5V: 5V external power supply
VCCIO - 3.3V: 5V external power supply

- Without jumper cap: powered by external (1.8V/2.5V/3.3V/5V).
- Onboard 3 LED indicators: TXD, RXD, PWR.

Parameter

- Communication interface: USB/UART
- Chip: PL2303
- USB interface voltage: 5V
- UART interface voltage: 1.8V/2.5V/3.3V/5V
- Dimension: 16.51mm x 48.26mm

Resources

Document

- [Schematic](#)

Software

PL2303 USB UART Board V2



PL2303 USB UART Board (Type C)



- [Serial debugging assistant](#)
- [PL2303 driver program](#)
- [PuTTY Serial Port Monitors software](#)
- [PL2303G Linux driver](#)

Datasheet

- [PL2303](#)
- [PL2303TA](#)

Support

Technical Support

If you need technical support or have any feedback/review, please click the **Submit Now** button to submit a ticket, Our support team will check and reply to you within 1 to 2 working days. Please be patient as we make every effort to help you to resolve the issue.

Working Time: 9 AM - 6 AM GMT+8 (Monday to Friday)

[Submit Now](#)