

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Mikromedia 4 for Kinetis Capacitive FPI with bezel



PID: MIKROE-3920

Sound, connectivity & expandibility

A very popular WiFi module labeled as CC3100 enables WiFi connectivity. This module is the complete WiFi solution on a chip: it is a powerful WiFi network processor with the power management subsystem, offering the TCP/IP stack, powerful crypto engine with 256-bit AES support, WPA2 security, SmartConfig[™] technology, and much more.

Resource-demanding and complex audio processing tasks can be offloaded from the host MCU by utilizing a dedicated audio CODEC IC, labeled as VS1053B. This IC supports many different audio formats, commonly found on various digital audio devices.

State of the art power supply, Display & Graphics controller

A high-quality 5" TFT true-color display with a capacitive touch panel is the most distinctive feature of the mikromedia 4. The display has a resolution of 800 by 480 pixels, and it can display up to 16.7M of colors. This is a powerful graphics coprocessor, equipped with 1215KB of frame buffer memory. It also includes some advanced features such as the hardware accelerated display rotation, display mirroring, hardware windowing, dynamic backlight control, programmable color and brightness control, and more.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	mikromedia 7
Architecture	ARM (32-bit)
Display size	4.3" 480x272px
Resolution	480x272px
Graphic controller	SSD1963
Touch Screen	Capacitive
Silicon Vendor	NXP
mikroBUS No.	2
Frame Type	Bezel
Features	USB Type C,USB Host,SD Card,RF,ON/OFF switch,MP3,External DC source,Buzzer,Battery Powered,Battery for RTC,Batt. Chg. when OFF,Accel

Downloads

Mikromedia 4 for Kinetis Capacitive FPI with bezel schematic

Mikromedia 4 for Kinetis Capacitive FPI with bezel example on libstock

Mikromedia 4 for Kinetis Capacitive FPI with bezel Manual

Mikromedia 4 for Kinetis Capacitive FPI with bezel 2D and 3D files

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).