

This document was generated on 02/25/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0022284060

Status: **Active** 

Overview: SPOX Connector System

KK 254 Breakaway Header, Vertical, 6 Circuits, Tin (Sn) Plating, Mating Pin Length **Description:** 

6.09mm

**Documents:** 

3D Model Product Specification PS-10-07-001 (PDF)

3D Model (PDF) Packaging Specification PK-40873-0041-001 (PDF)

Drawing (PDF) RoHS Certificate of Compliance (PDF)

**Agency Certification** 

**CSA** LR19980 UL E29179

General

**PCB** Headers **Product Family** 

Series

**Application** Board-to-Board, Signal, Wire-to-Board

Overview **SPOX Connector System** 

**Product Name** KK 254

**UPC** 800753684034

**Physical** 

Breakaway Yes Circuits (Loaded) 6 Circuits (maximum) 6 Color - Resin Black Durability (mating cycles max) 25 First Mate / Last Break No Flammability 94V-0 Glow-Wire Capable No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Net Weight 0.367/g

Number of Rows Orientation Vertical PC Tail Length 3.18mm **PCB Locator** No **PCB** Retention None PCB Thickness - Recommended 1.60mm

Packaging Type Bag Pitch - Mating Interface 2.54mm Plating min - Mating 2.540µm Plating min - Termination 2.540µm Polarized to Mating Part No Polarized to PCB No Shrouded Nο Stackable No Surface Mount Compatible (SMC) Yes

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole



**EU ELV** 

**Not Relevant** 

**EU RoHS China RoHS** Compliant

**REACH SVHC** Not Contained Per -D(2020)9139-DC (19 Jan 2021)

**Halogen-Free** 

**Status** 

**Not Low-Halogen** 

For more information, please visit Contact US

China ROHS Green Image ELV Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

42375 Series

**Mates With** 

KK Crimp Housing 2695, 6471, 7880, KK

PC Board Connector 4455

**Electrical** 

Current - Maximum per Contact 4.0A Voltage - Maximum 500V

**Solder Process Data** 

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

235

**Material Info** 

Engineering Number 42375-0006

**Reference - Drawing Numbers** 

Packaging Specification PK-40873-0041-001
Product Specification PS-10-07-001

Sales Drawing SD-42375-001-001, SD-42375-001-002

This document was generated on 02/25/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION