



FEATURES

- * 198-300W Isolated Output
- * Efficiency to 91%
- * Low No Load Power Consumption
- * Fixed Switching Frequency
- * 4:1 Input Range
- * Regulated Outputs
- * Input Under-Voltage Protection
- * Over Temperature Protection
- * Over Voltage/Current Protection
- * Remote On/Off
- * Half-Brick Size Meet Industrial Standard
- * UL60950-1 2nd (Basic Insulation) Approval (Except 3.3Vout)
- * CB Test Certificate IEC60950-1 (Except 3.3Vout)
- * Meet EN50155 With External Circuits
- * Shock & Vibration Meet EN50155 (EN61373)
- * Fire & Smoke Meet EN45545-2
- * 5000m Operating Altitude

CHB300W-110S SERIES

198-300 WATT 4:1 INPUT DC-DC CONVERTERS



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		% EFF. (2)	CAPACITOR LOAD MAX.
			MIN.	MAX.	NO LOAD	FULL LOAD		
CHB300W-110S3V3	43-160 VDC	3.3VDC	0 mA	60 A	10 mA	2093 mA	86	60000uF
CHB300W-110S05	43-160 VDC	5 VDC	0 mA	60 A	10 mA	3099 mA	88	60000uF
CHB300W-110S12	43-160 VDC	12 VDC	0 mA	25 A	10 mA	3030 mA	90	25000uF
CHB300W-110S24	43-160 VDC	24 VDC	0 mA	12.5 A	10 mA	3064 mA	89	12500uF
CHB300W-110S28	43-160 VDC	28 VDC	0 mA	10.7 A	10 mA	3064 mA	89	10700uF
CHB300W-110S48	43-160 VDC	48 VDC	0 mA	6.25 A	10 mA	2997 mA	91	4700uF

NOTE:

1. Nominal Input Voltage 110 VDC.
2. Measure at Nominal Input Voltage.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cincon:

[CHB300W-110S05](#) [CHB300W-110S24](#) [CHB300W-110S48](#) [CHB300W-110S12](#) [CHB300W-110S28](#) [CHB300W-110S28N-C](#) [CHB300W-110S28-C](#) [CHB300W-110S28N](#) [CHB300W-110S24N](#) [CHB300W-110S48-C](#) [CHB300W-110S48N-C](#) [CHB300W-110S12-C](#) [CHB300W-110S24-C](#) [CHB300W-110S48N](#) [CHB300W-110S12N](#) [CHB300W-110S05-C](#) [CHB300W-110S05N](#) [CHB300W-110S24N-C](#) [CHB300W-110S12N-C](#) [CHB300W-110S05N-C](#)