

COMPLIANT

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939


Features

- Halogen free available upon request by adding suffix "-HF" Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates
- RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55℃ to +125℃ (SK52AFL-SK510AFL) -55℃ to +150℃(SK5150AFL-SK5200AFL) Storage Temperature: -55℃ to +150℃
- Typical Thermal Resistance: 120°C/W Junction To Ambient 30°℃/W Junction To Case


MCC Part	Device	Maximum Maximum		Maximum
Number	Marking	Recurrent	RMS	DC
		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
SK52AFL	SK52	20V	14V	20V
SK53AFL	SK53	30V	21V	30V
SK54AFL	SK54	40V	28V	40V
SK55AFL	SK55	50V	35V	50V
SK56AFL	SK56	60V	42V	60V
SK58AFL	SK58	80V	56V	80V
SK510AFL	SK510	100V	70V	100V
SK5150AFL	SK5150	150V	105V	150V
SK5200AFL	SK5200	200V	140V	200V



SK52AFL

SK5200AFL

Thru




Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	5.0A	TL = 100℃
Peak Forward Surge Current	I _{FSM}	100A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	VF SK52AFL-SK54AFL SK55AFL-SK56AFL SK58AFL-SK510AFL SK5150AFL SK5200AFL	0.55V 0.70V 0.85V 0.87V 0.90V	I _{FM} = 5.0A; T _A = 25℃
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R SK52AFL-SK58AFL SK58AFL-SK5200AFL	0.5mA 10mA 0.2mA 5mA	$T_A = 25^{\circ}C$ $T_A = 100^{\circ}C$ $T_A = 25^{\circ}C$ $T_A = 100^{\circ}C$
Typical Junction Capacitance	CJ SK52AFL-SK54AFL SK55AFL-SK56AFL SK58AFL-SK510AFL SK5150AFL SK5200AFL	300pF 210pF 170pF 150pF 110pF	Measured at 1.0MHz, V _R =4.0V

DIMENSIONS INCHES NOTE DIM MIN MAX MIN MAX .047 0.90 1.20 1.65 b .049 .065 1.25 .016 .116 0.10 0.40 .004 2.25 .173 .220 4.40 5.60 .181 .126 3.20 4.6 0.70

SUGGESTED SOLDER PAD LAYOUT



Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

www.mccsemi.com



SK52AFL THRU SK5200AFL







FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT








FIG. 2-TYPICAL FORWARD CHARACTERISTICS





FIG. 4-TYPICAL REVERSE CHARACTERISTICS



www.mccsemi.com



Ordering Information :

Device	Packing	
Part Number-TP	Tape&Reel: 10Kpcs/Reel	

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): SK54AFL-TP_SK56AFL-TP_SK510AFL-TP_SK5150AFL-TP_SK5200AFL-TP