

## N-channel 600 V, 0.186 $\Omega$ typ., 18 A MDmesh™ M2 Power MOSFET in a PowerFLAT™ 8x8 HV package

Datasheet - production data





Figure 1: Internal schematic diagram



### Features

| Order code | V <sub>DS@TJ max</sub> | R <sub>DS(on) max.</sub> | I <sub>D</sub> |
|------------|------------------------|--------------------------|----------------|
| STL24N60M2 | 650 V                  | 0.210 $\Omega$           | 18 A           |

- Extremely low gate charge
- Excellent output capacitance (C<sub>oss</sub>) profile
- 100% avalanche tested
- Zener-protected

### Applications

- Switching applications

### Description

This device is an N-channel Power MOSFET developed using MDmesh™ M2 technology. Thanks to its strip layout and an improved vertical structure, the device exhibits low on-resistance and optimized switching characteristics, rendering it suitable for the most demanding high efficiency converters.

Table 1: Device summary

| Order code | Marking | Package           | Packing       |
|------------|---------|-------------------|---------------|
| STL24N60M2 | 24N60M2 | PowerFLAT™ 8x8 HV | Tape and reel |

---

## Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Electrical ratings .....</b>                | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics .....</b>        | <b>4</b>  |
|          | 2.1 Electrical characteristics (curves).....   | 6         |
| <b>3</b> | <b>Test circuits .....</b>                     | <b>8</b>  |
| <b>4</b> | <b>Package information .....</b>               | <b>9</b>  |
|          | 4.1 PowerFLAT™ 8x8 HV package information..... | 10        |
|          | 4.2 PowerFLAT™ 8x8 HV packing information..... | 12        |
| <b>5</b> | <b>Revision history .....</b>                  | <b>14</b> |

# 1 Electrical ratings

**Table 2: Absolute maximum ratings**

| Symbol            | Parameter   | Value      | Unit             |
|-------------------|---|------------|------------------|
| $V_{GS}$          | Gate-source voltage   | $\pm 25$   | V                |
| $I_D^{(1)}$       | Drain current (continuous) at $T_C = 25\text{ }^\circ\text{C}$  | 18         | A                |
| $I_D^{(1)}$       | Drain current (continuous) at $T_C = 100\text{ }^\circ\text{C}$ | 12         | A                |
| $I_{DM}^{(1)(2)}$ | Drain current (pulsed)  | 72         | A                |
| $P_{TOT}^{(1)}$   | Total dissipation at $T_C = 25\text{ }^\circ\text{C}$           | 125        | W                |
| $dv/dt^{(3)}$     | Peak diode recovery voltage slope                               | 15         | V/ns             |
| $dv/dt^{(4)}$     | MOSFET $dv/dt$ ruggedness                                       | 50         | V/ns             |
| $T_{stg}$         | Storage temperature range                                       | -55 to 150 | $^\circ\text{C}$ |
| $T_j$             | Operating junction temperature range                            |            |                  |

**Notes:**

(1)the value is limited by package

(2)Pulse width limited by safe operating area.

(3) $I_{SD} \leq 18\text{ A}$ ,  $di/dt \leq 400\text{ A}/\mu\text{s}$ ;  $V_{DS(\text{peak})} < V_{(BR)DSS}$ ,  $V_{DD} = 400\text{ V}$ .

(4) $V_{DS} \leq 480\text{ V}$

**Table 3: Thermal data**

| Symbol                     | Parameter                            | Value | Unit                      |
|----------------------------|--------------------------------------|-------|---------------------------|
| $R_{thj\text{-case}}$      | Thermal resistance junction-case max | 1     | $^\circ\text{C}/\text{W}$ |
| $R_{thj\text{-pcb}}^{(1)}$ | Thermal resistance junction-pcb max  | 45    | $^\circ\text{C}/\text{W}$ |

**Notes:**

(1)When mounted on FR-4 board of  $\text{inch}^2$ , 2oz Cu.

**Table 4: Avalanche characteristics**

| Symbol   | Parameter  | Value | Unit |
|----------|--|-------|------|
| $I_{AR}$ | Avalanche current, repetitive or not repetitive (pulse width limited by $T_{j\text{max}}$ )                          | 3.5   | A    |
| $E_{AS}$ | Single pulse avalanche energy (starting $T_j = 25\text{ }^\circ\text{C}$ , $I_D = I_{AR}$ ; $V_{DD} = 50\text{ V}$ ) | 180   | mJ   |

## 2 Electrical characteristics

$T_C = 25\text{ °C}$  unless otherwise specified

**Table 5: On/off states**

| Symbol        | Parameter                         | Test conditions  | Min. | Typ.  | Max.     | Unit          |
|---------------|-----------------------------------|--|------|-------|----------|---------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage    | $V_{GS} = 0\text{ V}$ , $I_D = 1\text{ mA}$                                      | 600  |       |          | V             |
| $I_{DSS}$     | Zero gate voltage Drain current   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 600\text{ V}$                                  |      |       | 1        | $\mu\text{A}$ |
|               |                                   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 600\text{ V}$ ,<br>$T_C = 125\text{ °C}^{(1)}$ |      |       | 100      | $\mu\text{A}$ |
| $I_{GSS}$     | Gate-body leakage current         | $V_{DS} = 0\text{ V}$ , $V_{GS} = \pm 25\text{ V}$                               |      |       | $\pm 10$ | $\mu\text{A}$ |
| $V_{GS(th)}$  | Gate threshold voltage            | $V_{DS} = V_{GS}$ , $I_D = 250\text{ }\mu\text{A}$                               | 2    | 3     | 4        | V             |
| $R_{DS(on)}$  | Static drain-source on-resistance | $V_{GS} = 10\text{ V}$ , $I_D = 9\text{ A}$                                      |      | 0.186 | 0.210    | $\Omega$      |

**Notes:**

<sup>(1)</sup>Defined by design, not subject to production test.

**Table 6: Dynamic**

| Symbol               | Parameter                     | Test conditions  | Min. | Typ. | Max. | Unit     |
|----------------------|-------------------------------|--|------|------|------|----------|
| $C_{iss}$            | Input capacitance             | $V_{DS} = 100\text{ V}$ , $f = 1\text{ MHz}$ , $V_{GS} = 0\text{ V}$   | -    | 1060 | -    | pF       |
| $C_{oss}$            | Output capacitance            |  | -    | 55   | -    | pF       |
| $C_{rSS}$            | Reverse transfer capacitance  |  | -    | 2.2  | -    | pF       |
| $C_{oss\ eq.}^{(1)}$ | Equivalent output capacitance | $V_{DS} = 0\text{ to }480\text{ V}$ , $V_{GS} = 0\text{ V}$  | -    | 258  | -    | pF       |
| $R_G$                | Intrinsic gate resistance     | $f = 1\text{ MHz}$ open drain  | -    | 7    | -    | $\Omega$ |
| $Q_g$                | Total gate charge             | $V_{DD} = 480\text{ V}$ , $I_D = 18\text{ A}$ , $V_{GS} = 10\text{ V}$<br>(see <a href="#">Figure 15: "Gate charge test circuit"</a> ) | -    | 29   | -    | nC       |
| $Q_{gs}$             | Gate-source charge            |  | -    | 6    | -    | nC       |
| $Q_{gd}$             | Gate-drain charge             |  | -    | 12   | -    | nC       |

**Notes:**

<sup>(1)</sup> $C_{oss\ eq.}$  is defined as a constant equivalent capacitance giving the same charging time as  $C_{oss}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$

**Table 7: Switching times**

| Symbol       | Parameter           | Test conditions   | Min. | Typ. | Max. | Unit |
|--------------|---------------------|---|------|------|------|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 300\text{ V}$ , $I_D = 9\text{ A}$ , $R_G = 4.7\text{ }\Omega$ ,<br>$V_{GS} = 10\text{ V}$ (see <a href="#">Figure 14: "Switching times test circuit for resistive load"</a> ) and ( <a href="#">Figure 19: "Switching time waveform"</a> ) | -    | 14   | -    | ns   |
| $t_r$        | Rise time           |   | -    | 9    | -    | ns   |
| $t_{d(off)}$ | Turn-off delay time |   | -    | 60   | -    | ns   |
| $t_f$        | Fall time           |   | -    | 15   | -    | ns   |

Table 8: Source drain diode

| Symbol             | Parameter                     | Test conditions   | Min. | Typ. | Max. | Unit          |
|--------------------|-------------------------------|---|------|------|------|---------------|
| $I_{SD}^{(1)}$     | Source-drain current          |   | -    |      | 18   | A             |
| $I_{SDM}^{(1)(2)}$ | Source-drain current (pulsed) |   | -    |      | 72   | A             |
| $V_{SD}^{(3)}$     | Forward on voltage            | $V_{GS} = 0\text{ V}$ , $I_{SD} = 18\text{ A}$  | -    |      | 1.6  | V             |
| $t_{rr}$           | Reverse recovery time         | $I_{SD} = 18\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 60\text{ V}$ (see <a href="#">Figure 16: "Test circuit for inductive load switching and diode recovery times"</a> )  | -    | 332  |      | ns            |
| $Q_{rr}$           | Reverse recovery charge       |   | -    | 4    |      | $\mu\text{C}$ |
| $I_{RRM}$          | Reverse recovery current      |   | -    | 24   |      | A             |
| $t_{rr}$           | Reverse recovery time         | $I_{SD} = 18\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 60\text{ V}$ , $T_j = 150\text{ }^\circ\text{C}$<br>(see <a href="#">Figure 16: "Test circuit for inductive load switching and diode recovery times"</a> ) | -    | 450  |      | ns            |
| $Q_{rr}$           | Reverse recovery charge       |   | -    | 5.5  |      | $\mu\text{C}$ |
| $I_{RRM}$          | Reverse recovery current      |   | -    | 25   |      | A             |

**Notes:**

- (1)The value is limited by package.  
(2)Pulse width is limited by safe operating area  
(3)Pulsed: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%

## 2.1 Electrical characteristics (curves)









Figure 8: Capacitance variations




Figure 9: Normalized gate threshold voltage vs temperature




Figure 10: Normalized on-resistance vs temperature




Figure 11: Normalized V(BR)DSS vs temperature




Figure 12: Output capacitance stored energy








Figure 13: Source-drain diode forward characteristics



### 3 Test circuits





## 4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 4.1 PowerFLAT™ 8x8 HV package information

Figure 20: PowerFLAT™ 8x8 HV package outline





Table 9: PowerFLAT™ 8x8 HV mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    | 0.75 | 0.85 | 0.95 |
| A1   | 0.00 |      | 0.05 |
| A3   | 0.10 | 0.20 | 0.30 |
| b    | 0.90 | 1.00 | 1.10 |
| D    | 7.90 | 8.00 | 8.10 |
| E    | 7.90 | 8.00 | 8.10 |
| D2   | 7.10 | 7.20 | 7.30 |
| E1   | 2.65 | 2.75 | 2.85 |
| E2   | 4.25 | 4.35 | 4.45 |
| e    |      | 2.00 |      |
| L    | 0.40 | 0.50 | 0.60 |


Figure 21: PowerFLAT™ 8x8 HV footprint



All dimensions are in millimeters.

### 4.2 PowerFLAT™ 8x8 HV packing information

Figure 22: PowerFLAT™ 8x8 HV tape



All dimensions are in millimeters.

Figure 23: PowerFLAT™ 8x8 HV package orientation in carrier tape





Figure 24: PowerFLAT™ 8x8 HV reel



All dimensions are in millimeters.

## 5 Revision history

**Table 10: Document revision history**

| Date        | Revision | Changes  |
|-------------|----------|--|
| 11-Jun-2013 | 1        | First release.   |
| 28-Feb-2014 | 2        | Modified: $I_D$ (at $T_C = 100\text{ °C}$ ) value in Table 3.<br>Modified: $V_{SD}$ max value, figures 3 and 11.<br>Updated: Section 4: Package mechanical data – Minor text changes.  |
| 25-May-2016 | 3        | Updated features and description in cover page.<br>Updated package silhouette and <i>Figure 1: "Internal schematic diagram"</i> .<br>Updated <i>Section 4: "Test circuits"</i> and <i>Section 5.1: "PowerFLAT™ 8x8 HV package information"</i> .<br>Minor text changes |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[STL24N60M2](#)