



## SPECIFICATIONS

Feature	UT4102C
Bandwidth	100 MHz
Rise Time	≤3.5 ns
Sample Range	2GS/s
Refresh Rate	2000 wfms/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	24k
Sample Rate	Real time 2GS/s, Equivalent: 50GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and Alternate, Code
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, Optional: LAN and GPIB
Mathematics	Add, Subtract, Multiply, Divide, Reverse and FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Other Features	Digital Multimeter and Logic Analyzer, 6 Digits Frequency Meter, Special Dual Time Base, FFT

## GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey, White and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm (wide) x 165mm (high) x 165mm (deep)
Standard Accessories	Probe x 2 (1x, 10x switchable; Optional Purchase: 100x Probe), Logic Analyzer Probe x 1, Multimeter Probe x 2, Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	550 x 435 x 310mm (0.074 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13kg