

This document was generated on 04/14/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0431782002

Status: Active

Overview: Sabre Power Connector

Description: Sabre Crimp Terminal, Male, 14-16 AWG or double 18-20 AWG, 4.57mm Max.

Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact

Documents:

<u>Drawing (PDF)</u>
<u>Product Specification PS-44441-9999-001 (PDF)</u>
RoHS Certificate of Compliance (PDF)

Packaging Specification 431780000-PK-000 (PDF) Product Literature (PDF)

General

Product Family Crimp Terminals

Series <u>43178</u>

Application Power, Wire-to-Wire

Comments For double crimping of 18-20 AWG wire in a side-by-

side orientation.

Crimp Quality Equipment Yes

Overview <u>Sabre Power Connector</u>

Product Name Sabre

UPC 800754378390

Physical

Durability (mating cycles max) 25 Gender Male Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin Net Weight 0.565/qPackaging Type Reel Plating min - Mating 0.508µm Plating min - Termination 0.508um

Termination Interface: Style Crimp or Compression

Wire Insulation Diameter 4.57mm max.

Wire Size AWG 14, 16, 18+18, 20+20

Wire Size mm² N/A

Electrical

Current - Maximum per Contact 18.0A Voltage - Maximum 600V

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Packaging Specification 431780000-PK-000
Product Specification PS-44441-9999-001
Sales Drawing SD-43178-2XXX-001
Test Summary 444410000-TS-000



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ECHA_01_2020 (16 January 2020

Halogen-Free

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

43178 Series

Mates With

43375 Female Crimp Terminals

Use With

43680 Plug Housings

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Manual Activation638130600

and Deactivation

Tool

Manual Extraction 638130800

Tool

Hand Crimp Tool 638233100

for Male Flat Blade Crimp Terminals

Hand Crimp Tool <u>638233200</u>

for Male Flat Blade Crimp Terminals

Modular Crimp 638233270

Head for the Battery 638160200 and Air 638160100 Tools

Terminator Die - <u>638404100</u>

Doubles

Terminator Die - Full 638404200

Radius Insulation &

Doubles

Terminator Die - side 638404300

by Side Insulation

Mini-Mac Applicator, 638919100

For Standard "B" Style Insulation

Crimps

FineAdjust Applicator 639013100

for Male Flat Blade

Crimp Terminals

FineAdjust Applicator 639013200

for Male Flat Blade

Crimp Terminals

T2 Terminator for <u>639113200</u>

Male Flat Blade Crimp Terminal

This document was generated on 04/14/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION