

This document was generated on 04/01/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0334720601 | | | |
|--|-------------------------------|---|--|-------------------------------------|
| Status: | | | | |
| ACINC | | | Ser. S | |
| Overview: | | | Tiol | 8 |
| Description: | | | | |
| | A, without Connector Position | Assurance, Black | | |
| | | | 4 | - |
| Documents: | | | | TTT |
| <u>3D Model (PDF)</u> | | Application Specification AS-33611-001-001 (PDF) | R | |
| Drawing (PDF) | | Packaging Specification PK-31300-903-001 (PDF) | | - |
| <u>3D Model</u> | | Packaging Specification PK-33472-001-001 (PDF) | | |
| | <u>PS-33472-000-001 (PDF)</u> | RoHS Certificate of Compliance (PDF) | Series image | e - Reference only |
| Application Specification AS-33472-100-001 (PDF) | | | | |
| | | | EU ELV | |
| General | | | Compliant | |
| Product Family | | Crimp Housings | EU RoHS | China RoHS |
| Series | | <u>33472</u> | Compliant | |
| Application | | Power, Wire-to-Board, Wire-to-Wire | REACH SVHC | |
| Comments | formation | No Connector Position Assurance (CPA) | Not Contained Per - | |
| More Detailed Tech Ir | normation | http://uscar.org/guest/teams/10/Electrical-Wiring- Component-Applications -Partnership | ECHA_01_2020 (16 | |
| Overview | | MX150 Sealed and Unsealed Connector System | January 2020 | |
| Product Name | | MX150 Sealed and Onsealed Connector System MX150 | Halogen-Free | |
| UPC | | 800756537443 | Status | |
| 010 | | 000700007440 | Low-Halogen | |
| Physical | | | | n, please visit <u>Contact US</u> |
| Circuits (maximum) | | 6 | | - |
| Color - Resin | | Black | China ROHS | Green Image |
| Gender | | Receptacle | ELV | Compliant |
| Glow-Wire Capable | | No | RoHS Phthalates | Not Contained |
| Keying to Mating Part | | Yes | | |
| Lock to Mating Part | | Yes | | |
| Material - Resin | | Modified Polystyrene Alloy | Search Parts in this Series 33472 Series | |
| Net Weight | | 9.430/g | | |
| Number of Rows | | 2 In dividual Call | | |
| Packaging Type | | Individual Cell | Mates With | |
| Panel Mount Bitch Mating Interface | | No 2 50mm | MX150 Male Sealed Connector 33482 | |
| Pitch - Mating Interface Polarized to Mating Part | | 3.50mm Yes | <pre> <br <="" td=""/></pre> | |
| Stackable | an | No | Sealed Connector | 348403410 |
| Temperature Range - | Operating | -40° to +125°C | | |
| | operating | | Use With | |
| Solder Process Data | | | | erminal <u>33012</u> , <u>33001</u> |
| Lead-freeProcess Cap | pability | N/A | | d Receptacle Cavity |
| Material Info | | | Plug <u>343454001</u> < 349510610 , 3495 | br>MX150 Backshell 10620 |
| Reference - Drawing | Numbers | | | |
| Application Specificati | | AS-33472-100-001, AS-33611-001-001 | | |
| Packaging Specification | | PK-31300-903-001, PK-33472-001-001 | | |
| Product Specification | | PS-33472-000-001 | | |
| Sales Drawing | | 334720602-001, SD-33472-0001-001, | | |
| 30.00 2.00mg | | SD-33472-0002-002 | | |
| 1 | | | | |
| | | | | |

Downloaded from Arrow.com.