

Liquid Flux Alcohol-Based No-Clean in 30ml (1.0oz) Squeeze Bottle w/tip

Product Highlights

- No-Clean
- Low solids
- Alcohol-Based
- Ideal for all rework, solder, and de-solder applications
- Excellent wetting
- Easily cleaned with isopropyl alcohol (IPA)
- Can be used with Leaded and Lead-Free applications

RoHS 3 and REACH compliant



Specifications

| | |
|----------------------|---|
| Flux Type: | No-Clean Liquid (for Leaded and Lead-Free applications) |
| Flux Classification: | ORL0 |
| Specific Gravity: | 0.8 |
| Packaging: | 30ml Squeeze Bottle |
| Shelf Life: | Refrigerated >24 months, Unrefrigerated >24 months |

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product requires ground shipping. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground will not impact this product's stated shelf life.

Cleaning

This is a water-soluble liquid flux; post-use cleaning is required. Clean with water or isopropyl alcohol (IPA).

Conforms to the following Industry Standards:

| | |
|--|-----|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| RoHS 3 Directive 2015/863/EU: | Yes |