


## Description


The AO4443 uses advanced trench technology to provide excellent  $R_{DS(ON)}$ , low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a Battery protection or in other Switching application.



## General Features

$V_{DS} = -40V$   $I_D = -8A$

$R_{DS(ON)} < 37m\Omega$  @  $V_{GS}=10V$



## Application

Battery protection

Load switch

Uninterruptible power supply



## Absolute Maximum Ratings ( $T_A=25^\circ C$ )

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-Source Voltage ( $V_{GS}=0V$ )	-40	V
$V_{GS}$	Gate-Source Voltage ( $V_{DS}=0V$ )	$\pm 20$	V
$I_D$	Drain Current-Continuous( $T_c=25^\circ C$ )	-20	A
	Drain Current-Continuous( $T_c=100^\circ C$ )	-8	A
$I_{DM}$ (pulse)	(Note 1) Drain Current-Continuous@ Current-Pulsed	-20	A
$P_D$	Maximum Power Dissipation( $T_c=25^\circ C$ )	37.5	W
	Maximum Power Dissipation( $T_c=100^\circ C$ )	19	W
$T_J, T_{STG}$	Operating Junction and Storage Temperature Range	-55 To 175	°C
$R_{JC}$	Thermal Resistance,Junction-to-Case	4	°C/W

**-40V P-Channel Enhancement Mode MOSFET****Electrical Characteristics (TA=25°C unless otherwise noted)**


<b>Symbol</b>	<b>Parameter</b>	<b>Conditions</b>	<b>Min</b>	<b>Typ</b>	<b>Max</b>	<b>Unit</b>
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V I <sub>D</sub> =-250μA	-40			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =-32V, V <sub>GS</sub> =0V			-1	μA
I <sub>GSS</sub>	Gate-Body Leakage Current	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V			±100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250μA	-1	-2	-3	V
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =-5V, I <sub>D</sub> =-10A		25		S
R <sub>DSD(ON)</sub>	Drain-Source On-State Resistance	V <sub>GS</sub> =-10V, I <sub>D</sub> =-20A		35	46	mΩ
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-10A		42	52	mΩ
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =-25V, V <sub>GS</sub> =0V, f=1.0MHz		840		pF
C <sub>oss</sub>	Output Capacitance			92		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			60		pF
t <sub>d(on)</sub>	Turn-on Delay Time	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-20V, R <sub>L</sub> =1.6 , R <sub>GEN</sub> =3		5		nS
t <sub>r</sub>	Turn-on Rise Time			12		nS
t <sub>d(off)</sub>	Turn-Off Delay Time			20		nS
t <sub>f</sub>	Turn-Off Fall Time			4.5		nS
Q <sub>g</sub>	Total Gate Charge	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-20V, I <sub>D</sub> =-15A		20		nC
Q <sub>gs</sub>	Gate-Source Charge			2.5		nC
Q <sub>gd</sub>	Gate-Drain Charge			4.5		nC
I <sub>SD</sub>	Source-Drain Current(Body Diode)				-20	A
V <sub>SD</sub>	Forward on Voltage	V <sub>GS</sub> =0V, I <sub>S</sub> =-20A			-1.2	V

Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature


**Switch Time Test Circuit and Switching Waveforms:**

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS (Curves)**


**Figure1. Power Dissipation**




**Figure2. Drain Current**



**Figure3. Output Characteristics**




**Figure4. Transfer Characteristics**




**-40V P-Channel Enhancement Mode MOSFET**


**Figure5. Capacitance**




**Figure6. R<sub>DS(ON)</sub> vs Junction Temperature**




**Figure7. V<sub>GS(th)</sub> vs Junction Temperature**




**Figure8. Gate Charge Waveforms**



**Figure9. Normalized Maximum Transient Thermal Impedance**




## SOP8 Package outline



Symbol	Dim in mm		
	Min	Nor	Max
A	1.350	1.550	1.750
A1	0.100	0.175	0.250
A2	1.350	1.450	1.550
b	0.330	0.420	0.510
c	0.170	0.210	0.250
D	4.800	4.900	5.000
e	1.270(BSC)		
E	5.800	6.000	6.200
E1	3.800	3.900	4.000
L	0.400	0.835	1.2700
o	0°	4°	8°

## Marking



## Ordering information

Order code	Package	Baseqty	Deliverymode
UMW AO4443	SOP-8	3000	Tape and reel