## UNCONTROLLED DOCUMENT

| PART NUMBER  |
|--------------|
| SSF-LXH303GD |

REV.

| REV. | E.C.N. NUMBER AND REVISION COMMENTS | DATE     |
|------|-------------------------------------|----------|
| Α    | REDRAWN.                            | 12.6.93  |
| В    | CHANGED DIMS.                       | 12.16.93 |
| С    | UPDATED OPER. SPECS.                | 10.12.94 |
| D    | E.C.N. #10BRDR. & REDRAWN.          | 9.2.98   |
| Ε    | E.C.N. #10BRDR.                     | 4.6.01   |

| 4.03 [0.159]                                     | 2.50 [0.098] | 5.26 [0.207] |
|--|--------------|--------------|
|  |              |              |
| Ø2.90 [Ø0.114]                                   |              | (2)          |
| ( + ) 6.33 [0.3                                  | 249]         | ( )          |
| 3.17 [0.125]                                     | 1)           |              |
| <del>                                     </del> |              | 040.504053   |
|  |              | 3.18 [0.125] |
| ANDDE - 0.50 [ SQR. (2                           |              | 1            |
| 2.54 [0.100]                                     | ==           | 4.00 [0.157] |

| ELECTRO-OPTICAL CHA | ARACTERI: | STICS TA=25°C | ;   | I <sub>f</sub> =20mA |                      |
|---------------------|-----------|---------------|-----|----------------------|----------------------|
| PARAMETER           | MIN       | TYP           | MAX | UNITS                | TEST COND            |
| PEAK WAVELENGTH     |           | 565 (GREEN)   |     | nm                   |                      |
| FORWARD VOLTAGE     |           | 2.2           | 2.6 | ٧f                   |                      |
| REVERSE VOLTAGE     | 5.0       |               |     | $v_r$                | Ir=100µA             |
| AXIAL INTENSITY     |           | 30            |     | mcd                  | $I_f = 20 \text{mA}$ |
| VIEWING ANGLE       |           | 60            |     | 2x theta             |                      |
| EMITTED COLOR:      | GREEN     |               |     |                      |                      |
| EPOXY LENS FINISH:  | GREEN     | DIFFUSED      |     |                      |                      |
|                     |           |               |     |                      |                      |

## LIMITS OF SAFE OPERATION AT 25°C

| MAX        | UNITS                                    |
|------------|--|
| 150        | mA                                       |
| 25         | mA                                       |
| 105        | mW                                       |
| - 1.6      | mW/°C                                    |
| -40 TO +85 | ·C                                       |
| + 260      | <b>.</b> C                               |
|            | 3 SEC. MAX                               |
|            | 150<br>25<br>105<br>- 1.6<br>- 40 TO +85 |

<sup>\*</sup> t<10µS

## NOTES:

- 1. SSL-LX3044GD, GREEN LED.
- 2. SSH-LXH303 HOLDER, BLACK NYLON, UL 94V-0.

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.= +0.00 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD SIZE=±0.05 (±0.002), LEAD SIZE=±0.05 (±0.003). MIN=+DECIMAL PRECISION MAX.= +0.00 (±0.002).

REV.

PART NUMBER
SSF-LXH303GD

T-3 (T-1) LED FAULT INDICATOR, 565nm GREEN LED, GREEN DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



CT

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE:

Y: DATE: 9.11.91 PAGE: 1 OF 1 SCALE: N/A

E D

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSF-LXH303GD