

## This document was generated on 11/19/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0743209010</u>			
Status:	S: Active			
Overview:				
Description:		tal/Analog Visual Interface, PCB Receptacle, Panel Mount,		The second second
		Angle, with Beveled Metal Pins, 0.76µm Gold (Au), Lead-Free,		
	Screw Hole, 4-40 Three			the share of
				and the
Documents:		Draduct Cracification TC 74220 004 004 (DDE)	Series imag	e - Reference only
<u>3D Model</u>		Product Specification TS-74320-001-001 (PDF) Packaging Specification PK-74320-010-002 (PDF)		
<u>3D Model (PDF)</u>			EU ELV	
Drawing (PDF) Broduct Specification		RoHS Certificate of Compliance (PDF)	Not Relevant	
Product Specification	<u>n PS-74320-001 (PDF)</u>		EU RoHS	China RoHS
Agency Certificatio	n		Compliant	
UL		E29179	REACH SVHC	
UL		E29179	Not Contained Per -	-
General			D(2020)4578-DC (2	
Product Family		I/O Connectors	June 2020)	
Series		74320	Halogen-Free	
Application		Wire-to-Board	Status	
Comments		DDWG (Digital Display Working Group) Standard	Low-Halogen	
Component Type		Receptacle		n, please visit <u>Contact Us</u>
Overview		MicroCross DVI Connectors and Cable Assemblies		n, please visit <u>Contact Os</u>
Product Name		MicroCross DVI Connectors and Cable Assemblies MicroCross DVI	China ROHS	Green Image
		N/A	ELV	Not Relevant
Type UPC		800754861878	RoHS Phthalates	Not Contained
		00010-001010		
Physical Boot Color		N/A		
		29	Search Parts in this Series	
Circuits (Loaded) Circuits (maximum)		29	74320 Series	
Color - Resin		Natural		
	cles max)	100	Mates With	
Durability (mating cycles max)		94V-0	<u>88744</u> , <u>74323</u>	
Flammability				
Gender Kaving to Mating Part		Receptacle		
Keying to Mating Part		Yes		
Lock to Mating Part Material - Metal		Yes Coppor Alloy	Hex Screw Kit <u>717811000</u> or <u>717812000</u>	
	ting	Copper Alloy Gold		
Material - Plating Ma		Tin		
Material - Plating Termination				
Net Weight Number of Rows		6.714/g		
		3 Bight Anglo		
Orientation		Right Angle		
PC Tail Length PCB Locator		2.34mm Yes		
PCB Locator PCB Retention				
		Yes		
Packaging Type		Tray		
Panel Mount		Yes 1.00mm		
Pitch - Mating Interfa		1.90mm		
Pitch - Termination I	піепасе	1.90mm		
Plating min - Mating	- C	0.762µm		
Plating min - Termin		2.540µm		
Polarized to Mating I	Part	Yes		
Polarized to PCB		Yes		
Ports		1		
Surface Mount Com	patible (SMC)	No		
Temperature Range		-20° to +85°C		

Termination Interface: Style	Through Hole	
Waterproof / Dustproof	No	
Wire Size AWG	N/A	
Electrical		
Current - Maximum per Contact	3.0A	
Grounding to Panel	Yes	
Shield Type	Full Shield	
Shielded	Yes	
Voltage - Maximum	40V AC (RMS)	
Solder Process Data		
Lead-freeProcess Capability	WAVE	
Material Info		
Reference - Drawing Numbers		
Packaging Specification	PK-74320-010-002	
Product Specification	PS-74320-001, TS-74320-001-001	
Sales Drawing	SD-74320-026-000	

## This document was generated on 11/19/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION