


ULR

Chip Type, High Voltage.



For SMD


- Chip Type, high Voltage.
- Applicable to automatic mounting machine using carrier tape.
- Compliant to the RoHS directive (2011/65/EU,(EU)2015/863).
- AEC-Q200 compliant. Please contact us for details.



Specifications

Item	Performance Characteristics					
Category Temperature Range	-40 to +105°C					
Rated Voltage Range	160 to 500V					
Rated Capacitance Range	2.7 to 39μF					
Capacitance Tolerance	±20% at 120Hz, 20°C					
Leakage Current	After 1 minute's application of rated voltage at 20°C, leakage current is not more than 0.04CV +100(μA).					
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C					
	Rated voltage (V)	160	200	250	400	450
Stability at Low Temperature	Measurement frequency: 120Hz					
	Rated voltage (V)	160	200	250	400	450
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 3000 hours at 105°C.					
	Capacitance change	Within ±20% of the initial capacitance value				
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.					
	tan δ	200% or less than the initial specified value				
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the characteristic requirements listed at right when they are removed from the plate.					
	Leakage current	Less than or equal to the initial specified value				
Marking	Black print on the case top.					


Chip Type



φD×L (mm)	8×10	10×10	10×13.5
A	2.9	3.2	3.2
B	8.3	10.3	10.3
C	8.3	10.3	10.3
E	3.1	4.5	4.5
L	10	10	13.5
H	0.8 to 1.1	0.8 to 1.1	0.8 to 1.1

Voltage	V	160	200	250	400	450	500
Code	2C	2D	2E	2G	2W	2H	

Type numbering system (Example : 400V 8.2μF)



Dimensions

Cap.(μF)	Code	160		200		250		400		450		500	
		2C	2D	2E	2G	2W	2H						
2.7	2R7												
3.9	3R9												
4.7	4R7												
5.6	5R6												
6.8	6R8												
8.2	8R2												
10	100												
12	120												
15	150												
22	220												
27	270												
33	330												
39	390												

Rated ripple current (mArms) at 105°C 120Hz

Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.80	1.00	1.25	1.40	1.60

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[ULR2D120MNL1GS](#) [ULR2E100MNL1GS](#) [ULR2E150MNL1GS](#) [ULR2G4R7MNL1GS](#) [ULR2H2R7MNL1GS](#)
[ULR2G120MNL1GS](#) [ULR2C270MNL1GS](#) [ULR2D220MNL1GS](#) [ULR2W100MNL1GS](#) [ULH2W5R6MNL1GS](#)
[ULR2C390MNL1GS](#) [ULR2W3R9MNL1GS](#) [ULR2H3R9MNL1GS](#) [ULR2C150MNL1GS](#) [ULR2H5R6MNL1GS](#)
[ULR2G8R2MNL1GS](#) [ULR2E220MNL1GS](#) [ULR2D330MNL1GS](#)