							REV.	DATE	DESCRIPTION	١
							NC	06/01/99	INITIAL RELEA	\SE
							A	05/01/04	UPDATE DRAWING	FORMAT
				13.10 [.516]		11.60 [ 	-36UNS-			
1					IN MULINETERS, CANENSONS IN [] ARE IN INCHES AND FOR OLISTONER REFERANCE DALY.	DRAWN G.R.S.	05/01/0	74	Amphenol C	onnex
3					unleas otherwise specified Toleranged for Willimeters are: 0.5 — 8mm ± 0.20mm	GHECKED		PART DESC		
					8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm	ISSUED				
4	CONTACT PIN	BER. COPPER BRASS	COLD	1	unlessi otherwise brechted Tölerances för ing-leb arei	0.FTT			SMA MALE TO FEMALE R/	A ADAPTOR
-				-	$.020315 = \pm 0.007^{"}$	""" 1 OF 1				
5	INSULATOR	TEFLÔN	NATURAL	1				PART NO.		
i	insulator Housing/Body	TEFLON BRASS	GOLD	1	$.315 - 1.180 = \pm 0.015^{"}$ 1.180 - 4.724 = ± 0.020"			PART NO.	132172 132172.DWG	A <sup>bize</sup> A <sup>scale</sup> N

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: <u>132172</u>