

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

www.tripplite.com

ECO-Surge 7-Outlet Surge Protector, 6 ft. (1.83 m) Cord, 1080 Joules, 6 Individually Controlled Outlets, Black Housing

MODEL NUMBER: TLP76MSGB











Environmentally friendly surge protector with individually controlled outlets safeguards your PC, printer, scanner, router, phone, fax, modem and other home/office electronics against dangerous surges, spikes and line noise.

#### Description

The TLP76MSGB ECO-Surge™ 7-Outlet Surge Protector protects more than just your vital electronics. It's an ideal green protection solution for your bottom line and the environment. Its energy-saving outlet configuration reduces waste (and costs) by cutting AC power to devices that aren't being used.

One NEMA 5-15R outlet is always on for a device that requires constant power, such as a router or DVR. The other six NEMA 5-15R outlets have individual on/off switches, so if you aren't using the device plugged into it, you can power off the outlet to save energy. Another illuminated on/off switch provides one-touch control to all outlets except the one that is always on.

Recommended for your home or office, the ECO-Surge Protector features 1080 joules to defend your components against even the strongest surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP76MSGB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

An integrated circuit breaker protects all outlets and automatically shuts down connected equipment in case of overload. The 6-ft. (1.83 m) AC power cord with NEMA 5-15P plug allows the black surge protector to reach distant outlets.

#### **Features**

### **Highlights**

- 7 NEMA 5-15R outlets—6 with individual on/off switches
- 1080-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- Automatic shutoff protects against dangerous overloads
- 6-ft. (1.83 m) AC power cord with NEMA 5-15P plug

## **Package Includes**

- TLP76MSGB ECO-Surge 7-Outlet Surge Protector
- · Owner's manual



**ECO-Surge Protector with Green Power-Saving Outlets**6 NEMA 5-15R outlets have individual on/off switches to cut power to devices not being used, which saves energy and moneyOne NEMA 5-15R outlet stays powered on 24/7 for essential devices, such as a router or DVRMaster on/off switch provides one-touch control over all outlets except the "always on" outletAccommodates up to 4 bulky transformer plugs

1080-Joule Surge Protection for Home or Office Electronics Protects your computer, printer, scanner, router, modem and other electronics against even the strongest surges and spikesFull normal mode (H-N) and common mode (N-G/H-G) line surge suppressionFilters out disruptive EMI/RFI line noise that can cause equipment damage or data lossExceeds IEEE 587 Category A and B surge suppression specifications

**Premium Safety Features**Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LEDs confirm surge protection status and "always on" connection at a glanceConforms to current UL 1449 3rd Edition safety standards

**Fits Effortlessly Into Your Workstation**6-ft. (1.83 m) AC power cord with NEMA 5-15P plug conveniently reaches distant outletsKeyhole slots on bottom panel provide convenient wall or desk mounting optionsBlack plastic housing designed for long life

**Backed by Tripp Lite's Ultimate Lifetime Insurance**\$25,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

# **Specifications**

OVERVIEW		
UPC Code	037332205810	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	72000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
ОИТРИТ		
Output Volt Amp Capacity (VA)	120	
Output Watt Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output (Watts)	1800	





Output Receptacles	(7) 5-15R	
Transformer Accommodation	(4) Yes	
Right-Angle Outlets	Yes	
Individually Controllable Load Banks	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	1 x Lighted Master Switch & 6 x Lighted Receptacle Switches	
LED Indicators	Protected (Green)" & Always On Receptacle (Red)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	<1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression.	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	400v	
EMI / RFI Filtering	Up to 40 dB	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Material of Construction  Antimicrobial	Plastic No	
Antimicrobial	No	
Antimicrobial  Power Cord Color	No Black	
Antimicrobial  Power Cord Color  Housing Color	No Black Black	
Antimicrobial  Power Cord Color  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement	No Black Black No	
Antimicrobial  Power Cord Color  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)	No Black Black No 300mm	
Antimicrobial  Power Cord Color  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Receptacle Color	No Black Black No 300mm Black	
Antimicrobial  Power Cord Color  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / cm)	No Black Black No 300mm Black 5.08 x 10.67 x 43.18	





	T	
Unit Dimensions (hwd / cm)	3.56 x 8.64 x 38.1	
Unit Dimensions (hwd / in.)	1.40 x 3.40 x 15	
Unit Weight (kg)	0.70	
Unit Weight (lbs.)	1.54	
Input Cord Color	Black	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Canada	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>