

This document was generated on 02/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0353630960		
Status:	Active		
Active		ard Connector System	
Description:	<u>Sherlock Wire-to-Board Connector System</u> 2.00mm Pitch Sherlock Wire-to-Board Header, Right-Angle, with Positive Lock, 9 Circuits		
Documents:			
3D Model		<u> 3D Model (PDF)</u>	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Agency Certificatio	n		Series image - Reference only
CSA		LR19980	
UL		E29179	EUELV
General			Not Relevant
Product Family		PCB Headers	EU RoHS China RoHS
Series		35363	Compliant
Application		Signal, Wire-to-Board	REACH SVHC
Overview		Sherlock Wire-to-Board Connector System	Not Contained Per -
Product Name		Sherlock	D(2020)9139-DC (19
UPC		822348260492	Jan 2021)
010		022040200402	Halogen-Free
Physical			Status
Breakaway		No	
Circuits (Loaded)		9	Low-Halogen
Circuits (maximum)		9	For more information, please visit Contact US
Color - Resin		Natural	China ROHS Green Image
Durability (mating cy	rcles max)	30	ELV Not Relevant
First Mate / Last Break		No	RoHS Phthalates Not Contained
Flammability		94V-0	Kons Filinalales Not Contained
Glow-Wire Capable		No	
Guide to Mating Part		No	
Keying to Mating Part		None	Search Parts in this Series
Lock to Mating Part		Yes	<u>35363</u> Series
Material - Plating Mating		Tin	
Material - Plating Mating Material - Plating Termination			Mates With
Material - Plating Termination Material - Resin		Tin	<u>35507</u> Sherlock Wire-to-Board Housing
		Nylon	<u>33307</u> Shehock Wile-to-Doald Housing
Net Weight		0.600/g	
Number of Rows		1 Dialat An ala	
Orientation		Right Angle	
PC Tail Length		3.20mm	
PCB Locator		No	
PCB Retention		Yes	
PCB Thickness - Recommended		1.60mm	
Packaging Type		Bag	
Pitch - Mating Interface		2.00mm	
Polarized to Mating Part		Yes	
Polarized to PCB		No	
Shrouded		Partial	
Stackable		No	
Surface Mount Comp	patible (SMC)	No	
Temperature Range - Operating		-40° to +105°C	
Termination Interface		Through Hole	
Electrical			
	per Contact	2.0A	
Current - Maximum per Contact Voltage - Maximum		125V	
voltage - Maximum		1200	

Downloaded from Arrow.com.

Material Info

Reference - Drawing Numbers Sales Drawing

SD-35363-002-001, SD-35363-002-002, SD-35363-002-003

This document was generated on 02/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION