



## Standard Avalanche SMD Rectifier



SMA (DO-214AC)



### FEATURES

- Low profile package
- Ideal for automated placement
- Controlled avalanche characteristics
- Glass passivated pellet chip junction
- Low reverse current
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- AEC-Q101 qualified available
  - Automotive ordering code: base P/NHE3 or P/NHM3
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



RoHS COMPLIANT HALOGEN FREE

### DESIGN SUPPORT TOOLS AVAILABLE



| PRIMARY CHARACTERISTICS |  |
|-------------------------|--|
| $I_{F(AV)}$             | 1.5 A                                      |
| $V_{RRM}$               | 200 V, 400 V, 600 V, 800 V, 1000 V, 1600 V |
| $I_{FSM}$               | 30 A                                       |
| $I_R$                   | 1.0 $\mu$ A                                |
| $V_F$                   | 1.15 V                                     |
| $E_R$                   | 20 mJ                                      |
| $T_J$ max.              | 150 °C                                     |
| Package                 | SMA (DO-214AC)                             |
| Circuit configuration   | Single                                     |

### TYPICAL APPLICATIONS

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, automotive, and telecommunication.

### MECHANICAL DATA

**Case:** SMA (DO-214AC)  
 Molding compound meets UL 94 V-0 flammability rating  
 Base P/N-E3 - RoHS-compliant, commercial grade  
 Base P/N-M3 - halogen-free, RoHS-compliant, commercial grade  
 Base P/NHE3\_X - RoHS-compliant and AEC-Q101 qualified  
 Base P/NHM3\_X - halogen-free, RoHS-compliant and AEC-Q101 qualified  
 (“\_X” denotes revision code e.g. A, B,...)  
**Terminals:** matte tin plated leads, solderable per J-STD-002 and JESD 22-B102  
 E3, M3, HE3, HM3 suffix meet JESD 201 class 2 whisker test  
**Polarity:** color band denotes the cathode end

| MAXIMUM RATINGS ( $T_A = 25\text{ °C}$ unless otherwise noted)   |                |             |        |        |        |        |        |      |
|--|----------------|-------------|--------|--------|--------|--------|--------|------|
| PARAMETER  | SYMBOL         | BYG10D      | BYG10G | BYG10J | BYG10K | BYG10M | BYG10Y | UNIT |
| Device marking code  |                | BYG10D      | BYG10G | BYG10J | BYG10K | BYG10M | BYG10Y |      |
| Maximum repetitive peak reverse voltage  | $V_{RRM}$      | 200         | 400    | 600    | 800    | 1000   | 1600   | V    |
| Average forward current  | $I_{F(AV)}$    | 1.5         |        |        |        |        |        | A    |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load  | $I_{FSM}$      | 30          |        |        |        |        |        | A    |
| Pulse energy in avalanche mode, non repetitive (inductive load switch off)<br>$I_{(BR)R} = 1\text{ A}$ , $T_J = 25\text{ °C}$ (for BYG10D thru BYG10M)<br>$I_{(BR)R} = 0.4\text{ A}$ , $T_J = 25\text{ °C}$ (for BYG10Y) | $E_R$          | 20          |        |        |        |        |        | mJ   |
| Operating junction and storage temperature range   | $T_J, T_{STG}$ | -55 to +150 |        |        |        |        |        | °C   |



| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |  |                         |                 |        |        |        |        |        |        |      |
|--|--|-------------------------|-----------------|--------|--------|--------|--------|--------|--------|------|
| PARAMETER  | TEST CONDITIONS  |                         | SYMBOL          | BYG10D | BYG10G | BYG10J | BYG10K | BYG10M | BYG10Y | UNIT |
| Maximum instantaneous forward voltage <sup>(1)</sup>                       | I <sub>F</sub> = 1 A   | T <sub>J</sub> = 25 °C  | V <sub>F</sub>  | 1.1    |        |        |        |        |        | V    |
|  | I <sub>F</sub> = 1.5 A   |                         |                 | 1.15   |        |        |        |        |        |      |
| Maximum DC reverse current   | V <sub>R</sub> = V <sub>RRM</sub>  | T <sub>J</sub> = 25 °C  | I <sub>R</sub>  | 1      |        |        |        |        |        | µA   |
|  |  | T <sub>J</sub> = 100 °C |                 | 10     |        |        |        |        |        |      |
| Maximum reverse recovery time  | I <sub>F</sub> = 0.5 A, I <sub>R</sub> = 1.0 A, I <sub>rr</sub> = 0.25 A |                         | t <sub>rr</sub> | 4      |        |        |        |        |        | µs   |

**Note**

<sup>(1)</sup> Pulse test: 300 µs pulse width, 1 % duty cycle

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                                 |        |        |        |        |        |        |      |      |  |
|---|---------------------------------|--------|--------|--------|--------|--------|--------|------|------|--|
| PARAMETER   | SYMBOL                          | BYG10D | BYG10G | BYG10J | BYG10K | BYG10M | BYG10Y | UNIT |      |  |
| Typical thermal resistance, junction to lead                            | R <sub>θJL</sub>                | 25     |        |        |        |        |        |      | °C/W |  |
| Typical thermal resistance, junction to ambient                         | R <sub>θJA</sub> <sup>(1)</sup> | 150    |        |        |        |        |        |      | °C/W |  |
|   | R <sub>θJA</sub> <sup>(2)</sup> | 125    |        |        |        |        |        |      |      |  |
|   | R <sub>θJA</sub> <sup>(3)</sup> | 100    |        |        |        |        |        |      |      |  |

**Notes**

- <sup>(1)</sup> Mounted on epoxy-glass hard tissue
- <sup>(2)</sup> Mounted on epoxy-glass hard tissue, 50 mm<sup>2</sup> 35 µm Cu
- <sup>(3)</sup> Mounted on Al-oxide-ceramic (Al<sub>2</sub>O<sub>3</sub>), 50 mm<sup>2</sup> 35 µm Cu

| ORDERING INFORMATION (Example) |                 |                        |               |                                    |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| BYG10M-E3/TR                   | 0.064           | TR                     | 1800          | 7" diameter plastic tape and reel  |
| BYG10M-E3/TR3                  | 0.064           | TR3                    | 7500          | 13" diameter plastic tape and reel |
| BYG10MHE3_A/H <sup>(1)</sup>   | 0.064           | H                      | 1800          | 7" diameter plastic tape and reel  |
| BYG10MHE3_A/I <sup>(1)</sup>   | 0.064           | I                      | 7500          | 13" diameter plastic tape and reel |
| BYG10M-M3/TR                   | 0.064           | TR                     | 1800          | 7" diameter plastic tape and reel  |
| BYG10M-M3/TR3                  | 0.064           | TR3                    | 7500          | 13" diameter plastic tape and reel |
| BYG10MHM3_A/H <sup>(1)</sup>   | 0.064           | H                      | 1800          | 7" diameter plastic tape and reel  |
| BYG10MHM3_A/I <sup>(1)</sup>   | 0.064           | I                      | 7500          | 13" diameter plastic tape and reel |

**Note**

<sup>(1)</sup> AEC-Q101 qualified



## RATINGS AND CHARACTERISTICS CURVES ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Forward Current vs. Forward Voltage




Fig. 4 - Max. Reverse Power Dissipation vs. Junction Temperature




Fig. 2 - Max. Average Forward Current vs. Ambient Temperature




Fig. 5 - Diode Capacitance vs. Reverse Voltage




Fig. 3 - Reverse Current vs. Junction Temperature




Fig. 6 - Reverse Recovery Time vs. Forward Current





Fig. 7 - Reverse Recovery Charge vs. Forward Current

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Vishay:

[BYG10D/TR](#) [BYG10D/TR3](#) [BYG10D-E3/TR](#) [BYG10D-E3/TR3](#) [BYG10DHE3/TR](#) [BYG10DHE3/TR3](#) [BYG10G/TR](#)  
[BYG10G/TR3](#) [BYG10G-E3/TR](#) [BYG10G-E3/TR3](#) [BYG10GHE3/TR](#) [BYG10GHE3/TR3](#) [BYG10J/TR](#) [BYG10J/TR3](#)  
[BYG10J-E3/TR](#) [BYG10J-E3/TR3](#) [BYG10JHE3/TR](#) [BYG10JHE3/TR3](#) [BYG10K/TR](#) [BYG10K/TR3](#) [BYG10K-E3/TR](#)  
[BYG10K-E3/TR3](#) [BYG10KHE3/TR](#) [BYG10KHE3/TR3](#) [BYG10M/TR](#) [BYG10M/TR3](#) [BYG10M-E3/TR](#) [BYG10M-E3/TR3](#)  
[BYG10MHE3/TR](#) [BYG10MHE3/TR3](#) [BYG10Y/TR](#) [BYG10Y/TR3](#) [BYG10Y-E3/TR](#) [BYG10Y-E3/TR3](#)  
[BYG10GHE3\\_A/H](#) [BYG10DHE3\\_A/H](#) [BYG10MHE3\\_A/H](#) [BYG10KHM3\\_A/H](#) [BYG10KHE3\\_A/I](#) [BYG10KHE3\\_A/H](#)  
[BYG10JHE3\\_A/H](#) [BYG10MHE3\\_A/I](#) [BYG10GHE3\\_A/I](#) [BYG10KHM3\\_A/I](#) [BYG10DHE3\\_A/I](#) [BYG10JHE3\\_A/I](#)  
[BYG10K-M3/TR](#) [BYG10M-M3/TR3](#) [BYG10DHM3/TR3](#) [BYG10D-M3/TR3](#) [BYG10DHM3/TR](#) [BYG10DHM3\\_A/H](#)  
[BYG10J-M3/TR3](#) [BYG10MHM3/TR](#) [BYG10G-M3/TR](#) [BYG10GHM3\\_A/H](#) [BYG10MHM3\\_A/H](#) [BYG10K-M3/TR3](#)  
[BYG10JHM3/TR](#) [BYG10KHM3/TR3](#) [BYG10MHM3\\_A/I](#) [BYG10JHM3\\_A/H](#) [BYG10MHM3/TR3](#) [BYG10GHM3\\_A/I](#)  
[BYG10Y-M3/TR3](#) [BYG10KHM3/TR](#) [BYG10DHM3\\_A/I](#) [BYG10GHM3/TR3](#) [BYG10Y-M3/TR](#) [BYG10JHM3/TR3](#)  
[BYG10GHM3/TR](#) [BYG10G-M3/TR3](#) [BYG10J-M3/TR](#) [BYG10M-M3/TR](#) [BYG10JHM3\\_A/I](#) [BYG10D-M3/TR](#)  
[BYG10YHM3\\_A/I](#) [BYG10YHE3\\_A/H](#) [BYG10YHM3\\_A/H](#) [BYG10YHE3\\_A/I](#)