## XU2S18PP340L5

security light curtain XU2-S - detection of body - 750..1200 mm - 12..24 V





## Main

IVIAIII	
Commercial Status	Commercialised
Range of product	Preventa Safety detection
Product or component type	Safety thru-beam pair photo-electric sensors
Device short name	XU2S
Output type	1 safety outputs OSSD PNP
[Sn] nominal sensing distance	8 m

Complementary

Detection system	Transmitter-receiver system	
[Us] rated supply voltage	1224 V DC (1030 V) reverse polarity protection	
Current consumption	<= 35 mA no-load	
Voltage drop	<= 1.5 V closed state	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Switching frequency	500 Hz maximum	
Electrical connection	Pre-cabled	
Line of sight type	Along case axis	
Delay response	<= 1 ms	
Delay recovery	<= 1 ms	
Cable outer diameter	5 mm	
Cable length	5 m	
Cable composition	4 x 0.34 mm² for receiver 3 x 0.34 mm² for transmitter	
Function available	Light or dark programmable switching Built-in muting function	
Marking	CE	
Material	Lenses: PMMA (polymethyl methacrylate) Case: nickel plated brass	
Product weight	0.485 kg	

## **Environment**

Standards	EN/IEC 60825-1 EN/IEC 61496-1 EN/IEC 61496-2	
Safety level	Can reach category 2 conforming to EN/ISO 13849-1 (associated with module XPSCM correctly wired) Can reach PL = c conforming to EN/ISO 13849-1 (associated with module XPSCM correctly wired) Type 2 conforming to IEC 61496-1-2	
Ambient air temperature for operation	-2555 °C	
Safety reliability data	PFH = 5.5E-7 1/h conforming to IEC 61508 (with muting function) PFH = 4.6E-7 1/h conforming to IEC 61508	
Ambient air temperature for storage	-4070 °C	
IP degree of protection	IP67 conforming to EN/IEC 60529	

Shock resistance	30 gn (3 axes: 3 times) conforming to EN/IEC 60068-2-27
Vibration resistance	7 gn (f = 1055 Hz) conforming to EN/IEC 60068-2-6

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1005 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

