



**Part Number :** [39000039](#)

**Product Description :** Mini-Fit Female Crimp Terminal, Tin (Sn) over Copper (Cu) Plated Brass, 18-24 AWG, Bag

**Series Number :** 5556

**Status :** Active

**Product Category :** Crimp Terminals

**Engineering Number :** 5556TL

**Packaging Alternative :** 0039000038 (Reel)



---

## Documents & Resources

### Drawings

[Drawing\\_039000039\\_sd.pdf](#)

[Packaging Design Drawing\\_PK-5556-003-001.pdf](#)

[Packaging Design Drawing\\_SPK-5556-001-001.pdf](#)

[Packaging Design Drawing\\_SPK-5556-001-002.pdf](#)

[Packaging Design Drawing\\_SPK-5556-001-003.pdf](#)

### Specifications

[Application Specification\\_55560001-AS-000.pdf](#)

[Product Specification\\_55560002-PS-CH-000.pdf](#)

[Product Specification\\_55560002-PS-ES-000.pdf](#)

[Product Specification\\_55560002-PS-SK-000.pdf](#)

[Product Specification\\_PS-5556-001-001.pdf](#)

[Product Specification\\_PS-5556-002-001.pdf](#)

[Test Summary\\_55560000-TS-000.pdf](#)

[Test Summary\\_55560010-TS-000.pdf](#)


[Test Summary\\_TS-5556-002-001.pdf](#)

[Test Summary\\_TS-5556-005-001.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21

REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Crimp Terminals
Series	5556
Description	Mini-Fit Female Crimp Terminal, Tin (Sn) over Copper (Cu) Plated Brass, 18-24 AWG, Bag
Application	Power, Wire-to-Board, Wire-to-Wire
Product Family	Mini-Fit Family Power Connectors
Product Name	Mini-Fit
UPC	800753585027

### Electrical

Current - Maximum per Contact	9.0A
Voltage - Maximum	600V

### Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Brass
Material - Plating Mating	Tin

Material - Plating Termination	Tin
Net Weight	0.130/g
Packaging Type	Bag
Plating min - Mating	0.889µm
Plating min - Termination	0.889µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.30-3.10mm
Wire Size (AWG)	18, 20, 22, 24
Wire Size mm <sup>2</sup>	N/A

### Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

### Use with Part(s)

Description	Part Number
Mini-Fit Jr. Receptacle Housings	<u>5557</u>
Mini-Fit BMI Dual Row Receptacle Housings	<u>44516</u>
Mini-Fit BMI Dual Row Receptacle Housings	<u>42474</u>
Mini-Fit BMI Dual Row Receptacle Housings	<u>43760</u>
Mini-Fit Jr. Dual Row Receptacle Housings	<u>46992</u>

### Application Tooling

#### Global

Description	Part Number
Extraction Tool for Mini-Fit Jr. Terminals	<u>0011030044</u>
PremiumGrade Hand Crimp Tool for Mini-Fit Jr. Male and Female Terminals, 18-24 AWG	<u>0638190901</u>

#### Application Tooling

#### Japan

Description	Part Number
Handtool (Straight Action)	<u>0570225500</u>
Hand Crimp Tool	<u>0570265000</u>
Hand Crimp Tool	<u>0570275000</u>
Hand Extraction Tool	<u>0570316000</u>

---

This document was generated on Feb 19, 2024