

Product information Field Attachable M12 Connectors with spring-type terminals - RKCQ 4/7

Industrial Connecting Solutions: Circular Connectors:M8 - M12 Connectors:M12 Connectors:M12 Circular connector acc. to IEC 61076-2-101:M12 Field Attachable Connectors:Field Attachable M12 Connectors with spring-type terminals https://e-catalog.hirschmann.com:443/link/57078-24228-256281-256292-256304-58429-58478-75079/en/RKG-04-15/uistate Name Field Attachable M12 Connectors with spring-type terminals Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with spring-type terminals. **Delivery informations** Availability available Product description RKCQ 4/7 Type Order No. 58836 Description Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with spring-type terminals. Number of contacts 4 Color of housing black Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing straight M12 Thread Design of electrical connection spring type terminal connection Coding of the M12 round plug connector А LED display present X Connectable conductor cross-section multiple wire max. 0.5 mm² (without sleeve) Screw joint for cable for external cable diameter 3.0 mm ... 6.5 mm Screwed cable gland, connecting thread SW 15 **Environmental conditions** Environmental temperature -25 °C 90 °C Degree of protection (IP), mounted IP67 Pollution degree 3 Materials Housing material / Molded body PBT Contact bearer material PBT Contact material stainless steel Contact material - Surface refinement silver-plated and gold-plated Knurled screw / nut material CuZn, nickel-plated Sealing material FKM Electrical data Contact resistance ≤ 5 mΩ 4 A at 40°C. UL and notice derating Rated current In Nominal voltage 250 V Rated voltage (Value) 250 V Test voltage 2 kV eff./60 s $> 1 G\Omega$ Insulation resistance





Belden Deutschland GmbH Im Gewerbepark 2 58579 Schalksmühle Germany Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.



