

Note: This datasheet may be out of date.

Please download the latest datasheet of XRCHA16M000F0A01R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=XRCHA16M000F0A01R

XRCHA16M000F0A01R0












Appearance & Shape







The crystal unit for automotive electronics that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high ccuracy unit.

Features

- 1.The series has high reliability and is available for a wide temperature range.
- 2. The crystal unit is small size $(2.5 \times 2.0 \times 0.8 \text{ (mm)})$, and contribute to reduction in mounting area.
- 3.The series complies to RoHS and ELV directives, being lead-free (phase 3).
- 4. The series complies to AEC-Q200.



Automotive Usage	Powertrain/Safety
Other Usage	Automotive



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Plastic Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of XRCHA16M000F0A01R0 from the official website of Murata Manufacturing Co., Ltd.

XRCHA16M000F0A01R0



Product Type	Crystal Unit	
Series	XRCHA	
Туре	HCR2520	
Frequency	16.0000MHz	
Frequency Tolerance	+/-100ppm max. (25+/-3°C)	
Operating Temperature Range	-40°C to 125°C	
Frequency Shift by Temperature	+/-100ppm max.	
Frequency Aging	+/-5ppm max./year	
Equivalent Series Resistance (ESR)	100ohm max.	
Drive Level (DL)	150μW (300μW max.)	
Load Capacitance (Cs)	8pF	
Shape	SMD	
Wash	Not available	
L x W (size)	2.5x2.0mm	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of XRCHA16M000F0A01R0 from the official website of Murata Manufacturing Co., Ltd.

XRCHA16M000F0A01R0





Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

