

Product Search Data Sheet

1.6±0.1

Note: This datasheet may be out of date.

Please download the latest datasheet of XRCMD48M000FXQ58R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XRCMD48M000FXQ58R0

XRCMD48M000FXQ58R0










Appearance & Shape







Features

The crystal unit that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

Features

- 1. The series is available in the applications to be necessary for high accuracy resonator.
- 2. The resonator is extremerly small size (1612), and contribute to reduction in mounting area.
- 3. The series complies to RoHS directive, being lead-free (phase 3).



Applications

Other Usage	Consumer
-------------	----------



Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Plastic Tape	3000

1 of 2

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ XRCMD48M000FXQ58R0\ from\ the\ official\ website\ of\ Muratangle and the statest of\ Muratangle and\ Muratang$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=XRCMD48M000FXQ58R0

XRCMD48M000FXQ58R0



Specifications

Product Type	Crystal Unit	
Series	XRCMD	
Туре	MCR1612	
Frequency	48.0000MHz	
Frequency Tolerance	+/-20ppm max. (Total)	
Operating Temperature Range	-30°C~85°C	
Frequency Aging	+/-1ppm max./year	
Equivalent Series Resistance (ESR)	40ohm max.	
Drive Level (DL)	30μW (100μW max.)	
Load Capacitance (Cs)	7pF	
Shape	SMD	
Wash	Not available (Please be sure to consult with our sales representative or engineer whenever and prior to using the products.)	
L x W (size)	1.6x1.2mm	
Mass	2.9mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

