## **BGA Heat Sink - High Performance** maxiFLOW w/Thermal Tape





ATS Part#: **ATS-52270P-C1-R0** 

Description: 27.00 x 27.00 x 17.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal

Tape

Heat Sink Type: maxiFLOW
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-52270P-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.7 °C/W	3 °C/W	2.6 °C/W	2.3 °C/W	2.1 °C/W	2 °C/W	1.9 °C/W
	Ducted Flow	2.9	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

27.00 mm 27.00 mm 17.50 mm 48.36 mm T412 BLUE-ANODIZED  Notes:  Dimension A and B refer to component size. Dimension C is the heat sink height from the bottom of the base to the top of the fin field. ATS-52270P-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675). Thermal performance data are provided for reference only. Actual performance may vary by application. ATS reserves the right to update or change its products without notice to improve the design or performance. ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant. Contact ATS to learn about custom options available.	Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
<ul> <li>Dimension A and B refer to component size.</li> <li>Dimension C is the heat sink height from the bottom of the base to the top of the fin field.</li> <li>ATS-52270P-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675).</li> <li>Thermal performance data are provided for reference only. Actual performance may vary by application.</li> <li>ATS reserves the right to update or change its products without notice to improve the design or performance.</li> <li>ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.</li> </ul>		27.00 mm	27.00 mm	17.50 mm	48.36 mm	T412	BLUE-ANODIZED
*Image above is for illustration purpose only.	BAA	<ul> <li>Dimensior</li> <li>Dimensior</li> <li>ATS-5227         <ul> <li>(Saint-Gol</li> </ul> </li> <li>Thermal papplication</li> <li>ATS reserperforman</li> <li>ATS certification</li> </ul>	C is the heat sink heat si	eight from the bottor act heat sink assemb e provided for referent ate or change its products k assembly is RoHS	oly with an equivalent nce only. Actual performation ducts without notice	t thermal formance	interface material may vary by

