


SURFACE MOUNT HIGH DENSITY 0.8 AMP SILICON BRIDGE RECTIFIER



This series is UL listed: file number E130224



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CBRHD-01 is a silicon full wave bridge rectifier mounted in a durable epoxy surface mount molded case, utilizing glass passivated chips.

MARKING CODE: CBD1

FEATURES:

- Efficient use of board space: requires only 42mm² of board space vs. 120mm² of board space needed for industry standard 1.0 Amp surface mount bridge rectifier.
- 50% higher density (Amps/mm²) than the industry standard 1.0 Amp surface mount bridge rectifier.
- Glass passivated chips for high reliability.

MAXIMUM RATINGS: (T _A =25°C unless otherwise noted)	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V _{RRM}	100	V
DC Blocking Voltage	VR	100	V
RMS Reverse Voltage	V _{R(RMS)}	70	V
Average Forward Current (T _A =40°C) (Note1)	IO	0.5	А
Average Forward Current (T _A =40°C) (Note 2)	Ι _Ο	0.8	А
Peak Forward Surge Current	IFSM	30	А
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C
Thermal Resistance (Note 3)	Θ_{JA}	85	°C/W

ELECTRICAL CHARACTERISTICS PER DIODE: (TA=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	ТҮР	MAX	UNITS
I _R	V _R = 100V		5.0	μA
I _R	V _R = 100V, T _A =125°C		500	μA
VF	I _F =400mA		1.0	V
СЈ	V _R =4.0V, f=1.0MHz	9.0		pF

Notes: (1) Mounted on Glass-Epoxy PCB.

(2) Mounted on Ceramic PCB.

(3) Mounted on PCB with 0.5" x 0.5" copper pads.


R2 (4-January 2010)






SURFACE MOUNT HIGH DENSITY 0.8 AMP SILICON BRIDGE RECTIFIER

HD DIP CASE - MECHANICAL OUTLINE





•

H

+

~

DIMENSIONS INCHES MILLIMETERS MIN SYMBOL MAX MIN MAX 0.006 0.014 0.15 0.35 А В 0.275 7.00 --С 0.70 1.10 0.027 0.043 D 0.035 0.90 1.30 0.051 Е 0.090 0.106 2.30 2.70 F 0.019 0.031 0.50 0.80 G 0.150 0.165 3.80 4.20 Н 0.051 0.067 1.30 1.70 J 0.177 0.193 4.50 4.90 Κ 0.090 0.106 2.30 2.70 L 0.000 0.008 0.00 0.20

HD DIP (REV: R2)

MARKING CODE: CBD1

R2 (4-January 2010)

R2

www.centralsemi.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: CBRHD-01 TR13 PBFREE