

Reducing bridge - RB UT 6-(2,5/4) - 3047251

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Reducing bridge, Number of positions: 2, Color: red



Key commercial data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 046356 055949
Weight per Piece (excluding packing)	2.62 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Technical data

Color	red
Material	PA 6.6
Number of positions	2
Inflammability class according to UL 94	V0
Maximum temperature	125 °C

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140

Reducing bridge - RB UT 6-(2,5/4) - 3047251

Classifications

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426