

Specification Sheet


Part Number: 111-01306

316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.

Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool.

Fully enclosed head prevents dirt or grit from interfering with locking mechanism.

High tensile strength for maximum strength and safety on heavy duty applications.



Stainless Steel Tie, 49" Long, 922lb Tensile Strength, SS316, Metal, 25/pkg

Article Number 111-01306

Type MBT49UH

Color Metal (ML)

Quantity Per bag

Product	Descri	ntion
Oaaot	D CCC:	Puvi

HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes, and more. Stainless steel ties can be used in virtually any indoor, outdoor, or underground application. Grade 316 material is highly resistant to corrosion and widely used in marine environments where chemicals, salts, acids, and temperature extremes may affect the bundling application. MBT stainless steel ties in 316 stainless steel material are also available with a polyester protective coating. This coating creates a barrier and protectant from chemical reactions of dissimilar metals.

Short Description

Stainless Steel Tie, 49" Long, 922lb Tensile Strength, SS316, Metal, 25/pkg

Global Part Name

MBT49UH-SS316-SR

Minimum Tensile Strength (Imperial)

922.0

Minimum Tensile Strength (Metric)

4100.0

Length L (Imperial)

49.0

Length L (Metric)

1245.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

ball bearing lock

Variant

No Serration

Width W (Imperial)

0.63

Width W (Metric) 16.0 **Bundle Diameter Min (Imperial)** 0.47 **Bundle Diameter Min (Metric)** 12.0 **Bundle Diameter Max (Imperial)** 15.0 **Bundle Diameter Max (Metric)** 380.0 **Thickness T (Metric)** 0.27 **Material** Stainless Steel (SS316) **Material Shortcut** SS316 **Flammability** Non-burning **Halogen Free** Yes **Operating Temperature** -112°F to +1000°F (-80°C to +538°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes

Package Quantity (Metric)	25			
Customs Number	732	6908695		
© 2021 HellermannTyton. All Rights R	eserved			
	ntact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions