

Note: This datasheet may be out of date

Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing

http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F60RB

NCU18XH103F60RB












Appearance & Shape









- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).



Limited Usage	Consumer Grade
Other Usage	Temperature compensation for transistor, IC and crystal oscillator in mobile communications Temperature sensor for rechargeable batteries Temperature compensation of LCD Temperature compensation in general use of electric circuits



Packaging Information

Packaging	Specifications	Minimum Order Quantity
RB	180mm Paper Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/


Last updated : 2017/09/26

Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing} \\$

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F60RB

NCU18XH103F60RB



Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Permissive Operating Current (25°C)	0.31mA
Rated Electric Power (25°C)	100.0mW
Typical Dissipation Constant (25°C)	1mW/℃
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	1.6x0.8mm
Size Code (in inch)	0.6x0.3inch
Shape	SMD
Mass	0.0047g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/


Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing} \\$

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F60RB

NCU18XH103F60RB





Resistance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

