

Product Search Data Sheet

Note: This datasheet may be out of date Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB

NCU18XH103F6SRB

In Production Recommended RoHS REAC

Appearance & Shape





Applications

Automotive Usage	Powertrain/Safety	
Limited Usage	Automotive Grade	
Other Usage	 Variousengine control units ABS control unit High power devices (IGBT) Temperature compensation for various circuits required nigh temperature. 	



Packaging	Specifications	Minimum Order Quantity
RB	180mm Paper Tape	4000



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB

NCU18XH103F6SRB

Specifications

Resistance (25°C)	10κΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Permissive Operating Current (25°C)	0.31mA
Rated Electric Power (25°C)	100.0mW
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 150°C
Size Code (in mm)	1.6x0.8mm
Size Code (in inch)	0.6x0.3inch
Shape	SMD
Mass	0.0047g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




NCU18XH103F6SRB

Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB





Resistance-Temperature Characteristics

Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3