



■ Features :

- 2"×1" compact size
- 2:1 wide input range
- High efficiency up to 92%
- 1500VDC I/O isolation
- Built-in remote ON/OFF control
- Built-in trimming output
- Comply with CE / FCC without external components
- Protections: Short circuit / Overload / Input and Output Over voltage
- Cooling by free air convection
- Six-sided shield metal case
- 100% burn-in test
- Low cost / High reliability
- Approvals: FCC / EAC / CE / UKCA
- 2 years warranty

■ GTIN CODE


MW Search: <https://www.meanwell.com/serviceGTIN.aspx>



SPECIFICATION

ORDER NO.	SKM50B-05	SKM50C-05	SKM50B-12	SKM50C-12	SKM50B-15	SKM50C-15	
OUTPUT	DC VOLTAGE	5V		12V		15V	
	CURRENT RANGE	1 ~ 10A		0.41 ~ 4.17A		0.33 ~ 3.33A	
	RATED POWER	50W					
	RIPPLE & NOISE (max.) Note.2	60mVp-p		80mVp-p		100mVp-p	
	LINE REGULATION Note.3	±0.2%					
	LOAD REGULATION Note.4	±0.5%					
	VOLTAGE ACCURACY	±2.0%					
	SWITCHING FREQUENCY	300KHz typ.					
	EXTERNAL CAPACITANCE LOAD (max.)	1000uF					
INPUT	EXTERNAL TRIM Adj. RANGE(Typ.)		±10%		-20 ~ +10%		
	VOLTAGE RANGE		B: 18 ~ 36VDC C: 36 ~ 75VDC				
	UNDER VOLTAGE SHUTDOWN		B: 16VDC C: 32VDC				
	EFFICIENCY (Typ.)		91%	91%	92%	91%	90%
	DC CURRENT	Full load	2300mA	1160mA	2300mA	1160mA	2300mA
		No load	110mA	60mA	110mA	60mA	110mA
	FILTER		Pi network				
REMOTE CONTROL		Power ON : R.C ~ -Vin > 2.5VDC or open circuit ; Power OFF : R.C ~ -Vin < 0.5VDC or short					
PROTECTION		Fuse recommended					
PROTECTION (Note. 5)	OVER CURRENT		110% ~ 180% rated output power				
	SHORT CIRCUIT		Protection type : Hiccup mode, recovers automatically after fault condition is removed				
	OVER VOLTAGE		Input(Typ.): B: >40 ~ 50VDC C: >80 ~ 100VDC input voltage Protection type : Shut down o/p voltage, recovers automatically after fault condition is removed Output(Typ.): 5Vo : 7V ~ 8.95V ; 12Vo : 15V ~ 19.2V ; 15Vo : 18V ~ 23.3V Protection type : Clamp by TVS diode				
ENVIRONMENT	WORKING TEMP.		-40 ~ +75°C (Refer to "Derating Curve")				
	CASE TEMP.		+115°C max.				
	WORKING HUMIDITY		20% ~ 90% RH non-condensing				
	STORAGE TEMP., HUMIDITY		-55 ~ +125°C, 10 ~ 95% RH				
	TEMP. COEFFICIENT		±0.03% / °C (0 ~ 55°C)				
VIBRATION		10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes					
SAFETY & EMC	SAFETY STANDARDS		EAC TP TC 020/2011 (EAC TP TC 004 for 48Vin type only) approved				
	WITHSTAND VOLTAGE		I/P-O/P: 1.5KVDC				
	ISOLATION RESISTANCE		I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH				
	EMC EMISSION Note.5		Compliance to BS EN/EN55032 Class A, FCC part 15 Class A without external components, EAC TP TC 020				
EMC IMMUNITY		Compliance to BS EN/EN61000-4-2,3,4,5,6,8, light industry level, criteria A, EAC TP TC 020					
OTHERS	MTBF		700Khrs min. MIL-HDBK-217F(25°C)				
	DIMENSION		50.8*25.4*13.7 mm or 2**1**0.54" inch (L*W*H)				
	WEIGHT		43g				

■ Mechanical Specification




Note : Pin tolerance ±0.1mm ; other tolerance ±0.8mm


■ Pin Configuration

Pin No.	Output	Pin No.	Output
1	+Vin	4	+Vout
2	-Vin	5	-Vout
3	R.C	6	Trim

■ External Output Trimming



■ Derating Curve



NOTE

1. All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
 2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
 3. Line regulation is measured from low line to high line at rated load.
 4. Load regulation is measured from 10% to 100% rated load.
 5. Consult MEAN WELL for deployment of Class B.
 6. Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.
- ※ Product Liability Disclaimer : For detailed information, please refer to <https://www.meanwell.com/serviceDisclaimer.aspx>