

# Charging cable Mode3 Typ2 32A 1ph 5m



Part number	08 91 409 0107 A0
Specification	Charging cable Mode3 Typ2 32A 1ph 5m
HARTING eCatalogue	https://b2b.harting.com/08914090107A0

Image is for illustration purposes only. Please refer to product description.

#### Identification

Element	Charging cable
Specification	Straight
Charging mode	Mode 3
Connector 1	Type 2 Female (Vehicle side)
Connector 2	Type 2 Male (infrastructure side)

## Version

Cable length	5 m
Termination method	Crimp termination
Core structure	3x 6 mm² + 0.5 mm²
Number of phases	1
Number of contacts	5
Number of signal contacts	2
Number of power contacts	3
Contact configuration	Signal: CP, PP Power: L1, N, PE
Details	Also available with customer specific logo on request.

### Technical characteristics

Rated current (signal)	2 A
Rated voltage (signal)	30 V
Rated current (power)	32 A



#### Technical characteristics

Rated voltage (power)	250 V
Type of current	AC
Charging power	7.4 kW
Coding resistance	220 Ω between PE and PP
Ambient temperature	-30 +50 °C in operation -40 +80 °C storage/transport
Air pressure	≥540 hPa ≈ 5000 m
Insertion force	<100 N
Withdrawal force	<100 N
Mating cycles	≥10,000
Degree of protection acc. to IEC 60529	IP44 mated condition
Cable diameter	12.8 mm ± 0.4 mm
Minimum bending radius	9x Cable diameter (repeated bending)
Conductor resistance @ 20 °C	≤3.3 $\Omega$ /km @ 6 mm <sup>2</sup> ≤39 $\Omega$ /km @ 0.5 mm <sup>2</sup>

## Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material (cover)	Thermoplastic polyurethane (TPU)
Material (cable)	Thermoplastic polyurethane (TPU)
Colour (cable)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
Material (cover)  Material (cable)  Colour (cable)  Material flammability class acc. to UL 94  RoHS  RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances	Thermoplastic polyurethane (TPU)  Thermoplastic polyurethane (TPU)  Black  V-0  compliant with exemption  6(c): Copper alloy containing up to 4 % lead by weight  compliant with exemption  50  No  No



## Material properties

REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Specifications and approvals

Specifications	IEC 62196-2 IEC 62893
CE	Yes

#### Commercial data

Packaging size	1
Net weight	2.164 kg
Country of origin	Romania
European customs tariff number	85444991
eCl@ss	27144705 Charging cable E-Mobility