

# MCR-SGA-4/6-DC - Strain gage/load cell amplifier



5604058

<https://www.phoenixcontact.com/us/products/5604058>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Signal conditioner for strain gage/load cell



## Product Description

Universal strain gage/load cell amplifier. 1.25 to 12-volt adjustable excitation, 0-5 V, 0-10 V and 4-20 mA output

## Commercial Data

Item number	5604058
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	C401
Product Key	CK1833
GTIN	4046356683685
Weight per Piece (including packing)	159.1 g
Weight per Piece (excluding packing)	159 g
Customs tariff number	85437090
Country of origin	US

# MCR-SGA-4/6-DC - Strain gage/load cell amplifier



5604058

<https://www.phoenixcontact.com/us/products/5604058>

## Technical Data

### Notes

#### Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

### Product properties

Product type	Signal conditioner
--------------	--------------------

### Electrical properties

#### Supply

Supply voltage range	11 V DC ... 30 V DC
Typical current consumption	100 mA
Max. current consumption	250 mA (350 W, full bridge at 10 V Excitation)

### Input data

#### Signal

Description of the input	Excitation voltage
Voltage input signal	1.25 V ... 12 V
Max. current input signal	100 mA
Protective circuit	Short-circuit and thermal protection
Input impedance	10 GΩ
Bridge resistance	120 Ω ... 20000 Ω
Gain range	1 V ... 2000 V (10 steps)
Input range of the sensor	0.1 mV ... 200 mV

### Output data

#### Signal

Voltage output signal	0 V ... 5 V
	0 V ... 10 V
	0 V ... 10 V
	-5 V ... 5 V
Current output signal	4 mA ... 20 mA

### Connection data

Connection method	COMBICON plug-in screw terminal block
Conductor cross section solid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

# MCR-SGA-4/6-DC - Strain gage/load cell amplifier



5604058

<https://www.phoenixcontact.com/us/products/5604058>

Width	22.5 mm
Height	99 mm
Depth	111 mm

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	3300 m (Above sea level)
Permissible humidity (operation)	10 % ... 90 %

# MCR-SGA-4/6-DC - Strain gage/load cell amplifier



5604058

<https://www.phoenixcontact.com/us/products/5604058>

## Classifications

### ECLASS

ECLASS-10.0.1	27210120
ECLASS-11.0	27210120
ECLASS-12.0	27210120
ECLASS-12.0	27210120

### ETIM

ETIM 7.0	EC001024
----------	----------

### UNSPSC

UNSPSC 21.0	39121708
-------------	----------

# MCR-SGA-4/6-DC - Strain gage/load cell amplifier



5604058

<https://www.phoenixcontact.com/us/products/5604058>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)