

18900 Panduit Drive Tinley Park, IL 60487

Customer Service: 800-777-3300

TDS: Effective Date: Revision: GMC 16JUL12 4

Technical Data Sheet

Vinyl Coated Cloth Tape – GMC

This specification is intended to outline the physical and chemical properties of *PANDUIT*'s pressure sensitive vinyl coated cloth material and include the following part numbers and printable material identifiers:

Part Number Prefixes				
PDL*	PCL*	PESC-*-*		
PCMH-*	PARW125-*			
PCM-*	PCWL-*			

Printable Material Suffixes				
CBD				

PRODUCT SPECIFICATIONS:

Description: Material is RoHS compliant (European Union directive 2002/95/EC).

Material is a coated vinyl cloth with a rubber –based pressure sensitive adhesive. This material is used in flat applications and in a wrap format

for wire/cable marking.

Print Methods: This material is preprinted and also recommended for dot matrix printing.

Adhesive: Repositionable rubber based, pressure sensitive adhesive

Standard Colors: White, yellow

Thickness: 8.0 +/- 0.7 mils (substrate and adhesive)

Service Temperature Range: 50°F to 170°F (10°C to 77°C)

Minimum Application Temperature: $60^{\circ}F (16^{\circ}C)$

Storage Conditions: Store at 70°F (21°C) and 50% Relative Humidity.

PROPERTIES: PERFORMANCE:

Peel Adhesion to Stainless Steel: 28 oz/in width (PSTC-101, 15 min. dwell)
Shear Adhesion: 3 hours (PSTC-107, modified procedure A)
Tensile Strength: MD 45 +/- 4.5 lbs./inch width (PSTC-131)
UV Resistance: *3000 hours no change observed (ASTM G154)

Elevated Temperature Exposure: After 8 hours at 150°F (65.5°C) there was no deterioration of the substrate

*3000 hours equates to 5 years of assimilated outdoor UV exposure.

Page 1 of 2 © 2007 PANDUIT Corp

TDS: GMC



18900 Panduit Drive Tinley Park, IL 60487

Customer Service: 800-777-3300

TDS: Effective Date: Revision: GMC 16JUL12

Technical Data Sheet

CHEMICAL/SOLVENT RESISTANCE:

Samples were preprinted and dot matrix printed with Panduit PDLR ribbon. These samples were laminated to flat steel panels and wrapped around a 1/12" OD wire in self-laminating format. Test was conducted at room temperature after 24 hour dwell. The samples were immersed in the specified chemical reagents for 5 immersions using the following cycle: a 10 minute immersion time followed by a 30 minute recovery time. After the final immersion the flat samples were rubbed 10 times with a lint free gauze.

	Visual Observation			
Chemical Reagent	Substrate / Adhesive	Pre-Printed Printed Legend	Dot Matrix Printed Legend	
Distilled Water	No effect	No effect	No effect	
Mineral Spirits	Slight adhesive bleed	No effect	No effect	
Toluene	Slight adhesive bleed, top coating removed	Print not legible	Print not legible	
Isopropyl Alcohol	No effect	No effect	No effect	
Methanol	No effect	No effect	No effect	
Acetone	Slight adhesive bleed	No effect	Loss of print density	
Methyl Ethyl Ketone	Slight adhesive bleed, top coating removed	Print not legible	Print not legible	
1,1,1 Trichloroethane	Slight adhesive bleed, top coating removed	Print not legible	Print not legible	
Freon TF	No effect	No effect	No effect	
Super Agitene	No effect	No effect	No effect	
Jet-A Fuel	No effect	No effect	No effect	
Arco TruSlide 68	No effect	No effect	No effect	
SAE 30 Motor Oil	No effect	No effect	No effect	

APPROVALS

UL Recognized: UL 969 File Number: MH 14576, MH 14979

CUL Recognized: C22.2 No. 0.15-01 File Number: MH 14979

LIMITED WARRANTY

All *PANDUIT* Identification Solution Products (except for Software programs) are warranted to be free from defects in material and workmanship at the time of sale but our obligation under this warranty is limited to replacement of the product proved to be defective within 6 months from the date of sale, or in the case of printers, within 90 days from the date of sale. This warranty is void if the products or printers are modified, altered or misused in any way. Use of *PANDUIT* printers with any product other than the specified *PANDUIT* products for which the printer was designed constitutes misuse. Before using, the user shall determine the suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

NEITHER PANDUIT NOR SELLER SHALL BE LIABLE FOR ANY OTHER INJURY, LOSS OR DAMAGE, WHETHER DIRECT OR CONSEQUENTIAL, ARISING OUT OF THE USE OF, OR THE INABILITY TO USE THE PRODUCT OR THE PRINTER.

THIS WARRANTY IS MADE IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS OF PARTICULAR USE ARE SPECIFICALLY EXCLUDED.

The information contained in this literature is based on our experience to date and is believed to be reliable. It is intended as a guide or use by persons having technical skill at their own discretion and risk. We do not guarantee favorable results or assume any liability in

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

PCM-32 PCM-66 PCM-28 PCM-12 PCM-29 PCM-22 PCM-AZ PCM-7 PCM-4 PCM-31 PCM-33 PCMH-23 PCM-100-124 PCM-99 PCM-49 PCM-25 PCM-110 PCM-1-18 PCM-A PCM-L2 PCM-U PCM-YEL PCM-0-9 PCM-150-174 PCM-180 PCM-20 PCM-23 PCM-39 PCM-40 PCM-400-424 PCM-425-449 PCM-50 PCM-70 PCM-84 PCM-87 PCM-TAN PCM-N PCM-A2 PCM-A1 PCM-D PCM-24 PCM-38 PCM-47 PCM-S PCM-T PCM-2L1 PCM-43 PCM-375-399 PCM-19-36 PCM-PUR PCM-BLK PCM-BRN PCM-56 PCM-97 PCM-76 PCM-173 PCMH-20 PCM-1T3 PCM-41 PCM-A4 PCM-F1 PCM-3T2 PCM-X4 PCM-73 PCM-T1 PCM-150 PCM-135 PCM-E2 PCM-3L2 PCM-113 PCM-4L3 PCM-68 PCMH-15 PCMH-3 PCM-2L3 PCM-162 PCM-182 PCM-86 PCMH-21 PCM-145 PCM-185 PCM-166 PCM-F4 PCM-163 PCM-R1 PCM-197 PCM-51 PCM-C2 PCM-111 PCM-P PCM-160 PCM-GND PCM-NEG PCM-R2 PCM-144 PCM-275-299 PCM-46 PCM-175 PCM-117 PCM-T2