

# compact cylinder ADNGF-20-60-P-A

Part number: 554228

FESTO

According to ISO 21287, with plain-bearing guide, piston rod secured against rotation by means of guide rods and yoke plate.



## Data sheet

| Feature                                    | Value   |
|--|---|
| Stroke                                     | 60 mm   |
| Piston diameter                            | 20 mm   |
| Based on the standard                      | ISO 21287   |
| Cushioning                                 | P: Flexible cushioning rings/plates at both ends                            |
| Assembly position                          | Any   |
| Design structure                           | Piston<br>Piston rod<br>Profile barrel                                      |
| Position detection                         | For proximity sensor  |
| Protection against torque/guide            | Guide rod with yoke   |
| Operating pressure                         | 1.5 ... 10 bar  |
| Mode of operation                          | double-acting   |
| Operating medium                           | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium         | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC    | 2 - Moderate corrosion stress   |
| Ambient temperature                        | -20 ... 80 °C   |
| Impact energy in end positions             | 0.2 J   |
| Theoretical force at 6 bar, return stroke  | 141 N   |
| Theoretical force at 6 bar, advance stroke | 188 N   |
| Moving mass with 0 mm stroke               | 60 g  |
| Additional weight per 10 mm stroke         | 26 g  |
| Basic weight for 0 mm stroke               | 161 g   |
| Additional mass factor per 10 mm of stroke | 11 g  |
| Pneumatic connection                       | M5  |
| Materials note                             | Conforms to RoHS  |
| Material cover                             | Aluminium<br>Anodised   |
| Material seals                             | TPE-U(PUR)  |
| Material piston rod                        | High alloy steel  |
| Material cylinder barrel                   | Wrought Aluminium alloy<br>Smooth anodised                                  |