

R6

## Features

- Peak pulse power:
  - 5000 W (10/1000  $\mu$ s)
- Stand off voltage range from 10 V to 180 V
- Unidirectional and bidirectional diode
- Low clamping factor
- Fast response time
- UL497B, file number: QVGQ2.E136224

## Description

Transil diodes provide high overvoltage protection by clamping action. Their instantaneous response to transient overvoltages makes them particularly suited to protect voltage sensitive devices such as MOS Technology and low voltage supplied ICs.

Product status link

[BZW50](#)

# 1 Characteristics

**Table 1. Absolute maximum ratings ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ )**


Symbol	Parameter	Value	Unit
$P_{PP}$	Peak pulse power dissipation <sup>(1)</sup>	5000	W
$P$	Power dissipation on infinite heatsink	6.5	W
$I_{FSM}$	Non repetitive surge peak forward current for unidirectional types	500	A
$T_{stg}$	Storage temperature range	-65 to +175	$^{\circ}\text{C}$
$T_{op}$	Maximum operating junction temperature	175	$^{\circ}\text{C}$
$T_L$	Maximum lead temperature for soldering during 10 s at 5 mm from case.	260	$^{\circ}\text{C}$

1. For a surge greater than the maximum values, the diode will fail in short-circuit.


**Table 2. Thermal resistance parameter**

Symbol	Parameter	Value	Unit
$R_{th(j-l)}$	Junction to leads	15	$^{\circ}\text{C}/\text{W}$
$R_{th(j-a)}$	Junction to ambient on printed circuit. $L_{lead} = 10\text{ mm}$	65	$^{\circ}\text{C}/\text{W}$

**Figure 1. Electrical characteristics (definitions)**



**Figure 2. Pulse definition for electrical characteristics**




**Table 3. Electrical characteristics - values ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ )**

Order code		$I_{RM} @ V_{RM}$ max.		$V_{BR} @ I_R^{(1)}$ min.		$V_{CL} @ I_{PP}$ 10/1000 $\mu\text{s}$ max.		$V_{CL} @ I_{PP}$ 8/20 $\mu\text{s}$ max.		$\alpha T^{(2)}$	$C^{(3)}$ typ.
Unidirectional	Bidirectional	$\mu\text{A}$	V	V	mA	V	A	V	A	$10^{-4}/^{\circ}\text{C}$	pF
BZW50-10	BZW50-10B	5	10	11.1	1	18.8	266	23.4	2564	7.8	24000
BZW50-12	BZW50-12B	5	12	13.3	1	22	227	28	2143	8.4	18500
BZW50-15	BZW50-15B	5	15	16.6	1	26.9	186	35	1714	8.8	13500
BZW50-18	BZW50-18B	5	18	20	1	32.2	155	41.5	1446	9.2	11500
BZW50-22	BZW50-22B	5	22	24.4	1	39.4	127	51	1177	9.6	8500
BZW50-27	BZW50-27B	5	27	30	1	48.3	103	62	968	9.8	7000
BZW50-33	BZW50-33B	5	33	36.6	1	59	85	76	789	10	5750
BZW50-39	BZW50-39B	5	39	43.3	1	69.4	72	90	667	10.1	4800
BZW50-47	BZW50-47B	5	47	52	1	83.2	60.1	108	556	10.3	4100
BZW50-56	BZW50-56B	5	56	62.2	1	99.6	50	129	465	10.4	3400
BZW50-68	BZW50-68B	5	68	75.6	1	121	41	157	382	10.5	3000
BZW50-82	BZW50-82B	5	82	91	1	145	34	189	317	10.6	2600
BZW50-100	BZW50-100B	5	100	111	1	179	28	228	263	10.7	2300
BZW50-120	BZW50-120B	5	120	133	1	215	23	274	219	10.8	1900
BZW50-150	BZW50-150B	5	150	166	1	269	19	343	175	10.8	1700
BZW50-180	BZW50-180B	5	180	200	1	322	16	410	146	10.8	1500


1. Pulse test:  $t_p < 50\text{ ms}$ .
2. To calculate  $V_{BR}$  versus  $T_j$ :  $V_{BR}$  at  $T_j = V_{BR}$  at  $25\text{ }^{\circ}\text{C} \times (1 + \alpha T \times (T_j - 25))$
3.  $V_R = 0\text{ V}$ ,  $F = 1\text{ MHz}$ . For bidirectional types, capacitance value is divided by 2.

## 1.1 Characteristics (curves)


**Figure 3. Peak power dissipation vs. initial junction temperature (printed circuit board)**




**Figure 4. Peak pulse power versus exponential pulse duration**





**Figure 5. Clamping voltage vs. peak pulse current**





**Figure 6. Capacitance vs. reverse applied voltage for unidirectional types (typical values)**



**Note:** The curves in [Figure 5. Clamping voltage vs. peak pulse current](#) are specified for a junction temperature of 25 °C before surge. The given results may be extrapolated for other junction temperatures by using the following formula:  $\Delta V_{BR} = \alpha T \times [T_{amb} - 25] \times V_{BR}(25^{\circ}\text{C})$ . For intermediate voltages, extrapolate the given results.

**Figure 7. Capacitance vs. reverse applied voltage for bidirectional types (typical values)**

**Figure 8. Peak forward voltage drop vs. peak forward current for unidirectional types (typical value)**


Note: For Figure 8. Peak forward voltage drop vs. peak forward current for unidirectional types (typical value), multiply by 2 for units with  $V_{BR} > 220$  V.

**Figure 9. Transient thermal impedance junction to ambient vs. pulse duration**

**Figure 10. Relative variation of leakage current vs. junction temperature**


## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 2.1 R6 package information

Figure 11. R6 package outline




Table 4. R6 package mechanical data


Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.		Typ.	Max.
A	8.6	-	9.1	0.338	-	0.358
B	25.4	-		1	-	
C	8.6	-	9.1	0.338	-	0.358
D	1.20	-	1.30	0.047	-	0.051

**Table 5. Marking**

Unidirectional order code	Marking	Bidirectional order code	Marking
BZW50-10	BZW50-10	BZW50-10B	BZW50-10B
BZW50-12	BZW50-12	BZW50-12B	BZW50-12B
BZW50-15	BZW50-15	BZW50-15B	BZW50-15B
BZW50-18	BZW50-18	BZW50-18B	BZW50-18B
BZW50-22	BZW50-22	BZW50-22B	BZW50-22B
BZW50-27	BZW50-27	BZW50-27B	BZW50-27B
BZW50-33	BZW50-33	BZW50-33B	BZW50-33B
BZW50-39	BZW50-39	BZW50-39B	BZW50-39B
BZW50-47	BZW50-47	BZW50-47B	BZW50-47B
BZW50-56	BZW50-56	BZW50-56B	BZW50-56B
BZW50-68	BZW50-68	BZW50-68B	BZW50-68B
BZW50-82	BZW50-82	BZW50-82B	BZW50-82B
BZW50-100	BZW50-100	BZW50-100B	BZW50-100B
BZW50-120	BZW50-120	BZW50-120B	BZW50-120B
BZW50-150	BZW50-150	BZW50-150B	BZW50-150B
BZW50-180	BZW50-180	BZW50-180B	BZW50-180B

### 3 Ordering information

**Figure 12. Ordering information scheme**



**Table 6. Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
BZW50xxxx	See <a href="#">Table 5. Marking</a>	R6	2.050 g	1000	Ammopack
BZW50xxxxB				100	Tape and reel
BZW50xxxxRL					
BZW50xxxxBRL					

1. Logo, date code, type code, cathode band (for unidirectional types only).



## Revision history

**Table 7. Document revision history**

Date	Revision	Changes
Feb-2003	1	Last update.
14-Dec-2012	2	Updated ECOPACK statement.
25-May-2018	3	Updated title description. Updated <a href="#">Figure 2. Pulse definition for electrical characteristics</a> and <a href="#">Figure 12. Ordering information scheme</a> .

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## STMicroelectronics:

[BZW50-150](#) [BZW50-15B](#) [BZW50-12B](#) [BZW50-68B](#) [BZW50-33B](#) [BZW50-120B](#) [BZW50-39B](#) [BZW50-39](#) [BZW50-22](#) [BZW50-27](#) [BZW50-33](#) [BZW50-68](#) [BZW50-82](#) [BZW50-56](#) [BZW50-15](#) [BZW50-18](#) [BZW50-10](#) [BZW50-180](#) [BZW50-56B](#) [BZW50-180B](#) [BZW50-47B](#) [BZW50-150B](#) [BZW50-27B](#) [BZW50-82RL](#) [BZW50-39BRL](#) [BZW50-33BRL](#) [BZW50-180RL](#) [BZW50-100B](#) [BZW50-82B](#) [BZW50-22B](#) [BZW50-33RL](#) [BZW50-15RL](#) [BZW50-27RL](#)