

## This document was generated on 12/14/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>2182160410</u>			
Status:	Active			
Overview:	Micro-Fit+ Connector System			and the second sec
Description:		er, Surface Mount, 3.00mm Pitch, Dual Row, 4 Circuits,		
Description		Capable, Press Clip, Black, Tape and Reel		1
Documents:				
Drawing (PDF)		Test Summary 2064600000-TS-000 (PDF)		
	2064600000-PS-000 (PDF)	Datasheet (PDF)		
	ion 2064600001-AS-000 (PDF)	RoHS Certificate of Compliance (PDF)		-
	on 2182160001-PK-000 (PDF)		Series imag	e - Reference only
			_	
General			EU ELV	
Product Family		PCB Headers	Not Relevant	
Series		218216		
Application		Power, Wire-to-Board	EU RoHS	<u>China RoHS</u>
Overview		Micro-Fit+ Connector System	Compliant	
Product Name		Micro-Fit+	REACH SVHC	
Taxonomy		PCB Headers and Receptacles	Not Contained Per	
UPC		195842878532	D(2022)4187-DC (1	0
			June 2022)	
Physical			Halogen-Free	
Breakaway		No	<u>Status</u>	
Circuits (Loaded)		4	Low-Halogen	
Circuits (maximum)		4	For more informatio	n, please visit <u>Contact US</u>
Color - Resin		Black		-
Durability (mating cycles max)		25	China ROHS	Green Image
First Mate / Last Brea	k	No	ELV	Not Relevant
Glow-Wire Capable		Yes	RoHS Phthalates	Not Contained
Keying to Mating Part		Yes		
Lock to Mating Part		Yes		
Material - Metal		High Copper Alloy	Search Parts in t	his Series
Material - Plating Mating		Matte Tin	218216 Series	
Material - Plating Terr	nination	Matte Tin		
Material - Resin		Liquid Crystal Polymer		
Net Weight		0.861/g	Mates With	
Number of Rows		2	Micro-Fit+ Recept	lacie <u>20646 i</u>
Orientation		Right Angle		
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Pitch - Mating Interface		3.00mm		
Pitch - Termination Interface		3.00mm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Shrouded		Yes		
Temperature Range -	Operating	-40° to +105°C		
Termination Interface	Style	Surface Mount		
Electrical				
Current - Maximum pe	er Contact	12.5A		
Voltage - Maximum	Si Contact	600V AC (RMS)/DC		
Material Info				
	Normalia and			
Reference - Drawing		2064600001 45 000		
Application Specificat		2064600001-AS-000		
Packaging Specification	UII	2182160001-PK-000 2064600000-PS-000		

2064600000-PS-000

Product Specification

## This document was generated on 12/14/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION