Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15WF104F03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104F03RC

NCP15WF104F03RC












Appearance & Shape







Applications

Limited Usage	Consumer Grade
Other Usage	Temperature compensation for transistor, IC and crystal oscillator in mobile communications 2. Temperature sensor for rechargeable batteries 3. Temperature compensation of LCD 4. Temperature compensation in general
	use of electric circuits



Packaging Information

Packaging	Specifications	Standard Packing Quantity
RC	180mm Paper Tape	10000



Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Same B-constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. NCP series are recognized by UL/cUL (UL1434, File No.E137188).

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15WF104F03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104F03RC

NCP15WF104F03RC



Specifications

Resistance (25°C)	100kΩ			
Resistance Value Tolerance	±1%			
(at 25°C)				
B-Constant (25/50°C)	4250K			
B-Constant (25/50°C)	±1%			
Tolerance	1170			
B-Constant(25/80°C)	4303K			
(Reference Value)	450010			
B-Constant(25/85°C)	4311K			
(Reference Value)				
B-Constant(25/100°C)	4334K			
(Reference Value)	100 111			
Max. Voltage	5V			
Maximum Operating Current	0.032mA			
(25°C)	0.032IIIA			
Typical Dissipation Constant	1mW/°C			
(25°C)	Tillivy, C			
Operating Temperature	-40°C to 125°C			
Range				
Size Code (in mm)	1.0x0.5mm			
Size Code (in inch)	0.4x0.2inch			
Shape	SMD			
Mass	0.0012g			

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of NCP15WF104F03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104F03RC

NCP15WF104F03RC







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

