

This document was generated on 02/16/2020

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0353620850

Status: Active

Overview: Sherlock Wire-to-Board Connector System

**Description:** 2.00mm Pitch Sherlock Wire-to-Board Header, Vertical, with Positive Lock, 8 Circuits,

with Kinked PC Tails, Natural

**Documents:** 

3D ModelProduct Specification PS-35507-003-001 (PDF)3D Model (PDF)Packaging Specification PK-35362-001-001 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>35362</u>

Application Signal, Wire-to-Board

Overview Sherlock Wire-to-Board Connector System

Product Name Sherlock UPC 822348259755

**.** . .


**Physical** Breakaway No Circuits (Loaded) 8 Circuits (maximum) 8 Color - Resin Natural Durability (mating cycles max) 30 First Mate / Last Break No Flammability 94V-0 Glow-Wire Capable No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Mated Height 8.50mm Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Net Weight 0.472/g

Number of Rows Orientation Vertical PC Tail Length 3.30mm **PCB Locator** No **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 2.00mm Pitch - Termination Interface 2.00mm Polarized to Mating Part Yes Polarized to PCB No Shrouded Partial Stackable Nο

Temperature Range - Operating -40° to +105°C
Termination Interface: Style Through Hole

No

Surface Mount Compatible (SMC)



**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ECHA\_01\_2020 (16

January 2020 <u>Halogen-Free</u>

**Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

35362 Series

**Mates With** 

35507 Sherlock Wire-to-Board Housing

Use With

502128000 Terminal

**Electrical** 

Current - Maximum per Contact 2.0A Voltage - Maximum 125V

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-35362-001-001 Product Specification PS-35507-003-001

Sales Drawing SD-35362-002-001, SD-35362-002-002

This document was generated on 02/16/2020

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION