

This document was generated on 03/06/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0022162020			
Status:	Active			
Overview:	KK® Interconnect S	ystem - Molex		E E
	KK 254 PC Board Connector, Right-Angle, End-to-End Stackable, 0.38µm Gold (Au) Selective, 2 Circuits			C A A
			-	
Documents:				
<u>3D Model</u>		Product Specification PS-10-07-001 (PDF)		
<u> 3D Model (PDF)</u>		Packaging Specification PK-44646-001-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Sariaa imaa	Deference only
Agency Certification			- Series Inag	e - Reference only
CSA		LR19980	EU ELV	
UL		E29179	Not Relevant	
OL		E29179	NOL Relevant	
General			EU RoHS	<u>China RoHS</u>
Product Family		PCB Receptacles	Compliant	
Series		4455	REACH SVHC	
Application		Board-to-Board, Signal	Not Contained Per	_
Overview		KK® Interconnect System - Molex	ECHA_01_2020 (1	6
Product Name		KK 254	January 2020	
UPC		800754931793	Halogen-Free	
			Status	
Physical			Low-Halogen	
Circuits (Loaded)		2		on, please visit <u>Contact U</u>
Circuits (maximum)		2		n, please visit <u>contact of</u>
Color - Resin		Natural (White)	China ROHS	Green Image
Flammability		94V-0	ELV	Not Relevant
Glow-Wire Capable		No	RoHS Phthalates	Not Contained
Guide to Mating Part		No		
Keying to Mating Part		None		
Lock to Mating Part		No		
Material - Metal		Brass	Search Parts in this Series	
Material - Plating Mating		Gold	4455 Series	
Material - Plating Termi		Tin		
Material - Resin		Nylon	Mates With	
Net Weight		0.221/g	KK Header 4094	, <u>42376</u> , <u>42375</u> , <u>42377</u> ,
Number of Rows		1	4030, 171856, 1	
Orientation		Right Angle		
PC Tail Length		3.35mm		
PCB Locator		No		
PCB Retention		None		
PCB Thickness - Reco	mmended	1.60mm		
Packaging Type		Tray		
Pitch - Mating Interface		2.54mm		
Pitch - Termination Inte		2.54mm		
Plating min - Mating		0.381µm		
Plating min - Terminatio	n	2.540µm		
Polarized to PCB	JII	Yes		
	Derating			
Temperature Range - Operating Termination Interface: Style		See Product Specification		
	Style	Through Hole		
Electrical				
Current Meximum per	O and a at	2 5 4		

2.5A

500V

No

Current - Maximum per Contact Grounding to PCB Voltage - Maximum

Solder Process Data

Duration at Max. Process Temperature (seconds)005Lead-freeProcess CapabilityWAVEMax. Cycles at Max. Process Temperature001Process Temperature max. C235

Material Info Engineering Number

A-4455-AZ02A(208)

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-44646-001-001 PS-10-07-001 SDA-4455-001, SDA-4455-002

This document was generated on 03/06/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION