

413B



Heavy Duty Flux Remover

413B Heavy Duty Flux Remover is specially formulated to dissolve and remove the most stubborn, encrusted, hard, baked-on fluxes and residues left on parts after soldering. It penetrates quickly to remove non-ionic and ionic contaminants left on the non-component sides of circuit boards. It can also work aggressively on isolated and hard-to-reach areas that require spot cleaning. It is also available in aerosol format.

413B is the best flux cleaner for removing rosin, non-rosin, no-clean fluxes, non-ionic and ionic contamination.

For plastic safe versions, visit 4050A and 4140A flux removers.

Read the product SDS before using this product (downloadable at www.mgchemicals.com).



Features & Benefits

- RoHS Compliant
- Quickly dissolves burnt-on flux
- Fast dry time
- Zero residue

Available Packaging

Cat. No.	Packaging	Net Vol.	Net Wt.
413B-425G	Aerosol	498 mL	425 g

Contact Information

MG Chemicals, 1210 Corporate Drive
Burlington, Ontario, Canada L7L 5R6

Email: support@mgchemicals.com

Phone: North America: +(1)800-340-0772

International: +(1) 905-331-1396

Europe: +(44)1663 362888

Properties

Viscosity @ 25 °C	<20.5 mm ² /s
Density	0.75-0.83 g/mL
Shelf Life	5 y
Flash Point	-18 °C
Boiling Point	≥56 °C
Auto-ignition Temperature	425 °C
Water Miscibility	Partially miscible

Storage and Handling

Store between -20 and 40 °C in a dry area, away from sunlight (see SDS).

Disclaimer

This information is believed to be accurate. It is intended for professional end-users who have the skills required to evaluate and use the data properly. M.G. Chemicals Ltd. does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[MG Chemicals:](#)

[413B-425G](#) [413B-1L](#) [413B-4L](#) [413B-20L](#)