

This document was generated on 10/25/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 67490-3220

Status: Active

Overview: Serial ATA Products

Description: 1.27mm Pitch Serial ATA Header, Reverse Type, Surface Mount, Right Angle, 7

Circuits, without Mylar, Gold (Au) Flash, Tray Package, Lead-Free

Documents:

<u>3D Model</u> <u>Product Specification PS-67490-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

Material - Plating Termination

UL E29179

General

Product Family PCB Headers

Series <u>67490</u>

Application Board-to-Board, Signal, Wire-to-Board

Comments Reverse Type|Without Mylar

Overview <u>Serial ATA Products</u>

Product Name Serial ATA UPC 822348635641

Physical

Breakaway No Circuits (Loaded) 7 Circuits (maximum) 7 Color - Resin Black Durability (mating cycles max) 50 First Mate / Last Break Yes Flammability 94V-0 **Glow-Wire Compliant** No Guide to Mating Part Yes Keying to Mating Part Yes Lock to Mating Part No Material - Plating Mating Gold

Material - Resin High Temperature Thermoplastic

Net Weight 0.600/g
Number of Rows 1


Orientation Right Angle

PCB Locator No **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.051µm Plating min - Termination 1.270µm Polarized to Mating Part No Shrouded No Stackable No

Temperature Range - Operating -35°C to +85°C Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.5A



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

67490Series

Mates With

Serial ATA Signal Connector 67489, 88755

Voltage - Maximum 15V DC

Solder Process Data

Lead-free Process Capability Reflow Capable (SMT only)

Process Temperature max. C 235

Material Info

Reference - Drawing Numbers
Electrical Model Document

Electrical Model Document EE-67490-001, EE-67490-002

Product Specification PS-67490-001 Sales Drawing SD-67490-001

This document was generated on 10/25/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION