





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMPHENOL INTERCONNECT PRODUCTS CORP. ANY REPRODUCTION OR DISCLOSURE, TO THIRD PARTIES, IN PART OR WHOLE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMPHENOL INTERCONNECT PRODUCTS CORP. IS PROHIBITED.


AIPC P/N	LENGTH "A"	WIRE AWG (REF)	NOTES	EPROM REV	ACD P/N	MANUAL SOLDER	AUTO SOLDER
624410001	1000 MM ±20 MM	30G	16	C	SF-QSFPPEXPAS-001	YES	YES
624410002	2000 MM ±40 MM	30G	16	C	SF-QSFPPEXPAS-002	YES	YES
624410003	3000 MM ±60 MM	30G	16	C	SF-QSFPPEXPAS-003	YES	YES
624410005	5000 MM ±100 MM	26G	16	C	SF-QSFPPEXPAS-005	YES	YES
624410007	7000 MM ±140 MM	26G EXD	14	C	SF-QSFPPEXPAS-007	YES	YES

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE PER EO 304427	7/13	DEC
B	REVISED PER ECN 304542	8/13	DEC
C	REVISED PER ECN 305768	9/14	DEC



- THIS DRAWING IS RESERVED FOR AMPHENOL CABLES ON DEMAND.
- TEST COMPLETED ASSEMBLIES PER AMPHENOL CS-1199. TEST ASSEMBLIES AT 10 Gbps.
- A PRE-PRINTED LABEL WITH THE INFORMATION SHOWN IN THE CABLE LABEL DETAIL IS POSITIONED WITHIN THE INDICATED AREA ON THE CABLE ASSEMBLY.
- UL LABEL MUST BE ON SHIPPING CARTON PER SUBJECT 764 OF THE UL COMPONENT WIRING HARNESS (ZPFW2) FILE #E86140. CSA LABEL MUST BE ON SHIPPING CARTON.
- PACKAGE COMPLETED ASSY IN AN APPROPRIATELY SIZED ANTI-STATIC BAG. LABEL PER BAG LABEL DETAIL.
- INSTALL DUST COVER (ITEM 10) OVER CONNECTORS PER MFG PROCESS PRIOR TO SHIPMENT TO CUSTOMER.
- MARK LABEL WITH SERIAL NUMBER. ENDICOTT LOCATION PREFIX IS 'APL'; CHINA LOCATION PREFIX IS 'APF'.
- EPROM PROGRAM PER AMPHENOL SPEC CS-1154. EPROM SERIAL No. MUST MATCH CABLE LABEL SERIAL No.
- CAUTION: ANTI-STATIC CONTROL MEASURES MUST BE OBSERVED DURING THE MANUFACTURE OF THIS ASSEMBLY.
- POT MOLD BOTH CABLE ENDS PER MFG PROCESS. USE LOCTITE 3106 TO COVER CABLE TERMINATION AREAS.
- SOLDER PER AMPHENOL CS-1186 (LEAD FREE SOLDER).
- ALL MATERIALS USED IN THE MANUFACTURE OF THIS ASSEMBLY SHALL COMPLY WITH AMPHENOL REGULATED MATERIALS SPECIFICATION CS-1152.
- SIMILAR TO AMPHENOL DRAWING 60302XXXX.
- REMOVE CBL JACKET AND WRAP ONE TURN OF COPPER TAPE (ITEM 14) OVER CBL BRAID IN AREA OF STRAIN RLF. ADD SHK TBG (ITEM 13) OVER CBL BRAID OVERLAPPING COPPER TAPE. WHEN CLOSING ADD SHK TBG (ITEM 12) OVER CBL JACKET/BRAID AND UP TO BACKSHELL.
- PERMANENTLY MARK LABEL WITH 'WEEE' LOGO AND 'CE' LOGO, REF AHSI SPEC CS-1210. A ROHS2 CERTIFICATE OF COMPLIANCE MUST BE INCLUDED IN EACH SHIPPING CARTON.
- WRAP ONE TURN OF COPPER TAPE (ITEM 16) AROUND CBL JACKET BEFORE PULLING BACK BRAID.

NOTE: DC BLOCKING CAP VALUE IS 0.1 µF  
EPROM CONNECTED TO VCCTX



**SPECIFICATION CONTROL DRAWING**

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: DECIMALS .X ±.X .XX ±.01 .XXX ±.005 ANGLES ±.5°	EAR NO. AMPH7006-004A	<b>Amphenol Interconnect Products Corp.</b> 20 Valley St. Endicott, NY, 13760	
	APPROVALS DRAWN D.CASHIMERE CHECKED	DATE 7/13	CABLE ASSEMBLY, QSFP/QSFP, PASSIVE, 100Ω, RoHS, 40 GbE-CR4
THIRD ANGLE PROJECTION	RESP ENG	SIZE DWG. NO.	REV.
	MFG ENG	D 62441XXXX	C
CAD FILE: S:\SolidWorks\PE 5 DIGIT NO\62441		SCALE 1:1	SHEET 1 OF 1

NOTES: UNLESS OTHERWISE SPECIFIED