

ZHD-SCE LOW FIRE HAZARD DIESEL RESISTANT HEAT SHRINK IDENTIFICATION SYSTEM

Technical Datasheet

TTDS-263 Revision 7 April 2017

ZHD-SCE Zero Halogen, Diesel Resistant, Heat Shrink Identification Marker Sleeves for the identification of wires and cables.

ZHD-SCE is presented as cut sleeves organised in ladder format.

Manufactured using a specially developed radiation cross-linked, zero halogen material. ZHD-SCE is designed specifically to bridge the gap for installations where the highest performance is demanded from an identification sleeve, without compromising on safety or capability.

ZHD-SCE Heat Shrink Identification Marker Sleeves are available as part of a complete identification system. The system comprises specific printers, thermal transfer ribbons and WINTOTAL software.

PAGE 1

CLASS 1 DATA CLASSIFICATION - SEE POLICY TEC-02-04

ZHD-SCE, LOW FIRE HAZARD, DIESEL RESISTANT

HEAT SHRINK CABLE IDENTIFICATION SYSTEM

Features

- Zero Halogen
- Low Toxic Fumes
- Non-flame propagating
- Resistant to key rail and industrial fluids including diesel (defined by RW-2536)
- Sleeve diameters from 2.4mm to 38.1mm
- Shrink ratio 2:1
- Pre-termination Cable Identification

Temperature Rating

• -55°C to 125°C (-67°F to 257°F)

Environmental Compliance

- No Halogens, Sulphur, Nitrogen, Phosphorus and Cadmium sources above trace level. The flame retardant used in this product does not contain melamine cyanurate
- Further information and a downloadable declaration covering RoHS and REACH compliance can be found at the 'TE Product Compliance Support Centre':

http://www.te.com/usa-en/utilities/productcompliance.html

Shelf Life

 Refer to TE document 408-121006 Cable Identification Shelf Life

Applications



Specifications / Approvals

TE Connectivity Standard	RW-2536					
Rail Standards	EN45545-2 , Hazard Classifications 1 and 2, In accordance with requirement set R22/R23					
	BS 6853 Code of practice for fire precautions in the design and construction of passenger carrying trains.					
	Interior minor use of materials of mass 100g to 500g vehicle category II					
	EN 50343 Rolling stock applications - Rolling stock - Rules for installation of cabling - Appendix H					
	NFPA 130 Standard for Fixed Guideway Transit and Passenger Rail Systems, Fire protection requirements, Interior Fire Propagation Resistance					
	Federal Railroad Administration , DOT, Appendix B to Part 238, Test Methods and Performance Criteria for the Flammability and Smoke Emission Characteristics of Materials used in Passenger Cars and Locomotive Cabs					
	SHAZAINENNSHI, Japan Railway Rolling Stock & Machinery Association 2003 Classification 'Flame Retardant' Serial number 2015-166K					

Where possible, TE has tested product as a finished item, including the print. Operational tests are followed by an assessment of mark adherence to validate fit form and function. Further details can be found in TE standard RW-2536.


PAGE 2



	Part D	Descripti	ion				
ZHD-SCE	<u>-1K</u>	<u>-4.8</u>	<u>-50</u>	<u>-S1</u>	<u>-9</u>		
						. 9	Colour
						S1	Scoring (Optional)
			L			50	Sleeve Length (mm)
						4.8	Expanded Inside Diameter (mm)
						1K	Pack size
						ZHD-SCE	Product family

Options

Pre-scoring	Perforated score to produce multiple marker sleeves from each ZHD-SCE sleeve.									
	Not scored		Code	Blank						
	Side scored		Code	SS						
	Sided scored pre-score	with one	Code	SS1						
	1 Pre-score		Code	S1						
	2 Pre-scores		Code	S2						
Packaging sizes	i ng sizes <blank></blank>			250 piece packs available for all sizes						
	1K		1000 piece reels available for all sizes up to 25.4							
	2.5K		2500 piece reels available for sizes 4.8 up to 25.4							
	5K		5000 piece reels available for sizes 2.4 and 3.2							
Colours		Yellow	White							
	Code	4	9							
		Red	Green	Blue	Orange					
	Code	2	5	6	3					



Specify product name, pack size (leave blank for 250), sleeve size (in mm), sleeve length (always 50), pre-score (leave blank if not required) and colour

Dimensions in mm (inches)

Ordering Information

Ordering description		Inside diameter				Recommended cable diameter use					
		As supplied (minimum)		After recovery (Maximum)		range					
	mm	mm inches mm inches		mm			inches				
ZHD-SCE - <pack size=""> - 2.4 - 50 - <score> - <colour></colour></score></pack>	2.4	0.094	1.19	0.047	1.27	to	1.90	0.050	to	0.075	
ZHD-SCE - <pack size=""> - 3.2 - 50 - <score> - <colour></colour></score></pack>	3.2	0.126	1.58	0.060	1.77	to	2.66	0.069	to	0.105	
ZHD-SCE - <pack size=""> - 4.8 - 50 - <score> - <colour></colour></score></pack>	4.8	0.189	2.36	0.090	2.54	to	4.06	0.100	to	0.160	
ZHD-SCE - <pack size=""> - 6.4 - 50 - <score> - <colour></colour></score></pack>	6.4	0.250	3.18	0.125	3.81	to	5.46	0.150	to	0.215	
ZHD-SCE - <pack size=""> - 9.5 - 50 - <score> - <colour></colour></score></pack>	9.5	0.375	4.75	0.187	5.59	to	8.12	0.220	to	0.320	
ZHD-SCE - <pack size=""> - 12.7 - 50 - <score> - <colour></colour></score></pack>	12.7	0.500	6.35	0.250	6.99	to 1	10.79	0.275	to	0.425	
ZHD-SCE - <pack size=""> - 19.0 - 50 - <score> - <colour></colour></score></pack>	19.0	0.730	9.53	0.375	10.16	to 1	16.25	0.400	to	0.640	
ZHD-SCE - <pack size=""> - 25.4 - 50 - <score> - <colour></colour></score></pack>	25.4	1.000	12.70	0.500	14.29	to 2	21.59	0.563	to	0.850	
ZHD-SCE - 38.1 - 50 - <score> - <colour></colour></score>	38.1	1.500	19.05	0.750	20.95	to 3	33.02	0.825	to	1.300	

CLASS 1 DATA CLASSIFICATION - SEE POLICY TEC-02-04



PAGE 3



1000

Color

Markers

-

Printer TE3124

Printer Information

Print quality and print performance can only be guaranteed when specific TE printer and ribbons are used.

The current list of printers and ribbons can be found in TE document 411-121005 'Identification Printer Product Ribbon Matrix'. This document can be found in 'Access Our Tools':

http://www.te.com/usa-en/utilities/access-product-tools-and-resources.html



Qty

1

WINTOTAL software, available to download for a 14 day evaluation period from the Identification Printer Software page:

http://www.te.com/usa-en/products/identification-labeling/ printers-software.html

Contact a TE representative for further information



www.te.com/rail

New C Set

Selected Set

1

2

3

4

Open Save Set As

ected Product

Name ZHD-SCE 024-50

] 🔍 🕼 🚺 🕵 👖

Font 10 pt. Arial

HEBREW - עברית

CHINESE - 中国

THAI - ไทย

BENGALI - বাঙালি

Lines Size 1. 50.0 x 5.0 mm

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2017 TE Connectivity Ltd. family of companies All Rights Reserved.

PAGE 4

CLASS 1 DATA CLASSIFICATION - SEE POLICY TEC-02-04



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

ZHD-SCE-1K-4.8-50-4 ZHD-SCE-1K-9.5-50-S1-4 ZHD-SCE-1K-12.7-50-9 ZHD-SCE-3.2-50-4 ZHD-SCE-1K-3.2-50-S1-9 ZHD-SCE-38.1-50-S1-4 ZHD-SCE-1K-2.4-50-9 ZHD-SCE-6.4-50-4 ZHD-SCE-1K-19.0-50-S1-4 ZHD-SCE-5K-4.8-50-S1-4 ZHD-SCE-19.0-50-4 ZHD-SCE-9.5-50-9 ZHD-SCE-2.4-50-9 ZHD-SCE-19.0-50-S1-4 ZHD-SCE-5K-2.4-50-4 ZHD-SCE-9.5-50-4 ZHD-SCE-1K-3.2-50-S1-4 ZHD-SCE-12.7-50-4 ZHD-SCE-5K-3.2-50-4 ZHD-SCE-1K-2.4-50-S1-4 ZHD-SCE-1K-4.8-50-S1-9 ZHD-SCE-1K-4.8-50-9 ZHD-SCE-12.7-50-S1-9 ZHD-SCE-6.4-50-S1-4 ZHD-SCE-38.1-50-4 ZHD-SCE-9.5-50-S1-4 ZHD-SCE-2.4-50-4 ZHD-SCE-4.8-50-S1-4 ZHD-SCE-1K-3.2-50-4 ZHD-SCE-4.8-50-S1-9 ZHD-SCE-12.7-50-S1-4 ZHD-SCE-1K-6.4-50-9 ZHD-SCE-1K-6.4-50-S1-9 ZHD-SCE-1K-3.2-50-9 ZHD-SCE-1K-19.0-50-4 ZHD-SCE-2.4-50-S1-4 ZHD-SCE-2.5K-6.4-50-S1-4 ZHD-SCE-5K-2.4-50-S1-9 ZHD-SCE-1K-25.4-50-S1-9 ZHD-SCE-1K-12.7-50-4 ZHD-SCE-5K-3.2-50-9 ZHD-SCE-12.7-50-9 ZHD-SCE-1K-25.4-50-4 ZHD-SCE-5K-3.2-50-S1-9 ZHD-SCE-1K-6.4-50-S1-4 ZHD-SCE-1K-2.4-50-S1-9 ZHD-SCE-1K-25.4-50-S1-4 ZHD-SCE-1K-12.7-50-S1-9 ZHD-SCE-1K-6.4-50-4 ZHD-SCE-1K-2.4-50-4 ZHD-SCE-0.5K-38.1-50-S1-4 ZHD-SCE-5K-2.4-50-9 ZHD-SCE-1K-12.7-50-S1-4 ZHD-SCE-5K-3.2-50-S1-4 ZHD-SCE-4.8-50-9 ZHD-SCE-1K-25.4-50-9 ZHD-SCE-0.5K-38.1-50-9 ZHD-SCE-19.0-50-9 ZHD-SCE-2.5K-4.8-50-4 ZHD-SCE-3.2-50-S1-4 ZHD-SCE-3.2-50-9 ZHD-SCE-25.4-50-S1-4 ZHD-SCE-25.4-50-4 ZHD-SCE-1K-9.5-50-9 ZHD-SCE-1K-4.8-50-S1-4 ZHD-SCE-25.4-50-9 ZHD-SCE-5K-2.4-50-S1-4 ZHD-SCE-2.5K-4.8-50-S1-4 ZHD-SCE-1K-9.5-50-4 ZHD-SCE-1K-19.0-50-9 ZHD-SCE-1K-19.0-50-S1-9 ZHD-SCE-3.2-50-S1-9 ZHD-SCE-38.1-50-9 ZHD-SCE-6.4-50-9 ZHD-SCE-1K-9.5-50-S1-9 ZHD-SCE-4.8-50-4