


## Interface transceiver of RS-232 standard with one supply voltage

IC HGX232 is purposed for application in high-performance information processing systems and control devices of wide application.

Input voltage levels are compatible with standard CMOS levels.

- Output voltage levels are compatible with input levels of C-MOS, N-MOS and TTL integrated circuits.
- Supply voltage range from 2.0 to 6.0 V.
- Low input current: 1.0 mA; 0.1 mA at T = 25 °C.
- Output current 24 mA.
- Latching current not less than 450 mA at T = 25°C
- Tolerable value of static potential not less than 2000V



### IC marking in package

HGX232EXN DIP

HGX232EXM SOIC


### Truth table

| Inputs                            | Outputs                             |
|-----------------------------------|-------------------------------------|
| R <sub>IN</sub> , T <sub>IN</sub> | R <sub>OVT</sub> , T <sub>OVT</sub> |
| H                                 | L                                   |
| L                                 | H                                   |

Note -  
H – voltage high level;  
L – low voltage level

For all packages

### Pin symbols in package



### ORDERING INFORMATION

| DEVICE       | Package Type | MARKING | Packing | Packing Qty  |
|--------------|--------------|---------|---------|--------------|
| HGX232ECN    | DIP16L       | HGX232  | TUBE    | 1000pcs/box  |
| HGX232ECM/TR | SOP16L       | HGX232  | REEL    | 2500pcs/reel |
| HGX232EIN    | DIP16L       | HGX232  | TUBE    | 1000pcs/box  |
| HGX232EIM/TR | SOP16L       | HGX232  | REEL    | 2500pcs/reel |

**Table of pin description**


| Pin No. | Symbol            | Pin name   |
|---------|-------------------|--|
| 01      | C1+               | Output of external capacitance of positive voltage multiplier unit |
| 02      | V+                | Output of positive voltage of multiplier unit                      |
| 03      | C1-               | Output of external capacitance of positive voltage multiplier unit |
| 04      | C2+               | Output of external capacitance of negative voltage multiplier unit |
| 05      | C2-               | Output of external capacitance of negative voltage multiplier unit |
| 06      | V-                | Output of negative voltage of multiplier unit                      |
| 07      | T2 <sub>OUT</sub> | Output of transmitter data (levels RS – 232)                       |
| 08      | R2 <sub>IN</sub>  | Input of receiver data (levels RS – 232)                           |
| 09      | R2 <sub>OUT</sub> | Output of receiver data (levels TTL/KMOS)                          |
| 10      | T2 <sub>IN</sub>  | Input of transmitter data (levels TTL/KMOS)                        |
| 11      | T1 <sub>IN</sub>  | Input of transmitter data (levels TTL/KMOS)                        |
| 12      | R1 <sub>OUT</sub> | Output of receiver data (levels TTL/KMOS)                          |
| 13      | R1 <sub>IN</sub>  | Input of receiver data (levels RS – 232)                           |
| 14      | T1 <sub>OUT</sub> | Output of transmitter data (levels RS – 232)                       |
| 15      | GND               | Common output  |
| 16      | V <sub>CC</sub>   | Supply output of voltage source                                    |

**Maximum conditions**

| Symbol           | Parameter   | Rate                  |              | Unit |
|------------------|---|-----------------------|--------------|------|
|                  |   | min                   | max          |      |
| V <sub>CC</sub>  | Supply voltage                                    | -0.3                  | 6.0          | V    |
| V+               | Transmitter high output voltage                   | V <sub>CC</sub> - 0.3 | 14           |      |
| V-               | Transmitter low output voltage                    | -0.3                  | -14          |      |
| V <sub>TIN</sub> | Transmitter input voltage                         | -0.3                  | V+ + 0.3     |      |
| V <sub>RIN</sub> | Receiver input voltage                            | -30                   | 30           |      |
| P <sub>D</sub>   | Dissipated power<br>DIP – package<br>SO - package | -                     | 842          | mW   |
|                  |   |                       | 762          |      |
| I <sub>SC</sub>  | Output current of transmitter short circuit       | -                     | Continuously | mA   |
| T <sub>a</sub>   | Ambient temperature                               | -60                   | 150          | °C   |

**Absolute maximum conditions**

| Symbol           | Parameter                                | Rate     |                 | Unit |    |
|------------------|--|----------|-----------------|------|----|
|                  |  | min      | max             |      |    |
| V <sub>CC</sub>  | Supply voltage                           | 4.5      | 5.5             | V    |    |
| V+               | Transmitter output high voltage          | 5.0      | -               |      |    |
| V-               | Transmitter output low voltage           | -5.0     | -               |      |    |
| V <sub>TIN</sub> | Transmitter input voltage                | 0        | V <sub>CC</sub> |      |    |
| V <sub>RIN</sub> | Receiver input voltage                   | -30      | 30              |      |    |
| I <sub>SC</sub>  | Transmitter short circuit output current | -        | ±60             | mA   |    |
| T <sub>a</sub>   | Ambient temperature                      | HGX232EC | 0               | 70   | °C |
|                  |  | HGX232EI | -40             | 85   |    |




| Symbol                                   | Parameter                         | Test conditions   | Rate |           |                    |           | Unit   |
|--|-----------------------------------|---|------|-----------|--------------------|-----------|--------|
|  |                                   |   | 25°C |           | от -40 °C до 85 °C |           |        |
|  |                                   |   | min  | max       | min                | max       |        |
| $I_{CC}$                                 | Consumption current static        | $V_{CC} = 5.5 \text{ V}$<br>$V_{IL} = 0 \text{ V}$  | -    | 10.0      | -                  | 14.0*     | mA     |
| <b>Receiver electrical parameters</b>    |                                   |   |      |           |                    |           |        |
| $V_h$                                    | Hysteresis voltage                | $V_{CC} = 5.0 \text{ V}$  | 0.2  | 0.9       | 0.2                | 1.0       | V      |
| $V_{On}$                                 | On (operation) voltage            | $V_O \leq 0.1 \text{ V}$<br>$I_{OL} \leq 20 \text{ mA}$   | -    | 2.4       | -                  | 2.3       |        |
| $V_{off}$                                | Off (dropout) voltage             | $V_O \geq V_{CC} - 0.1 \text{ V}$<br>$I_{OH} \leq -20 \text{ mA}$   | 0.8  | -         | 0.9                | -         |        |
| $V_{OL}$                                 | Output low voltage                | $I_{OL} = 3.2 \text{ mA}$<br>$V_{CC} = 4.5 \text{ V}$<br>$V_{IH} = 2.4 \text{ V}$   | -    | 0.3       | -                  | 0.4       |        |
| $V_{OH}$                                 | Output high voltage               | $I_{OH} = -1.0 \text{ mA}$<br>$V_{CC} = 4.5 \text{ V}$<br>$V_{IL} = 0.8 \text{ V}$  | 3.6  | -         | 3.5                | -         |        |
| $R_i$                                    | Input resistance                  | $V_{CC} = 5.0 \text{ V}$  | 3.0  | 7.0       | 3.0                | 7.0       | kOhm   |
| <b>Transmitter electrical parameters</b> |                                   |   |      |           |                    |           |        |
| $V_{OL}$                                 | Output low voltage                | $V_{CC} = 4.5 \text{ V}$<br>$V_{IH} = 2.0 \text{ V}$<br>$R_L = 3.0 \text{ kOhm}$  | -    | -5.2      | -                  | -5.0      | V      |
| $V_{OH}$                                 | Output high voltage               | $V_{CC} = 4.5 \text{ V}$<br>$V_{IL} = 0.8 \text{ V}$<br>$R_L = 3.0 \text{ kOhm}$  | 5.2  | -         | 5.0                | -         |        |
| $I_{IL}$                                 | Input low current                 | $V_{CC} = 5.5 \text{ V}$<br>$V_{IL} = 0 \text{ V}$  | -    | -1.0      | -                  | -10.0     | mA     |
| $I_{IH}$                                 | Input high current                | $V_{CC} = 5.5 \text{ V}$<br>$V_{IH} = V_{CC}$   |      | 1.0       |                    | 10.0      |        |
| SR                                       | Speed of output front change      | $V_{CC} = 5.0 \text{ V}$<br>$C_L = 50 - 1000 \text{ pF}$<br>$R_L = 3.0 - 7.0 \text{ kOhm}$  | 3.0  | 30        | 2.7                | 27        | V/mks  |
| $R_O$                                    | Output resistance                 | $V_{CC} = V_+ = V_- = 0 \text{ V}$<br>$V_O = \pm 2 \text{ V}$   | 350  | -         | 300                | -         | Ohm    |
| $I_{SC}$                                 | Short circuit output current      | $V_{CC} = 5.5 \text{ V}$<br>$V_O = 0 \text{ V}$<br>$V_I = V_{CC}$<br>$V_I = 0 \text{ V}$  |      | -50<br>50 |                    | -60<br>60 | mA     |
| ST                                       | Speed of information transmission | $V_{CC} = 4.5 \text{ V}$<br>$C_L = 1000 \text{ pF}$<br>$R_L = 3.0 \text{ kOhm}$<br>$t_w = 7 \text{ mks}$ (for extreme - $t_w = 8 \text{ mks}$ ) | 140  | -         | 120                | -         | kbit/c |

| Symbol                       | Parameter   | Test conditions  | Rate  |      |                      |      | Unit |
|------------------------------|---|--|-------|------|----------------------|------|------|
|                              |   |  | 25 °C |      | from -40 °C to 85 °C |      |      |
|                              |   |  | min   | max  | min                  | max  |      |
| $t_{PHLR}$<br>( $t_{PLHR}$ ) | Signal propagation delay time when switching on (off) | $V_{CC} = 4.5 V$<br>$C_L = 150 pF$<br>$V_{IL} = 0 V$<br>$V_{IH} = 3.0 V$<br>$t_{LH} = t_{HL} \leq 10 ns$                       | -     | 9.7  | -                    | 10   | mks  |
| $t_{PHLT}$<br>( $t_{PLHT}$ ) | Signal propagation delay time when switching on (off) | $V_{CC} = 4.5 V$<br>$C_L = 2500 pF$<br>$V_{IL} = 0 V$<br>$V_{IH} = 3.0 V$<br>$R_L = 3 k\Omega$<br>$t_{LH} = t_{HL} \leq 10 ns$ |       | 5.0* |                      | 6.0* |      |

### Capacitance

| Symbol   | Parameter           | $V_{CC}$ ,<br>V | Rate | Unit |
|----------|---------------------|-----------------|------|------|
| $C_{IN}$ | Input capacitance   | 5.0             | 9.0  | pF   |
| $C_{PD}$ | Dynamic capacitance |                 | 90   |      |

Timing diagram when measuring IC dynamic parameters



**Figure 3**




Figure 4




Figure 5





Figure 6


**PACKAGE**

**SOP16**



| Dimensions In Millimeters |       |       |          |           |       |
|---------------------------|-------|-------|----------|-----------|-------|
| Symbol :                  | Min : | Max : | Symbol : | Min :     | Max : |
| A                         | 1.225 | 1.570 | D        | 0.400     | 0.950 |
| A1                        | 0.100 | 0.250 | Q        | 0°        | 8°    |
| B                         | 9.800 | 10.00 | a        | 0.420 TYP |       |
| C                         | 5.800 | 6.250 | b        | 1.270 TYP |       |
| C1                        | 3.800 | 4.000 |          |           |       |

**DIP16**



| Dimensions In Millimeters |        |        |          |           |       |
|---------------------------|--------|--------|----------|-----------|-------|
| Symbol :                  | Min :  | Max :  | Symbol : | Min :     | Max : |
| A                         | 6.100  | 6.680  | L        | 0.500     | 0.800 |
| B                         | 18.940 | 19.560 | a        | 1.524 TYP |       |
| D                         | 8.200  | 9.200  | b        | 0.889 TYP |       |
| D1                        | 7.42   | 7.820  | c        | 0.457 TYP |       |
| E                         | 3.100  | 3.550  | d        | 2.540 TYP |       |
| L                         | 0.500  | 0.800  |          |           |       |

## Important statement:

Huaguan Semiconductor Co,Ltd. reserves the right to change the products and services provided without notice. Customers should obtain the latest relevant information before ordering, and verify the timeliness and accuracy of this information.

Customers are responsible for complying with safety standards and taking safety measures when using our products for system design and machine manufacturing to avoid potential risks that may result in personal injury or property damage.

Our products are not licensed for applications in life support, military, aerospace, etc., so we do not bear the consequences of the application of these products in these fields.

Huaguan Semiconductor Co,Ltd. the performance of the semiconductor products produced by the company can reach the performance indicators that can be applied at the time of sales. the use of testing and other quality control technologies is limited to the quality assurance scope of Huaguan semiconductor. Not all parameters of each device need to be tested. The above documents are for reference only, and all are subject to the physical parameters.

Our documentation is only permitted to be copied without any tampering with the content, so we do not accept any responsibility or liability for the altered documents.