

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NFZ2MSD900SN10# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD900SN10%23

NFZ2MSD900SN10#

"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > NFZ2MSD900SN10L





Features

1.2 max.

án mmù

1.6±0.2

 NFZ2MSD_SN is a noise filter designed for noise suppression of audio lines such as PC and AV equipment.
Can be used in high current circuits due to its low DC resistance.

3. Low magnetic flux leakage with magnetically shielded structure.

4. Meets 125°C maximum operating temperature.

Applications

Other Usage For general	
-------------------------	--

Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of NFZ2MSD900SN10# from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD900SN10%23

NFZ2MSD900SN10#

"#" indicates a package specification code.

Specifications

Shape	SMD	Operating Temperature Range (Self- temperature rise is included)	-40℃ to 125℃
Size Code (in mm)	2016		
Size Code (in inch)	0806		
Length	2.0mm		
Length Tolerance	±0.2mm		
Width	1.6mm		
Width Tolerance	±0.2mm		
Thickness	1.2mm		
Thickness Tolerance	max.		
Rated Current	2A		
Operating Temperature Range	-40°C to 85°C		
Mass(typ.)	0.0188g		
Number of Circuit	1		
DC Resistance(max.)	95mΩ		
DC Resistance	95mΩ max.		
Impedance (at 10MHz)	90Ω		
Impedance (at 10MHz) Tolerance	±30%		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of NFZ2MSD900SN10# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD900SN10%23

NFZ2MSD900SN10#

"#" indicates a package specification code.




INNOVATOR IN ELECTRON




Max. current (DC, AC) as function of product temperature (derating curve).





Impedance-Frequency Characteristics

Derating of Rated Current



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: NFZ2MSD900SN10L