

Ultrane 510

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Water-based polymer
- **Length (cm)** 22-27
- **Wrist** Knitted wrist
- **Colour/Color** Green
- **Interior finish** Seamless textile support
- **Exterior finish** Ventilated back
- **Size / EAN** 6 7 8 9 10 11
- **Packaging** 1 pair/bag - 12 pairs/bag - 96 pairs/carton
- **Complementary information** Silicone and DMF Free
Oeko-tex®



PERFORMANCE RESULTS

Certification category 2



4131

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**RADIOACTIVE
CONTAMINATION
EN 421**



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance

For more details: www.mapa-pro.com

Ultrane 510

DESCRIPTION AND GENERAL PROPERTIES

- Breathable coating to have a better comfort in use
- Anatomical shape: close fit for precision
- Durable for a long-wear

MAIN FIELDS OF USE

Automotive/mechanical industry

- Precision mechanical work
- Precision assembly
- Automotive assembly
- Mechanical maintenance
- Assembly of small parts
- Fitting small screws and fasteners

Electronics

- Assembly of electrical components
- Microprocessor handling

Cosmetics and Pharmaceutical industry

- Cosmetics preparation
- Medicine manufacturing

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the tests performed in the laboratory.
- It is recommended to not use them next to moving machinery
- It is not recommended for persons sensitised to natural latex(wrist with elastic natural rubber).
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.

Storage conditions

Store the gloves in their original packaging protected from heat, light and humidity.

Laundering conditions

Caution : using the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/04/16/0397

- Issued by the notified body nr

CTC - 4 rue Hermann Frenkel- 69367 Lyon cedex 07 - France
0075